

## **Table of Contents**

Abstract

Abstrak

Acknowledgements

1.0	Introduction	1
1.1	General System	3
1.2	Advantages Of Fiber Optical Communication	5
1.2.1	Bandwidth	5
1.2.2	Small Size And Weight	5
1.2.3	Electrical Insulator	6
1.2.4	Security Of Signal	6
1.2.5	Less Interference	6
1.2.6	Low Transmission Loss	6
1.2.7	Toughness And Flexibility	7
1.2.8	Reliability And Maintenance	7
1.2.9	Low Cost	7
1.3	Aim Of The Thesis	7
1.4	References	9
2.0	Theoretical Aspects Of An Optical Communication System	10
2.1	Detectors	10
2.1.1	Coherent Detection	12
2.1.2	Comparison Of Sensitivities	17
2.2	Qualitative Analysis	23

2.3	Noise	25
2.3.1	Thermal Noise	25
2.3.2	Dark Current Noise	26
2.3.3	Quantum Noise	26
2.3.3.1	Digital Signaling Quantum Noise	27
2.3.4	Phase Noise	27
2.3.5	Summary Of Optical Receiver Sensitivity	34
2.4	References	35
3.0	Component Used In Optical Coherent Communication	
3.1	Introduction	35
3.2	Light Source	35
3.3	Variable Aperture	37
3.4	Polarizer	38
3.5	Waveplate	39
3.5.1	Half-Wave Plate	40
3.5.2	Quarter-Wave Plate	41
3.6	Beam Splitter	41
3.7	Mirror	43
3.8	Piezoelectric	43
3.9	Power / Energy Meter	44
3.10	Oscilloscope	46
3.11	Signal Generator	47
3.12	Receiver	49

<b>4.0</b>	<b>PSK Communication</b>	
<b>4.1</b>	<b>Introduction</b>	<b>53</b>
<b>4.2</b>	<b>Mode of Encoding</b>	<b>55</b>
<b>4.3</b>	<b>Mode of Detection</b>	<b>56</b>
<b>4.4</b>	<b>Mode of Communication</b>	<b>56</b>
<b>4.5</b>	<b>Medium</b>	<b>57</b>
<b>4.6</b>	<b>Phase Shift Keying (PSK)</b>	<b>57</b>
<b>4.7</b>	<b>Encoding And Decoding For Narrow Band PSK Transmission</b>	
	<b>Via Optical Fibre</b>	<b>61</b>
<b>4.8</b>	<b>Heterodyne Transmission DPSK System Experiment</b>	
	<b>At 1.4 Gbit/s</b>	<b>62</b>
<b>4.9</b>	<b>Fibre Distribution For 80 Compressed Digital Video Channel</b>	
	<b>Using Differential QPSK</b>	<b>62</b>
<b>4.10</b>	<b>1550-nm Transmission Digitally Modulated 28-GHz</b>	
	<b>Sub-carriers Over 77km Of Non-Dispersion Shifted Fiber</b>	<b>63</b>
<b>4.11</b>	<b>10-Gbps x 4-ch WDM Transmission Experiment over 2400 km</b>	
	<b>Dispersion Shifted Fibre Using DPSK Detection Scheme</b>	<b>64</b>
<b>4.12</b>	<b>4-Gb/s Heterodyne Transmission Experiments Using DPSK</b>	
	<b>And Other Modulation</b>	<b>64</b>
<b>4.13</b>	<b>Novel Technique For High-Capacity 60 GHz Fibre-Radio</b>	
	<b>Transmission Systems</b>	<b>65</b>
<b>4.14</b>	<b>Atmospheric Optical Communication System Using</b>	
	<b>Sub-Carrier PSK Modulation</b>	<b>66</b>

4.15	Ultimate Capacity Of A Return-Channel Laser Diode In Transporting Multi-Channel Bust QPSK/16QAM Signals	69
4.16	The Impact Of Raleigh Back Scattering Induced Noise On QPSK Transmission With Fabry-Perot Laser	70
4.17	Dispersion Compensation For Homodyne Detection System Using A 10 Gb/s Optical PSK-VSB Signal	71
4.18	The Performance of a Coherent Residual Carrier PSK System Using Hybrid Carrier Phase Synchronization	72
4.19	A Method For Evaluating MPSK Performance Using M/2 PSK Signal Set	73
4.20	Novel Fiber Optic BPSK And QPSK Modulation Links	74
4.21	The Influence Of Cross-phase Modulation On Optical FDM PSK Homodyne Transmission Systems	75
4.22	Phase Noise And Polarisation State Insensitive Coherent Optical Receivers	77
4.23	A Packaging Technique For An Optical 90 <sup>0</sup> – Hybrid Balance Receiver Using A Planar Lightwave Circuit	79
4.24	Phase Noise Innsensitive Multilevel Polarisation Shift Keying Based On Quadrature Amplitude-Modulation Mapping In Coherent Optical Systems	80
4.25	Reference	81
5.0	Detection Techniques	
5.1	Introduction	86

5.2	Mach Zehnder Technique	86
5.3	Michelson Technique	89
6.0	Coherent PSK Communication System Design	
6.1	Introduction	102
6.2	All Optical Two-Channel PSK Communication, Using A Single Light Source	103
6.2.1	Transmitter Design Using Mach Zehnder Technique	103
6.2.2	Receiver	106
6.2.3	Receiver Design Using Michelson Interferometer Technique	108
6.2.4	Results	112
6.3	All Optical Single Channel, Two-Ways PSK Communication By Using Single Light Source	123
6.3.1	Results	128
6.4	All Optical Single Channel, Two-Way Communication, Utilising A Single Light Source Without A Time Delay Unit	135
6.4.1	System Design Using Michelson Technique	135
6.4.2	System Design Using The Mach Zehnder Technique	138
6.4.3	Results	140
6.5	All Optical Two Channels, Two Ways PSK Communication, By Using Single Light Source	149
6.5.1	Experiment	150
6.5.2	Results	153

6.6	Coherence Length Dependent Multi-Channel PSK Communication System Using A Single Light Source	165
6.6.1	Experiment	167
6.6.2	Results	170
6.7	Reference	180
7.0	Conclusion	181
7.1	Further Work	184
7.2	Reference	186
Appendix A		187
Appendix B		190