

REFERENCES

REFERENCES

- Abdelaziz. M. and Ghannam. M.M. (2010). *Influence of titanium chloride addition on the optical and dielectric properties of PVA films*. Physica B: Condensed Matter 405, 958-964.
- Aldon. L., Van Thournout. M., Strobel. P., Isnard. O., Olivier-Fourcade. J. and Jumas. J.-C. (2006). *Neutron diffraction and Mössbauer studies of iron substituted $\text{Li}_2\text{Ti}_3\text{O}_7$ of ramsdellite-type as negative electrode for Li-ion accumulator*. Solid State Ionics 177, 1185-1191.
- Allen. J.L., Jow. T.R. and Wolfenstine. J. (2006). *Low temperature performance of nanophase $\text{Li}_4\text{Ti}_5\text{O}_{12}$* . Journal of Power Sources 159, 1340-1345.
- Amaral. F., Rubinger C.P.L., Henry, F., Costa. L.C., Valente. M.A. and Barros-Timmons. A. (2008). *Dielectric properties of polystyrene-CCTO composite*. Journal of Non-Crystalline Solids 354, 5321-5322.
- Amatucci. G.G., Badway. F., Pasquier. A.D. and Zheng. T. (2001). *An asymmetric hybrid nonaqueous energy storage cell*. Journal of the Electrochemical Society 148, A930-A939.
- Ayesh. S.H. (2008). *Dielectric relaxation and thermal stability of polycarbonate doped with MnCl_2 salt*. Journal of Thermoplastic Composite Materials 21, 309-322.
- Azuma. B., Imoto. I., Yamada. S. and Sekai. K. (1999). *Advanced carbon anode materials for lithium ion cells*. Journal of Power Sources 81-82, 1-7.
- Baba. M., Kumagai. N., Kobayashi. H., Nakano. O. and Nishidate. K. (1999). *Fabrication and electrochemical characteristics of all-solid-state lithium-ion batteries using V_2O_5 thin films for both electrodes*. Electrochemical Solid State Letters 2, 320-322.
- Bach. S., Pereira-Ramos. J.P. and Baffier. N. (1999). *Electrochemical properties of sol-gel $\text{Li}_{4/3}\text{Ti}_{5/3}\text{O}_4$* . Journal of Power Sources 81-82, 273-276.
- Barik. S.K., Choudhary. R.N.P. and Mahapatra P.K. (2008). *Structural and electrical properties of $\text{Na}_{1/2}\text{Gd}_{1/2}\text{TiO}_3$ nanoceramics*. Journal of Alloys and Compound 459, 35-40.
- Basu. S. (1999). *Early studies on anodic properties of lithium intercalated graphite*. Journal of Power Sources 81-82, 200-206.
- Bhajantri. R.F., Ravindrachary. V., Harisha. A., Crasta. V., Nayak. S.P. and Poojary. B. (2006). *Microstructural studies on BaCl_2 doped poly (vinyl alcohol)*. Polymer 47, 3591-3598.

- Bhat. N.V., Nate. M.M., Kurup. M.B. and Bambole, V.A. (2007). *Structural changes in chlorine implanted poly(vinyl alcohol) films*. Nuclear Instruments and Methods in Physics Research, Section B: Beam Interactions with Materials and Atoms 262, 39-45.
- Bohnke. O., Duroy. H., Fourquet. J-L., Ronchetti. S. and Mazza. D. (2002). *In search of the cubic phase of the Li⁺ ion-conducting perovskite La_{2/3-x}Li_{3x}TiO₃: structure and properties of quenched and in situ heated samples*. Solid State Ionics 149, 217-226.
- Bourderau. S., Brousse. T. and Schleich. D.M. (1999). *Amorphous silicon as a possible anode material for Li-ion batteries*. Journal of Power Sources 81-82, 233-236.
- Boyce. J.B. and Mikkelsen Jr. J.C. (1979). *Anisotropic conductivity in a channel-structured superionic conductor: Li₂Ti₃O₇*. Solid State Communications 31, 741-745.
- Cao. G.S., Zhao. X.B., Li. T. and Lu. C. P. (2001). *Zn₄Sb₃(---C₇) powders as a potential anode material for lithium-ion batteries*. Journal of Power Sources 94, 102-107.
- Chanmal. C.V. and Jog. J.P. (2008). *Dielectric relaxations in PVDF/BaTiO₃ nanocomposites*. eXPRESS Polymer Letters 2, 294-301.
- Chen. C.H., Vaughey. J.T., Jansen. A.N., Dees. D.W., Kahaian. A.J., Goacher. T. and Thackeray. M.M. (2001). *Studies of Mg-Substituted Li_{4-x}Mg_xTi₅O₁₂ spinel electrodes (0 ≤ x ≤ 1) for lithium batteries*. Journal of the Electrochemical Society 148, A102-A104.
- Chen. J.M., Yao. C.Y., Cheng. C.H., Hurng. W.M. and Kao T.H. (1995). *Cokes as negative electrodes in secondary batteries*. Journal of Power Sources 54, 494-495.
- Chen. F., Li. R., Hou. M., Liu. L., Wang. R. and Deng. Z. (2005). *Preparation and characterization of ramsdellite Li₂Ti₃O₇ as an anode materials for symmetric supercapacitors*. Electrochimica Acta 51, 61-65.
- Chen. Y-C., Chen. J-M., Huang. Y-H., Lee. Y-R. and Shih. H.C. (2007). *Size effect of tin oxide nanoparticles on high capacity lithium battery anode materials*. Surface and Coatings Technology 202, 1313-1318.
- Chen. Y-F., Lee. C-Y., Yeng. M-Y. and Chiu. H-T. (2003). *The effect of calcination temperature on the crystallinity of TiO₂ nanopowders*. Journal of Crystal Growth 247, 363-370.
- Courtney. I.A., Dunlap. R.A. and Dahn. J.R. (1999). *In-situ ¹¹⁹Sn Mössbauer effect studies of the reaction of lithium with SnO and SnO:0.25 B₂O₃:0.25 P₂O₅ glass*. Electrochimica Acta 45, 51-58.
- D'Andrea. S., Panero. S., Reale. P. and Scrosati. B. (2000). *Advanced lithium ion battery materials*. Ionics 6, 127-132.
- Deschamps. M. and Yazami. R. (1997). *Great reversible capacity of carbon lithium electrode in solid polymer electrolyte*. Journal of Sources 68, 236-238.
- Dompablo. M.E.A., Várez. A. and García-Álvarado. F. (2000). *Structural study of electrochemically obtained Li_{2+x}Ti₃O₇*. Journal of Solid State Chemistry 153, 132-139.

- Ganesan. M., Dhananjeyan. M.V.T., Sarangapani. K.B. and Renganathan. N.G. (2007). *Solid state rapid quenching method to synthesize micron size $\text{Li}_4\text{Ti}_5\text{O}_{12}$* . Journal of Electroceramics 18, 329-337.
- Gao. J., Jiang. C., Ying. J. and Wan. C. (2006). *Preparation and characterization of high-density spherical $\text{Li}_4\text{Ti}_5\text{O}_{12}$ anode materials for lithium secondary batteries*. Journal of Power Sources 155, 364-367.
- Gautam. A and Ram. S. (2010). *Preparation and thermomechanical properties of Ag-PVA nanocomposite films*. Materials Chemistry and Physics 119, 266-271.
- Guo. H., Zhao. H., Yin. C. and Qiu. W. (2006). *Si/SnSb alloy composite as high capacity anode materials for Li-ion batteries*. Journal of Alloys and Compounds 426, 277-280.
- Gocmez. H and Fujimori. H. (2008). *Synthesis and characterisation of ZrO-MgO solid solutions by citrate gel process*. Materials Science and Engineering B 148, 226-229.
- Hao. Y-J., Lai. Q-Y., Lu. J-Z., Wang. H-L., Chen. Y-D. and Ji. X-Y. (2006). *Synthesis and characterization of spinel $\text{Li}_4\text{Ti}_5\text{O}_{12}$ anode material by oxalic acid-assisted sol-gel method*. Journal of Power Sources 158, 1358-1364.
- Hao. Y., Lai. Q., Xu. Z., Liu. X. and Ji. X. (2005). *Synthesis by TEA sol-gel method and electrochemical properties of $\text{Li}_4\text{Ti}_5\text{O}_{12}$ anode materials for lithium-ion battery*. Solid State Ionics 176, 1201-1206.
- Hao. Y-J., Lai. Q-Y., Lu. J-Z. and Ji. X-Y. (2007). *Effects of dopant on the electrochemical properties of $\text{Li}_4\text{Ti}_5\text{O}_{12}$ anode materials*. Ionics 13, 369-373.
- Huang H., Kelder. E.M. and Schooman. J. (2001). *Graphite-metal oxide composites as anode for Li-ion batteries*. Journal of Power Sources 97-98, 114-117.
- Huang S.H., Wen. Z.Y., Lin. B., Han. J.D. and Xu. X.G. (2008). *The high-rate performance of the newly designed $\text{Li}_4\text{Ti}_5\text{O}_{12}/\text{Cu}$ composite anode for lithium ion batteries*. Journal of Alloys and Compounds 457, 400-403.
- Huang. S., Wen. X., Zhu. X. and Lin. Z. (2007). *Effects of dopant on the electrochemical performance of $\text{Li}_4\text{Ti}_5\text{O}_{12}$ as electrode material for lithium ion batteries*. Journal of Power Sources 165, 408-412.
- Ibrahim. D.M. and Abu-Ayana. (2008). *Preparation and characterization of ultrafine alumina via sol-gel polymeric route*. Materials Chemistry and Physics 111, 326-330.
- Idota. Y., Kubota. T., Matsufuji. A., Maekawa. Y, Miyasaka. T. (1997). *Tin-based amorphous oxide: A high-capacity lithium-ion-storage material*. Science 276, 1395-1397.
- Jansen. A.N., Kahaian. A.J., Kepler. K.D., Nelson. P.A., Amine. K., Dees. D.W., Vissers. D.R. and Thackeray. M.M. (1999). *Development of a high-power lithium-ion battery*. Journal of Power Sources 81-82, 902-905.

- Jais. U.S., Lee. W.E. and James. P.F. (1996). *Sol-gel preparation and crystallisation of barium osumilite glass*. Journal of Non-Crystalline Solids 194, 213-224.
- Ji. S., Zhang J., Wang. W., Huang. Y., Feng. Z., Zhang. Z. and Tang. Z. (2010). *Preparation and effects of Mg-doping on the electrochemical properties of spinel $\text{Li}_4\text{Ti}_5\text{O}_{12}$ as anode material for lithium ion battery*. Materials Chemistry and Physics 123, 510-515.
- Jiang. J and Dahn. J.R. (2004). *Effects of solvents and salts on the thermal stability of LiC_6* . Electrochimica Acta 49, 4599-4604.
- Jones. S.D. and Akridge. J.R. (1992). *A thin film solid state microbattery*. Solid State Ionics 53-56, 628-634.
- Ju. S.H. and Kang. Y.C. (2009). *Characteristics of spherical-shaped $\text{Li}_4\text{Ti}_5\text{O}_{12}$ anode powders prepared by spray pyrolysis*. Journal of Physics and Chemistry of Solids 70, 40-44.
- Kaczmarek. H. and Podogórski. A. (2007a). *The effect of UV-irradiation on poly (vinyl alcohol) composites with montmorillonite*. Journal of Photochemistry and Photobiology A: Chemistry 191, 209-215.
- Kaczmarek. H. and Podogórski. A. (2007b). *Photochemical and thermal behaviours of poly (vinyl alcohol)/graphite oxide composites*. Polymer Degradation and Stability 92, 939-946.
- Kanehori. K., Matsumoto. K., Miyauchi. K. and Kudo. T. (1983). *Thin film solid electrolyte and its application to secondary lithium cell*. Solid State Ionics 9-10, 1445-1448.
- Kanamura. K., Chiba. T. and Dokko. K. (2006). *Preparation of $\text{Li}_4\text{Ti}_5\text{O}_{12}$ spherical particles for rechargeable lithium batteries*. Journal of the European Ceramic Society 26, 577-581.
- Kataoka. K., Takahashi. Y., Kijima. N., Hayakawa. H., Akimoto J. and Ohshima. K-i. (2008). *A single-crystal study of the electrochemically Li-ion intercalated spinel-type $\text{Li}_4\text{Ti}_5\text{O}_{12}$* . Solid State Ionics 180, 631-635.
- Kavan. L., Procházka. J., Spitler, T.M., Kalbáč, M., Zúkalová, M., Drezen, T. and Grätzel, M. (2003). *Li insertion into $\text{Li}_4\text{Ti}_5\text{O}_{12}$ (spinel). Charge capability vs. particle size in thin-film electrodes*. Journal of the Electrochemical Society 150, A1000-A1007.
- Kim. S.H., Lee. K.H., Seong. B.S., Kim. G-H., Kim. J.S. and Yoon. Y.S. (2006). *Synthesis and structural properties of lithium titanium oxide powder*. Korean Journal of Chemical Engineering 23, 961-964.
- Kinoshita. K. and Zaghbi. K. (2002). *Negative electrodes for Li-ion batteries*. Journal of Power Sources 110, 416-423.

- Kobayashi. Y., Tanase. T., Tabata. T., Miwa. T. and Konno. M. (2008). *Fabrication and dielectric properties of the BaTiO₃-polymer nano-composite thin films*. Journal of the European Ceramic Society 28, 117-122.
- Lamastra. F.R., Bianco. A., Meriggi. A., Montesperelli. A. Nanni A. and Gusmano. G. (2008). *Nanohybrid PVA/ZrO₂ and PVA/Al₂O₃ electrospun mats*. Chemical Engineering Journal 145, Pages 169-175.
- Let. A.L., Mainwaring. D.E., Rix. C. and Murugaraj. P. (2008). *Thio sol-gel synthesis of titanium disulfide thin films and powders using titanium alkoxide precursors*. Journal of Non-Crystalline Solids 354, 1801-1807.
- Lee. J., Lee. K.J. and Jang. J. (2008). *Effect of silica nanofillers on isothermal crystallization of poly(vinyl alcohol): In-situ ATR-FTIR study*. Polymer Testing 27, 360-367.
- Livage. J., Babonneau. F., Chatry. M. and Coury. L. (1997). *Sol-gel synthesis and NMR characterization of ceramics*. Ceramic International 23, 13-18.
- Ma. S., Li. Ji., Jing X. and Wang F. (1996). *A study of cokes used as anodic materials in lithium ion rechargeable batteries*. Solid State Ionics 86-88, 911-917.
- Madarász. J., Okuya. M., Varga. P.P., Kaneko. S. and Pokol. G. (2007). *TG/DTA-EGA-MS studies on titania precursor with low content of organics for porous thin films of TiO₂*. Journal of Analytical and Applied Pyrolysis 79, 479-483.
- Majid S.R. and Arof A.K. (2007). *Electrical behavior of proton-conducting chitosan-phosphoric acid-based electrolytes*. Physica B: 390, 209-215.
- Majid S.R and Arof A.K. (2005) *Proton-conducting polymer electrolyte films based on chitosan acetate complexed with NH₄NO₃ salt*. Physica B: Condensed Matter 355, 78-82.
- Matsumura. Y., Wang. S. and Mondori. J. (1995). *Mechanism leading to irreversible capacity loss in Li ion rechargeable batteries*. Journal of Electrochemical Society 142, 2914-2918.
- Megahed. S. and Ebner. W. (1995). *Lithium-ion battery for electronic applications*. Journal of Power Sources 54, 155-162.
- Menachem. C., Wang. Y., Flowers. J., Peled. E. and Greenbaum. S.G. (1998). *Characterization of lithiated natural graphite before and after mild oxidation*. Journal of Power Sources 76, 180-185.
- Migahed. M.D., Ishra. M., Fahmy. T. and Barakat. A. (2004). *Electric modulus and AC conductivity studies in conducting PPy composite films at low temperature*. Journal of Physics and Chemistry of Solids 65, 1121-1125.
- Mohan. V.M., Qiu. W., Shen. J. and Chen. W. (2010). *Electrical properties of poly(vinyl alcohol) (PVA) based on LiFePO₄ complex polymer electrolyte films*. Journal of Polymer Research 17, 143-150.

- Mohomed, K., Gerasimov, T.G., Moussy, F., Harmon, J.P. (2005). *A broad spectrum analysis of the dielectric properties of poly(2-hydroxyethyl methacrylate)*. Polymer 46, 3847-3855.
- Mullens. J., Van Werde. K., Vanhoyland. G., Nouwen. R., Van Bael. M.K. and Van Poucke. (2002). *The use of TGA-MS, TGA-FTIR, HT-XRD and HT-DRIFT for the preparation and characterization of PbTiO₃ and BaTiO₃*. Thermochemica Acta 392-393, 29-35.
- Neudecker. B. J., Zuhr. R. A. and Bates. J. B. (1999). *Lithium silicon tin oxynitride (Li_ySiTON): high-performance anode in thin-film lithium-ion batteries for microelectronics*. Journal of Power Sources 81-82, 27-32.
- Neudecker. B.J., Dudney. N.J. and Bates. J.B. (2000). *Lithium-free thin film battery with in situ plated anode*. Journal of Electrochemical Society 147, 517-523.
- Nishijima. M., Kagohashi. T., Takeda. Y., Imanishi. M. and Yamamoto. O. (1997). *Electrochemical studies of a new anode material, Li_{3-x}M_xN (M = Co, Ni, Cu)*. Journal of Power Sources 68, 510-514.
- Nouwen. R., Mullens. J., Franco. D., Yperman. J. and Van Poucke. L.C. (1996). *Use the thermogravimetric analysis-Fourier transform infrared spectroscopy in the study of the reaction mechanism of the preparation of Pb(Zr, Ti)O₃ by the sol-gel method*. Vibrational Spectroscopy 10, 291-299.
- Osman Z. and Arof A.K. (2003). *FTIR studies of chitosan acetate based polymer electrolytes*. Electrochimica Acta 48, 993-999.
- Pasquier. A.D., Laforgue. A. and Simon. P. (2004). *Li₄Ti₅O₁₂/poly(methyl)thiophene asymmetric hybrid electrochemical device*. Journal of Power Sources 125, 95-102.
- Patil. A., Patil. V., Shin D.W., Choi. J-W., Paik. D-S. and Yoon. S-Jin. (2008). *Issue and challenges facing rechargeable thin film lithium batteries*. Materials Research Bulletin 43, 1913-1942.
- Patsidis. A. and Psarras. G.C. (2008). *Dielectric behaviour and functional of polymer matrix-ceramic BaTiO₃ composites*. eXPRESS Polymer Letters 10 (2), 718-726.
- Peramunage. D. and Abraham. K.M. (1998). *Preparation of micron-sized Li₄Ti₅O₁₂ and its electrochemistry in polyacrylonitrile electrolyte-based lithium cells*. Journal of the Electrochemical Society 145, 2609-2615.
- Pissis, P. and Kyritsis, A. (1997). *Electrical conductivity studies in hydrogels*. Solid State Ionics 97, 105-113.
- Popielarz. R. and Chiang. C.K. (2007). *Polymer composites with the dielectric constant comparable to that of barium titanate ceramics*. Materials Science and Engineering: B 139, 48-54.

- Prabakar. K, Narayandass. S.K. and Mangalaraj. D. (2003). *Dielectric and electric modulus properties of vacuum evaporated Cd_{0.8}Zn_{0.2}Te thin films*. Materials Science and Engineering B98, 225-231.
- Qiu W, Zhou R, Yang L and Liu Q. (1996). *Lithium-ion rechargeable battery with petroleum coke anode and polyaniline cathode*. Solid State Ionics 86-88, 903-906.
- Rahman. M.M., Wang. J-Z., Hassan. M.F., Chou. S., Wexler. D. and Liu/ H-K. (2010). *Basic molten salt process-A new route for synthesis of nanocrystalline Li₄Ti₅O₁₂-TiO₂ anode material for Li-ion batteries using eutectic mixture of LiNO₃-LiOH-Li₂O₂*. Journal of Power Sources 195, 4297-4303.
- Raja. M.W., Mahanty. S., Kundu. M. and Basu. R.N. (2009). *Synthesis of nanocrystalline Li₄Ti₅O₁₂ by a novel aqueous combustion technique*. Journal of Alloys and Compounds 468, 258-262.
- Shenouda A.Y. and Murali. K.R. (2008). *Electrochemical properties of doped lithium titanate compounds and their performance in lithium rechargeable batteries*. Journal of Power Sources 176, 332-339.
- Shen, C-M., Zhang. X-G., Zhou. Y-ke. and Li. H-Lin. (2002). *Preparation and characterization of nanocrystalline Li₄Ti₅O₁₂ by sol-gel method*. Materials Chemistry and Physics 78, 437-441.
- Shi. H. (1998) *Coke vs. graphite as anodes for lithium-ion batteries*. Journal of Power Sources 75, 64-72.
- Shokrollahi. H. (2009). *The magnetic and structural properties of the most important alloys of iron produced by mechanical alloying*. Materials and Design 30, 3374-3387.
- Shu. J. (2008) *Electrochemical behavior and stability of Li₄Ti₅O₁₂ in a broad voltage window*. Journal of Solid State Electrochemistry 13, 1535-1539 .
- Shu. J. (2009). *Li-Ti-O compounds and carbon-coated Li-Ti-O compounds as anode materials for lithium ion batteries*. Electrochimica Acta 54, 2869-2876.
- Si. Q., Hanai. K., Imanishi. N., Kubo. M., Hirano. A., Takeda. Y. and Yamamoto. O. (2009). *Highly reversible carbon-nano-silicon composite anodes for lithium rechargeable batteries*. Journal of Power Sources 189, 761-765.
- Sun. Q. and Fu. Z-W. (2008). *Vanadium nitride as a novel thin film anode material for rechargeable lithium batteries*. Electrochimica Acta 54, 403-409.
- Švorčík. V., Podgrabinski. T., Náhlík. J., Rybka. V., Hnatowicz. V. (2005). *Dielectric properties of doped polymethylmethacrylate*. Materials Letters 59, 341-344.
- Takamura. T. (2002). *Trends in advanced batteries and key materials in the new century*. Solid State Ionics 152-153, 19-34.
- Takahashi. Y. (1997). *Neutron structure analysis of poly (vinyl alcohol)*. Journal of Polymer Science Part B: Polymer Physics 35, 193-198.

- Tarascon. J.-M. and Armand. M. (2001) *Issues and challenges facing rechargeable lithium batteries*. Nature 414, 359-367.
- Tawansi et al., El-Khodary. A. and Abdelnaby. (2005). *A study of the physical properties of FeCl₃ filled PVA*. Current Applied Physics 2005, 572-578.
- Tawansi. A., Zidan. H.M. and Eldumiaty. A.H. (1998). *Electron spin resonance, magnetic and optical properties of MnCl₂ filled PVC films*. Polymer Testing 17, 211-224.
- Thackerey. M.M. (1995). *Structural considerations of layered and spinel lithiated oxides for lithium ion batteries*. Journal of the Electrochemical Society 142, 2558-2563.
- Thomas. P., Varughese. K.T., Dwarakanath. K., Varma. K.B.R. (2010). *Dielectric properties of poly(vinylidene fluoride)/CaCu₃Ti₄O₁₂ composites*. Composites Science and Technology 70, 539-545.
- Tian. H. and Tagaya. H. (2008). *Dynamic mechanical property and photochemical stability of perlite/PVA and OMMT/PVA nanocomposites*. Journal of Materials Science 43, 766-770.
- Tran. T.D., Derwin. D.J., Zaleski. P., Song. X. and Kinoshita K. (1999). *Lithium intercalation studies of petroleum cokes of different morphologies*. Journal of Power Sources 81-82, 296-299.
- Van Thournout. M., Aldon. L., Womes. M., Ducourant. B., Olivier-Fourcade. J., Tessier. C. and Levasseur. S. (2007). *Metal-doped Li₂Ti₃O₇ with ramsdellite structure as high voltage anode for new generation Li-ion batteries*. Journal of Power Sources 174, 1270-1274.
- Wan. K., Li. S.F.Y., Gao. Z. and Siow. K.S. (1998). *Tin-based oxide anode for lithium-ion batteries with low irreversible capacity*. Journal of Power Sources 75, 9-12.
- Wang. D., Xu. H-Y., Gu. M. and Chen. C-H. (2009). *Li₂CuTi₃O₈-Li₄Ti₅O₁₂ double spinel anode materials with improved rate performance for Li-ion batteries*. Electrochemistry Communications 11, 50-53.
- Wang. G.J., Gao.J., Fu. L.J., Zhao. N.H., Wu. Y.P. and Takamura. T. (2007). *Preparation and characteristic of carbon-coated Li₄Ti₅O₁₂ anode material*. Journal of Power Sources 174, 1109-1112.
- Wang. G.X., Bradhurst. D.H., Dou. S.X. and Liu. H.K. (1999). *Spinel Li[Li_{1/3}Ti_{5/3}]O₄ as an anode materials for lithium ion batteries*. Journal of Power Sources 83, 156-161.
- Wen. S., Ji. S., Sun. J., Tian. F. and Xie J. (2006). *Mechanism of lithium insertion into NiSi₂ anode material for lithium ion batteries*. Rare Metals 25, 77-81.
- Winter. M., Besenhard. J.O., Spahr. M.E. and Novák. P. (1998). *Insertion Electrode Materials for Rechargeable Lithium Batteries*. Advanced Materials 10, 725-763.

- Wissler. M. (2006). *Graphite and carbon powders for electrochemical applications*. Journal of Power Sources 156, 142-150.
- Wu. X.M., Li. X.H., Zhang. Y.H., Xu. M.F. and He. Z.Q. (2004). *Synthesis of $Li_{1.3}Al_{0.3}Ti_{1.7}(PO_4)_3$ by sol-gel technique*. Materials Letters 58, 1227- 1230.
- Yan. G., Fang. H., Zhao. H., Li. G., Yang. Y. and Li. L. (2009). *Ball-milling-assisted sol-gel route to $Li_4Ti_5O_{12}$ and its electrochemical properties*. Journal of Alloys and Compounds 470, 544-547.
- Yang. Y., Liu.C. and Wu. H. (2009). *Preparation and properties of poly (vinyl alcohol)/exfoliated α -zirconium phosphate nanocomposite films*. Polymer Testing 28, 371-377.
- Yang. L.H., Dong. Cheng. and Guo. J. (2008). *Hybrid microwave synthesis and characterization of the compounds in the Li-Ti-O system*. Journal of Power Sources 175, 575-580.
- Yang L. and Gao. L. (2009). *$Li_4Ti_5O_{12}/C$ composite electrode material synthesized involving conductive carbon precursor for Li-ion battery*. Journal of Alloys and Compounds 485, 93-97.
- Yao. X.L., Xie. S., Chen. C.H., Wang. Q.S., Sun. J.H., Li. Y.L. and Lu. S.X. (2005). *Comparisons of graphite and spinel $Li_{1.33}Ti_{1.67}O_4$ as anode materials for rechargeable lithium-ion batteries*. Electrochimica Acta 50, 4076-4081.
- Yao. X.L., Xie. S., Nian. H.Q. and Chen. C.H. (2008). *Spinel $Li_4Ti_5O_{12}$ as a reversible anode materials down to 0 V*. Journal of Alloys and Compounds 456, 375-379.
- Yuan. T., Cai. R., Wang. K., Ran.R., Liu. S. and Shao. Z. (2008). *Combustion synthesis of high-performance $Li_4Ti_5O_{12}$ for secondary Li-ion battery*. Ceramic International 35, 1757-1768.
- Zaghib. K., Simoneau. M., Armand. M. and Guathier. M. (1999). *Electrochemical study of $Li_4Ti_5O_{12}$ as negative electrode for Li-ion polymer rechargeable batteries*. Journal of Power Sources 81-82, 300-305.
- Zhang. C.Y. (2009). *The influence of substrate and annealing temperatures on electrical properties of p-type ZnO films*. Physica B: 404, 138-142.
- Zhang. Q., Wen. Z., Liu. Y., Song. S. and Wu. X. (2009). *Na^+ ion conductors of glass-ceramics in the system $Na_{1+x}Al_xGe_{2-x}P_3O_{12}$ ($0.3 \leq x \leq 1.0$)*. Journal of Alloys and Compounds 479, 494-499.
- Zhao. Y., Liu. G., Liu. L. and Jiang. Z. (2009). *High-performance thin-film $Li_4Ti_5O_{12}$ electrodes fabricated by using ink-jet printing technique and their electrochemical properties*. Journal of Solid State Electrochemistry 13, 705-711.
- Zhou. D., Liu. Z., Lv. X., Zhou. G. and Jian Y.J. (2006). *Electrochemical studies of LiB compound as anode material for lithium-ion battery*. Electrochimica Acta 51, 5731-5737.

Zidan. H.M. (1999). *Effect of AgNO₃ filling and UV-irradiation on the structure and morphology of PVA films*. Polymer Testing 18, 449-461.