

TABLE OF CONTENTS

ABSTRACT	ii
ACKNOWLEDGEMENT	v
TABLE OF CONTENT	vi
LIST OF TABLES	x
LIST OF FIGURES	xi
CHAPTER	
1 INTRODUCTION	1
1.1 Solar dryer greenhouse.....	1
1.2 Scope of dissertation.....	3
1.3 Proposed method.....	5
1.4 Outline of the dissertation	6
2 LITERATURE REVIEW	7
2.1 Solar dryer history.....	7
2.2 Design and development of greenhouse solar dryer	10
2.3 CFD application in greenhouse development	13
2.3.1 Two dimensional and three dimensional CFD analyses	14
2.3.2 CFD analysis for mono span greenhouse with pitched	
roof design.....	16
2.4 Governing equations	17
2.4.1 Navier-Stokes equation	17

2.4.2	Turbulence model	18
2.4.3	Heat transfer model.....	21
2.4.4	Modeling for buoyancy	22
3	METHODOLOGY.....	25
3.1	CFD Simulation	25
3.1.1	Pre-processing stage.....	26
3.1.1.1	Geometry creation.....	26
3.1.1.2	Mesh development	28
3.1.1.3	Physical properties set-up	29
3.1.1.4	Boundary condition.....	32
3.1.2	Solving	34
3.1.3	Post processing.....	35
3.2	Physical measurement.....	36
4	RESULTS AND DISCUSSION	41
4.1	Mesh sensitivity study.....	41
4.2	Convergence trend	43
4.3	Solar dryer greenhouse with both roof and side opening open (condition 1).....	44
4.3.1	Temperature for location P1 until P9	45

4.3.2	Temperature distribution from CFD simulation	46
4.3.3	Air flow velocity profile	47
4.3.4	Data analysis and discussion for solar dryer with roof and side opening	48
4.4	Solar dryer greenhouse with roof opening open and side opening close (condition 2)	51
4.4.1	Temperature for location P1 until P9	52
4.4.2	Temperature distribution from CFD simulation	53
4.4.3	Air flow velocity profile	54
4.4.4	Data analysis and discussion for solar dryer with side opening only	55
4.5	Overall data analysis and discussion	58
5	SUGGESTIONS FOR IMPROVEMENT	60
5.1	Introduction	60
5.2	Proposed design	62
5.3	Comparison of current and new design solar dryer greenhouse	65
5.3.1	Temperature distribution	65
5.3.2	Air flow velocity	68
6	CONCLUSIONS	70

6.1	Future work	71
	REFERENCES.....	72

LIST OF TABLES

TABLE

1.1	Conditions considered in the study	3
3.1	Domain properties	31
3.2	Polyethylene properties	31
3.3	Air properties	32
3.4	Temperature sensor specification	37
3.5	Solar radiation sensor specification	37
3.6	Wind speed and wind direction sensor specification	38
4.1	Difference of outside temperature (T_{out}) and inside temperature (T_{in}) data between simulation and measured for condition 1..	50
4.2	Difference of outside temperature (T_{out}) and inside temperature (T_{in}) data between simulation and measured for condition 2.	57

LIST OF FIGURES

FIGURE

1.1	Solar dryer greenhouse building at MARDI	4
1.2	Steps included in performing the CFD analysis in this project	5
2.1	Classification of solar dryers and dryer modes. (Fudholi et al., 2010)	9
2.2	Different types of natural circulation greenhouse type crop dryers. (Koyuncu, 2006).....	11
2.3	Natural convection solar dryer greenhouse (Ekechukwu and Norton,1996)	12
2.4	Large scale tunnel type solar dryer using polycarbonate cover design (Janjai et al.,2011)	12
2.5	The number of published peer-reviewed publications of CFD applied to the ventilation of agricultural buildings (Norton et al,2007).	13
2.6	Influence of the turbulence model on the flow pattern at the symmetry plane of a confined flow (Moureah and Flick, 2005 as quote by Norton et al ,2007)	21
3.1	ANSYS CFX module (ANSYS CFX Introduction, 2009).....	25
3.2	Three-dimensional computational domain	27
3.3	Tetrahedral mesh	28
3.4	Model after the meshing process	28
3.5	Sun radiation at 10.30 am	33
3.6	Sun radiation at 1.30 pm	33
3.7	Sun radiation at 4.30 pm	33
3.8	CFX solver solution process flowchart solver (ANSYS CFX Solver theory guide, 2009	34
3.9	Temperature sensor	36
3.10	Solar radiation sensor	37
3.11	Wind speed and wind direction sensor	38
3.12	Location of temperature and humidity sensor inside the greenhouse	39
3.13	Location of sensor inside greenhouse	40
3.14	Location of sensor outside greenhouse	40
4.1	Solar dryer greenhouse model with different numbers of element (a) 0.6 m (b) 0.4m (c) 0.1 m and (d) 0.05m	41
4.2	Temperature of location P1, P2 and P3 for model with different numbers of element	42
4.3	Convergence trends of the simulation	43
4.4	Temperature for each location at (a) 10.30 am, (b) 1.30 pm, and (c) 4.30 pm on 13th March and 21st March 2011 1	45
4.5	Temperature distribution contour at (a) 10.30 am, (b) 1.30 pm, and (c) 4.30 pm and on 13 th March and 21 st March 2011 11	46
4.6	Air flow velocity profile at (a) 10.30 am, (b) 1.30 pm, and (c) 4.30 pm and on 13th March and 21st March 2011	47
4.7	Measured and CFD-simulated air temperature differences for inside (T_{in}) (average) and outside (T_{out}) for solar dryer with	

4.8	side and roof opening open at (a) 10.30 am, (b) 1.30 pm and (c) 4.30 pm	49
	Temperature for each location at (a) 10.30 am, (b) 1.30 pm, and (c) 4.30 pm on 26 th March and 4 th April 2011.....	52
4.9	Temperature distributions contour at (a) 10.30 am, (b) 1.30 pm, and (c) 4.30 pm on 26 th March and 4 th April 2011.....	53
4.10	Air flow velocity profile at (a) 10.30 am, (b) 1.30 pm, and (c) 4.30 pm on 26 th March and 4 th April 2011.....	54
4.11	Measured and CFD-simulated air temperature differences for inside (T_{in}) (average) and outside (T_{out}) for solar dryer with roof opening only at (a) 10.30 am, (b) 1.30 pm and (c) 4.30 pm.....	56
5.1	Designs to be considered in the improvement study (a) design 1 and (b) design 2	63
5.2	Result comparison of current design, design 1 and design 2 for (a) temperature and (b) air flow velocity	64
5.3	Temperature distribution for improved and current design solar dryer at (a) 10.30 am, (b) 1.30 pm and (c) 4.30 pm	65
5.4	Temperature for each location at (a) 10.30 am, (b) 1.30 pm and (c) 4.30 pm	67
5.5	Air flow velocity distribution at (a) 10.30 am, (b) 1.30 pm and (c) 4.30 pm.....	68
5.6	Air flow velocity at (a) 10.30 am, (b) 1.30 pm and (c) 4.30 pm	69