| | | | Page |
|-------|----------|--|------|
| ACKNO | OWLEDGEM | ENTS | iii |
| ABSTE | RACT | | iv |
| ABSTE | RAK | | vi |
| CONT | ENTS | | viii |
| LIST | OF TABLE | ES | xiii |
| LIST | OF FIGU | RES | xvi |
| CHAP? | FER 1 In | troduction | |
| 1.1 . | The Oil | Palm | 1 |
| 1.2 | Extract | ion of Palm Oil | 2 |
| 1.3 | Palm Oi | l Effluent | 3 |
| 1.4 | Uses of | Palm Oil | 5 |
| 1.5 | Emulsio | ns | 6 |
| 1.6 | Objecti | ves of Study | 8 |
| | Referen | ces | 11 |
| CHAP | | ipid Constituents of Oil Droplets rom Palm Oil Sludge | |
| 2.1 | Introdu | ction | 17 |
| | 2.1.1 | Palm Oil Lipids | 18 |
| 2.2 | Materia | ls and Methods | 22 |
| | 2.2.1 | Separation of Oil Droplets from Centrifuged Sludge | 22 |
| | 2.2.2 | Microscopy | 23 |
| | 2.2.3 | Particle Sizing | 23 |
| | 2.2.4 | Extraction of Lipids from Dried Oil Droplets | 24 |
| | 2.2.5 | Column Chromatography of Lipid Extract | 24 |
| | 2.2.6 | Thin Layer Chromatography | 25 |
| | 2.2.7 | Identification of Lipids | 26 |

| | | | Page |
|-------------------|---|---|----------------------------|
| | 2.2.8 | Preparation of Visualiser Sprays | 26 |
| | 2.2.9 | Quantification of Glycolipids | 28 |
| | 2.2.10 | Quantification of Phosphorus | 28 |
| | 2.2.11 | Fatty Acid Composition Analysis | 29 |
| | 2.2.12 | Glycerides Analysis | 30 |
| 2.3 | Results | and Discussion | |
| | 2.3.1 | Separation of Oil Droplets and Phosphorus Determination | 31 |
| | 2.3.2 | Microscopy and Particle Sizing | 33 |
| | 2.3.3 | Chemical Analysis of Oil Droplets | 35 |
| 2.4 | Conclus | ion | 43 |
| | Reference | ces | 46 |
| | | | |
| CHAP' | TER 3 | Surface Active Properties of Palm Oil | |
| CHAP: | | _ | 70 |
| | Introduc | ction | 70 73 |
| 3.1 | Introduc | ction | |
| 3.1 | Introduc Materia | ction | 73 |
| 3.1 | Introduc Materia Methods | ction | 73 75 |
| 3.1 | Introduc Materia Methods 3.3.1 | ction ls Surface Tension Measurement | 73 75 75 |
| 3.1 | Introduc Materia: Methods 3.3.1 3.3.2 3.3.3 | Surface Tension Measurement Interfacial Tension Measurement Exraction of Alcohol Insoluble Residue (AIR) of Sludge from Palm | 73 75 75 76 |
| 3.1 3.2 3.3 | Introduc Materia: Methods 3.3.1 3.3.2 3.3.3 Calcula per Mole | Surface Tension Measurement Interfacial Tension Measurement Exraction of Alcohol Insoluble Residue (AIR) of Sludge from Palm Oil Mill tion of Surface Excess, [and area | 73 75 75 76 77 |
| 3.1 3.2 3.3 | Introduc Materia: Methods 3.3.1 3.3.2 3.3.3 Calcula per Mole | Surface Tension Measurement Interfacial Tension Measurement Exraction of Alcohol Insoluble Residue (AIR) of Sludge from Palm Oil Mill tion of Surface Excess, [and area ecule, σ | 73 75 75 76 77 |

PERPUSTAKAAN UNIVERSITI MALAYA

| | | | Page |
|------|-----------|---|------|
| | 3.5.3 | Surface Active Substances Associated with the Oil Droplets from the Aqueous Sludge | 89 |
| | 3.5.4 | Surface Activity of Low Concentration of Pure Monoglycerides and Phos- pholipids at the Refined Palm Oil (NBDPO)/Water Interface | 90 |
| 3.6 | Conclusi | ion | 100 |
| | Reference | ces | 103 |
| CHAP | | Properties of Palm Oil Emulsions Prepared with Nonionic Surfactants | |
| 4.1 | Introduc | ction | 132 |
| 4.2 | Materia: | ls and Methods | 136 |
| | 4.2.1 | Material | 136 |
| | 4.2.2 | Preparation of Emulsions | 137 |
| | 4.2.3 | Stability of Emulsions - Creaming | 140 |
| | 4.2.4 | Particle Size Measurement | 140 |
| | 4.2.5 | Interfacial Tension Measurement | 141 |
| | 4.2.6 | Viscosity Measurements | 141 |
| | 4.2.7 | Effect of Electrolytes and pH on Emulsion Stability | 141 |
| 4.3 | Results | And Discussion | 142 |
| | 4.3.1 | Stability of Palm Oil Emulsions prepared using Mixed Emulsifiers | 142 |
| | 4.3.2 | Particles Size Distribution | 150 |
| | 4.3.3 | Interfacial Tension | 152 |
| | 4.3.4 | Emulsification of Palm Oil using Tween 40 | 155 |
| | 4.3.5 | Estimation of Surface Area of Tween 40 | 157 |

| | | | Page |
|------|-------------------|---|------|
| | 4.3.6 | Stability of Emulsion with respect to pH and Electrolytes | 162 |
| | 4.3.7 | Viscosity of Palm Oil-in-Water Emulsion | 163 |
| | 4.3.8 | Preparation of Emulsion - Order of Addition | 164 |
| | 4.3.9 | Emulsification of Palm Oil with Span 40 | 165 |
| 4.4 | Conclus | sion | 167 |
| | Referer | nces | 171 |
| CHAP | | Properties of Palm Oil Emulsions Prepared using Emuldan | |
| 5.1 | Introdu | action | 205 |
| 5.2 | Binary Crystal | Phase System and Liquid line Phases | 207 |
| 5.3 | Ternary | y System | 210 |
| 5.4 | Stabil: | isation of Emulsions | 211 |
| 5.5 | Rheolog | gy of Emulsions | 213 |
| | 5.5.1 | Measurement of Emulsion Rheology | 215 |
| 5.6 | Outline | e of Study | 216 |
| 5.7 | Materia | als and Methods | 217 |
| | 5.7.1 | Mapping of Ternary Phase Diagram | 218 |
| | 5.7.2 | Preparation of Palm Olein-in- Water Emulsion using (Samples 1-24) | 218 |
| | 5.7.3 | Preparation of Emuldan in Water (Samples A-G) | 219 |
| | 5.7.4 | Particle Sizing | 219 |
| | 5.7.5 | Rheological Measurements | 219 |
| 5.8 | Result | s and Discussion | 221 |

| | | | | | Page |
|----------|---------|---------|----------------------------|--------------|------|
| 5.8 | .1 Te | nary Ph | ase Diagram | | 221 |
| 5.8 | .2 Cr | eaming | Stability | | 223 |
| 5.8 | .3 Pa | rticles | Size Distrib | ution | 224 |
| 5.8 | .4 Op | tical M | icroscopy | | 226 |
| 5.8 | .5 Rh | eologic | al Properties | of Emulsions | 228 |
| | 5. | | Flow Properti Emulsions | es of | 229 |
| | 5. | 8.5.2 | Viscoelastic | Properties | 236 |
| 5.8 Con | clusion | | | | 255 |
| Ref | erences | ; | | | 259 |
| | | | _ | | 22/ |
| CHAPTER | 6 Fina | 1 Concl | usion | | 320 |
| PUBLICAT | TIONS | | | | 329 |

LIST OF TABLES

| CHAPTER 1 | | Page |
|-----------|--|------|
| Table 1. | Twelve key physical factors affecting the stability and rheology of emulsions (0=not important, 1=sometimes important, 2=often important, 3=generally important) | 15 |
| CHAPTER 2 | | |
| Table 1. | Triglyceride Composition w/w of Palm Oil and Palm Kernel Oil | 53 |
| Table 2. | Fatty Acid Composition w/w of Palm Oil and Palm Kernel Oil | 53 |
| Table 3. | Phosphorus and Nitrogen Contents of the Cream Layer of Oil Droplets | 54 |
| Table 4. | Composition of Twice Water-Washed Oil Droplets | 55 |
| Table 5. | Lipid Composition of the CHCl $_2$ /MeOH Extract of the Dried Oil Droplets by Column Chromatography (w/w) | 55 |
| Table 6. | Lipid Composition of Chloroform Fraction Isolated from Cream Layer Separated by Column Chromatography and Determined by Gas Chromatography | 56 |
| Table 7. | Fatty Acid Composition of the Neutral Lipids (Chloroform Fraction) Isolated from the Cream Layer as Determined by Gas Chromatography | 56 |
| Table 8. | Relative % w/w of Various Glycolipids (Acetone Fraction) extracted from the oil droplets (cream layer) and Retention Factors Determined from Thin Layer Chromatography in the solvent System (CHCl ₃ :MeOH:CH ₃ COOH:H ₂ O) 70:25:25:6 (v/v) | 57 |

| | | Page |
|-----------|--|------|
| Table 9. | Fatty Acid Composition of Phospholipids from CHCl ₃ /MeOH Extract of Dried Oil Droplets | 58 |
| CHAPTER 3 | | |
| Table 1. | Fatty Acid Composition of Chemically Refined Palm Oil (NBDPO) | 110 |
| Table 2. | Quality of Chemically Refined Palm Oil (NBDPO) | 110 |
| Table 3. | Lipid Composition of Partially Processed Palm Oil | 111 |
| Table 4. | Derived Best Fit Equation based on the Interfacial Tension vs ln Concentration of Additives added to Palm Oil (NBDPO) | 112 |
| Table 5. | Interfacial Tension of Palm Oil/ Water at Various Stages of Refining Measured at 60°C | 113 |
| Table 6. | Properties of AIR precipatated using 1:1 (v/v) (Methanol: Supernatant) at pH 3, at Room Temperature | 114 |
| CHAPTER 4 | | |
| Table 1. | Composition of Palm Oil (RBDPO) Used | 177 |
| Table 2. | Fatty Acid Composition of Palm Oil (RBDPO) Used | 177 |
| Table 3. | Mean Droplet Diameter and Span of Palm Oil Emulsions Prepared with Emulsifier Mixtures of Span 40 and Tween 40 at various HLBs | 178 |
| Table 4. | A Comparison of the Interfacial Tension of Palm Oil (RBDPO)/Water in Mixtures of Various HLB and Tween 40 only in Palm Oil (RBDPO) | 179 |

| | | Page |
|-----------|---|------|
| Table 5. | Expected Surface Area of the Tween 40 Molecule at the Oil Droplet Surface for Complete Coverage. Emulsions consist of 30:100 (wt. basis) of Oil:Water | 180 |
| CHAPTER 5 | | |
| Table 1. | Composition of Emuldan | 274 |
| Table 2. | Fatty Acid Composition of Emuldan | 274 |
| Table 3. | Composition and Appearance of Emulsions prepared using Olein, Emuldan and Water | 275 |
| Table 4. | Composition and Appearance of Samples Prepared using Water and Emuldan | 276 |
| Table 5. | Droplet Size Distribution of Samples 1-18,A,B and C Sample,Droplet Size | 277 |
| Table 6. | Rheological Equations obtained by Curve Fitting of Samples A-B and Samples 1-12. Apparent Viscosities deduced at Shear Rate 30 s-1 | 278 |
| Table 7. | Steady State Compliance Je and Zero Shear Viscosity No of Emuldan/Water and Emuldan/Oil/Water Systems. | 279 |
| Table 8. | Rheological Data of Samples C-G and Samples 13-24 at the Critical Stress Value $T_{\rm C}. \label{eq:continuous}$ | 280 |

LIST OF FIGURES

| | | | Page |
|---------|----|---|------|
| CHAPTER | | 1 | |
| Fig. | 1. | Flow Diagram of Palm Oil Extraction in a Palm Oil Mill | 16 |
| CHAPT | ER | 2 | |
| Fig. | 1. | Common Plant Lipids | 59 |
| Fig. | 2. | Sludge After High Speed Centrifugation | 61 |
| Fig. | 3. | Oil Droplets of the Cream Layer Separated from the Sludge by Centrifugation (Mag 200x) | 61 |
| Fig. | 4. | Solids from Bottom Sediment Isolated from Sludge by Centrifugation | 62 |
| Fig. | 5. | Particle Size Distribution of of Oil Droplets in the Cream Layer Isolated by Centrifugation of the Sludge | 63 |
| Fig. | 6. | Particle Size Distribution of the Oil Droplets in the cream layer after Washing Twice with Water; b: Particle Size Distribution of the Sediments Collected from the Oil Layer after washing Twice with water | 64 |
| Fig. | 7. | Thin-layer Chromatography of CHCL3/MeOH Extract on Silica Gel G. Solvent System CHCl3:MeOH:CH3COOH:H2O (170:25:25:6). | 65 |
| Fig. | 8. | Thin Layer Chromatography of the Chloroform Fraction from column chromatography. Solvent system Hexane:Diethyl ether:Formic Acid (80:20:2), visualised with 2,7'-Dichlorofluorescein spray (yellow) and Ferric Chloride spray (lipids are stained brown). | 66 |

| | Page |
|---|------|
| Fig.9. TLC of the Different Fractions Separated by Silicic Acid Column Chromatography. Solvent System CHCl ₃ :MeOH:Ch ₃ COOH:H ₂ O (170:25:25:6). | 67 |
| Fig. 10. A Comparison of the Retention Time of the Gas Chromatogram of Some Sterol Standards and that of the Unsaponifiables from the Oil Droplets. | 68 |
| CHAPTER 3 | |
| Fig. 1. Possible Orientation of Emulsifiers at the Oil-Water Interface. | 115 |
| Fig. 2. Refining Processes for Crude Palm Oil | 116 |
| Fig. 3. The Effect of Various Types of Partially Refined Oil on the Interfacial Tension of Chemically Refined Palm Oil (NBDPO)/Water Interface | 117 |
| Fig. 4. The Effect of Various Additives on the Interfacial Tension of Chemically Refined Palm Oil (NBDPO)/ Water Interface | 118 |
| Fig. 5. Interfacial Tension and Surface Tension of Supernatant from the Sludge at Various Temperatures. | 119 |
| Fig. 6. Effect of Dilution with H ₂ O at 60°C on the Surface Tension of Supernatant and Interfacial Tension of Palm Oil (NBDPO)/Supernatant and Crude Palm Oil/Supernatant respectively. | 120 |
| Fig. 7. Interfacial Tension of the Alcohol Insoluble Residue (AIR) in Water against Palm Oil (NBDPO) as a function of the Concentration of AIR in Water. | 121 |
| Fig. 8. Effect of Additives on the Interfacial Tension of Palm Oil (NBDPO)/Water System | 122 |

| | | | Page |
|------|-----|--|------|
| Fig. | 9. | Influence of Chain Length of Monoglycerides on the Interfacial Tension of Palm Oil (NBDPO)/Water System at 60°C. | 123 |
| Fig. | 10. | Influence of Unsaturation of the Monoglycerides (18 carbon atoms) on the Interfacial Tension of Palm Oil (NBDPO)/Water System at 60°C. | 124 |
| Fig. | 11. | Influence of Unsaturation of the Monoglycerides (16 carbon atoms) on the Interfacial Tension of Palm Oil (NBDPO)/Water System at 60°C. | 125 |
| Fîg. | 12. | Influence of Chain Length of Monoglycerides on the Molecular Area of the Monoglycerides at the Palm Oil (NBDPO)/Water Interface. | 126 |
| Fig. | 13. | Influence of Unsaturation of Monoglyceride (18 carbon atoms) on the Molecular Area of the Monoglycerides at the Palm oil (NBDPO)/Water Interface. | 127 |
| Fig. | 14. | Influence of a Double Bond on the Molecular Area of Monopalmitin at the Palm Oil (NBDPO)/Water Interface. | 128 |
| Fig. | 15. | Interfacial Tension of Palm Oil (NBDPO)/Water Interface in the presence of Various Phospholipids Added to the Palm Oil (60°C). | 129 |
| Fig. | 16. | Molecular Structures of Phospholipids | 130 |
| Fig. | 17. | Influence of Various Phospholipids on the Molecular Area of the Phospholipids at the Refined Palm oil (NBDPO)/ Water Interface at 60°C | 131 |

| | | Page |
|-----------|---|------|
| CHAPTER 4 | 4 | |
| Fig. 1. | Molecular Structure of (a) Polyoxyethylene Sorbitan Esters and (b) Sorbitan Esters Series of Surfactants illustrating the Possible Orientation of the Hydrophilic and Hydrophobic Group at the Oil/Water Interface. | 181 |
| Fig. 2. | Cause and Effect Diagram for the Factors Affecting the Properties of Emulsions. | 182 |
| Fig. 3. | Stability of 23.0% w/w Palm Oil Emulsions (50 ml) at 60°C with 5.0% w/w Emulsifier Mixture in Oil after 1 and 10 Days Storage. | 183 |
| Fig. 4. | Stability of 23% w/w palm oil emulsions at 60°C with 1% w/w emulsifier mixture in oil after 3 weeks of storage. | 184 |
| Fig. 5. | Stability of 50% w/w palm oil emulsions at 60°C with 0.1% w/w emulsifier mixture in oil after 2 weeks storage. | 185 |
| Fig. 6. | Droplet size distribution of 23.0% w/w palm oil emulsions at 5.0% w/w emulsifier mixtures of different HLB values. | 186 |
| Fig. 7. | Droplet size distribution of 23.0% w/w palm oil emulsions at 1.0% w/w emulsifier mixtures of different HLB values. | 187 |
| Fig. 8. | Droplet size distribution of 50% w/w palm oil emulsion or 0.1% w/w emulsifier mixtures of different HLB values. | 188 |
| Fig. 9. | Effect of ageing at 60°C on the droplet size distribution of 23.0% w/w palm oil emulsion at 1.0% w/w emulsifier mixture with a HLB value of 11.3. | 189 |

| | | | Page |
|------|-----|--|------|
| Fig. | 10. | Effect of aging at 60°C on the droplet size distribution of 50% w/w palm oil emulsion at 0.1% w/w emulsifier mixture with a HLB value of 9.37. | 190 |
| Fig. | 11. | Interfacial tension of palm oil against water at various concentration of Tween 40 and Span 40 in oil. | 191 |
| Fig. | 12. | Interfacial tension of palm oil against water at three different concentrations of emulsifier mixture with various HLB. | 192 |
| Fig. | 13. | Effect of Tween 40 concentration on the droplet size distribution 50% w/w palm oil emulsions. | 193 |
| Fig. | 14. | Effect of Tween 40 concentration on the (a) droplet size of 23% v/v palm-oil emulsions and (b) interfacial tension of the palm oil-water interface at 60°C. | 194 |
| Fig. | 15. | Stability of 50% w/w palm oil emulsion (50 ml) made with different concentrations of Tween 40 at 60°C. | 195 |
| Fig. | 16. | Effect of oil phase volume on the droplet size distribution of palm oil emulsions containing 1.0% Tween 40 in oil. | 196 |
| Fig. | 17. | The mean droplet size of palm oil emulsions at various phase volume using 1.0% w/w Tween 40 in oil. | 197 |
| Fig. | 18. | Photomicrograph of emulsion droplets prepared with 1% Tween 40 in oil at ϕ = 0.7. | 198 |
| Fig. | 19. | Viscosity curves of various phase volume of palm oil emulsions prepared with 1% w/w Tween 40 in oil. Inset shows apparent viscosities as a function of phase volume at 520s ⁻¹ . | 199 |

| | | | Page |
|------|-----|--|------|
| Fig. | 20. | Test of thixotropy illustrated by the viscosity curves of palm oil-in-water emulsion of ϕ 0.69 at 60°C. Inset shows programme used to test thixotropy. | 200 |
| Fig. | 21. | Stability of 23% w/w palm oil emulsions at 60°C with various concentrations of Span in oil. | 201 |
| Fig. | 22. | Effect of Span 40 concentration in oil on the droplet size distribution of 23.0% w/w palm oil. | 202 |
| Fig. | 23. | Effect of aging at 60°C on the droplet size distribution of 23% w/w palm oil emulsions at 0.14% and 1.0% w/w Span 40 in oil. | 203 |
| СНАР | TER | 5 | |
| Fig. | 1. | Structure Models showing (a) Orientation of Surfactant Molecules in the Crystalline stage; b) Formation of lamellar mesophase above Tc (Kraft point) in the presence of water and (c) Formation of gel phase below Tc (d) Hexagonal I, cylindrical aggregates of polar lipids with polar group in contact with the continuous water phase (e) Hexagonal II, cylindrical aggregates of water in a continuous lipid phase. | 281 |
| Fig. | 2. | Phase Diagram deduced by Visual Appearance of Samples indicating the Location of the Emulsions Studied. | 282 |
| Fig. | 3. | Ternary Phase Diagram Indicating the Location of the Samples (1-24) with Respect to the Composition of the Three Components of Emuldan:Olein: Water on Weight Basis. | 283 |
| Fig. | 4. | Visual Observation of Samples A-C and | 284 |

| | | | Pag |
|------|-----|--|-----|
| Fig. | 5. | Effect of Concentration of Emuldan in Olein on the Interfacial Tension of the Olein/Water System at 60°C | 285 |
| Fig. | 6. | Droplet Size Distribution of Emulsion Samples No.1-6 and A,B,C. | 286 |
| Fig. | 7. | Droplet Size Distribution of Emulsion Samples 7-12. | 287 |
| Fig. | 8. | Droplet Size Distribution of Emulsion Samples 13-18. | 288 |
| Fig. | 9. | Mean Droplet Diameter of Emulsions as a Function of Wt. % Emuldan/Water at Various Fixed Concentration of Olein. | 289 |
| Fig. | 10. | Mean Droplet Diameter of Emulsion as a Function of Wt.% Olein/Water at Various Concentration of Emuldan. | 290 |
| Fig. | 11. | Mean Droplet Diameter as a Function of Wt.% Emuldan/Oil at Various Concentration of Water No systematic correlation among the samples could be determined). | 291 |
| Fig. | 12. | Optical Micrograph of Sample 2, Containing 3:25:72 wt.%) of Emuldan:Olein:Water (Mag 10x5). | 292 |
| Fig. | 13. | Micrograph of Sample 5 containing 3:10:87 wt.%) of Emuldan:Olein:Water. Note much smaller droplets compared to sample 2, Fig. 12 (Mag 10x5). | 293 |
| Fig. | 14. | Optical Micrograph of Sample 13 containing 10:30:60 (wt.%) of Emuldan:Olein:Water. Note aggregation of droplets but well dispersed smaller particles in the background (Mag 10x5). | 294 |
| Fig. | 15. | Optical Micrograph of Sample 20 containing 15:25:60 (wt.%) of Emuldan: Olein:Water. (Mag 10x5). | 295 |

| | | | Page |
|--------|-----|---|------|
| Fig. 1 | | Optical Micrograph Showing Crystal Formation after Three Weeks Storage of Sample 10 containing 5:15:80 (wt.*) of (Emuldan:Olein:Water). Note well dispersed smaller particles in the background. (Mag.10x5) | 296 |
| Fig. 1 | | Optical Micrograph of Sample 9 containing 5:20:75 (wt. %) of Emuldan:Olein:Water stored for 6 months (Mag.10x5). | 297 |
| Fig. 1 | .8. | Optical Micrograph of Dispersions Formed with 5 Wt.% Emuldan in Wate., Showing Birefringent Droplets will Extinction Crosses under Polarised Light. | 298 |
| Fig. 1 | .9. | Optical Micrograph of Lamellar Liquid Crystalline Structure of Sample D containing 15 Wt.% Emuldan in Water under Polarised Light (Mag 10x5). | 299 |
| Fig. 2 | 20. | Optical Micrograph of Lamellar Liquid Crystalline Structures of Sample E containing 20 Wt. % Emuldan in Water (Mag. 10x5). | 300 |
| Fig. 2 | 21. | Flow Curves of Samples A,B and 1-12 as illustrated by Samples A,B, 7 and 11. (Flow curves of the rest of the samples are close and thus not shown). | 301 |
| Fig. 2 | 22. | Viscosity Curves of Samples A,B and 1-12 as illustrated by Samples A,B, 7 and 11. Flow curves of the rest of the samples are very close and thus are not shown. | 302 |
| Fig. 2 | 23. | Apparent Viscosity at Shear Rate, 30s-1 against Wt. Emuldan in Water for Samples A, B and 1-12. Note the extremely low 100 values (0.001-0.036 Pa s). | 303 |
| Fig. 2 | 24. | Illustrative Creep-Recovery Curve of a Viscoelastic Material | 304 |
| Ti- 1 | 2.5 | Groom Recovery Curve of Samples C-G | 305 |

| | | Page |
|----------|---|------|
| Fig. 26. | Creep Recovery Curves of Samples 13-24 as illustrated by Samples 13,16 and 23. | 306 |
| Fig. 27. | A Plot of Steady State Compliance Jeo of Samples 13-24 and C-G as a Function of Wt.% Emuldan/Water. | 307 |
| Fig. 28. | A Plot of Zero Shear Viscosity $\eta_{\rm O}$ for Samples C-G and 13-24 as a Function of Wt.% Emuldan/Water. | 308 |
| Fig. 29. | Illustrative Shear Stress Response of a Viscoelastic Material. The shift angle is a Measure of the Degree of Viscoelasticity of the Material. | 309 |
| Fig. 30. | Stress Sweep of Samples C-G at 1 Hz. Note G* overlaps G'. Inset shows the stress sweep overlap of samples E-G. | 310 |
| Fig. 31. | Plot of G' and G" as a Function of Wt.% of Emuldan/Water at the Linear Viscoelastic Region. (Note G' > G") | 311 |
| Fig. 32. | Typical Stress Sweep of Samples 13-18 at 1 Hz. as illustrated by Samples 14,17 and 18. Note G* overlaps G' except sample 18. | 312 |
| Fig. 33. | Plot of G', G" as a Function of Wt.% Emuldan/Water at the Linear Viscoelastic Region (Note G'>G" except sample 18). | 313 |
| Fig. 34. | Typical Stress Sweep of Samples 18-24 at 1 Hz as illustrated by samples 20,21 and 23. Note G* overlaps G'. | 314 |
| Fig. 35. | Plot of Critical Stress of Samples C-G 13-24 as a Function of Wt.% Emuldan/Water. | 315 |
| Fig.36. | Plot of G' at τ_c as a Function of Wt.\% Emuldan/Water illustrating the Decrease in G' in the Ternary System (Samples 13-24) as compared to the Binary System (Samples C-G). | 316 |

| | | | Page |
|------|-----|---|------|
| Fig. | 37. | Frequency Sweep of Samples C-G at 20 Pa. Note G* overlaps G'. Inset shows the Frequency Sweep Overlap of Samples E-G. | 317 |
| Fig. | 38. | Typical Mechanical Spectra of Sample 13-18 at SPa as illustrated by Samples 13, 15, 17 and 18. Note overlap of G* and G'. | 318 |
| Fig. | 39. | Typical Mechanical Spectra of Samples 19-24 at 20 Pa as illustrated by Samples 19,20 and 23. Note overlap of G* and G'. | 319 |