

## Table of Contents

<b>Title</b>	<b>Page</b>
Title Page	
Abstract	ii
Abstrak	iv
Declaration	vi
Acknowledgements	vii
Table of Contents	viii
List of Figures	xi
List of Tables	xv
Chapter	
1. Introduction	1
1.1. General	1
1.2. Research Objectives	3
1.3. Outline of Research	3
2. Literature Review	6
2.1. Superplasticity	6
2.1.1. History of Superplasticity	7
2.1.2. Characteristics of Superplasticity	8
2.1.2.1. High Strain Rate Sensitivity	8
2.1.2.2. Fine Grain Size	11

2.1.2.3. Temperature	12
2.1.3. Mechanism of Superplasticity	12
2.1.4. Application of Superplasticity	17
2.2. Boronizing	21
2.2.1. Mechanism of Boronizing	23
2.2.2. Pack Boronizing	24
2.2.3. Superplastic Boronizing	27
2.3. Boronizing Substrate	29
2.3.1. Duplex Stainless Steel	29
2.3.2. Superplastic Duplex Stainless Steel	31
3. Experimental Procedure	34
3.1. Substrate Material	34
3.2. Material Preparation	35
3.3. Design Boronizing Crucible	36
3.4. Superplastic Boronizing Process	37
3.5. Characterization Methods	40
3.5.1. Optical Microscope	40
3.5.2. Scanning Electron Microscopy	41
3.5.3. Microhardness Test	43
3.5.4. X-ray Diffraction	44
4. Results and Discussions	45
4.1. Substrate Material	45

4.2. Superplastic Boronizing	48
4.2.1. XRD Analysis	49
4.2.2. Flow Stress Behaviour	50
4.2.3. Microstructure of Boronized Layer	52
4.2.4. Hardness Profile	56
4.2.5. Activation Energy Analysis	59
4.2.6. Powder Consumption	62
5. Conclusions and Recommendations	64
5.1. Conclusions	64
5.2. Recommendations	65
References	66

## List of Figures

<b>Figure</b>	<b>Caption</b>	<b>Page</b>
2.1	A demonstration of superplasticity in Cu-Al alloy with 8000% elongation	7
2.2	Stain rate sensitivity exponent versus strain rate	10
2.3	Stress versus strain rate with superplastic behavior	11
2.4	Grain boundaries sliding	13
2.5	Evolution of microstructure during (a) superplastic and (b) plastic deformation	14
2.6	Basic accommodation mechanisms of superplasticity (a) diffusional accommodation (b) accommodation by dislocation motion (c) dislocation motion inside the mantle results in the grain rotation (d) combined model with elements of dislocation and diffusional accommodation	16
2.7	Superplastic forming (a) SPF process (b) Tool for a Landrover front part	19

2.8	Superplastic diffusion bonding and superplastic forming (SDB/SF)	
	(a) SDB/SPF process steps (b) SDB/SPF formed component	20
2.9	Schematic diagram of powder pack boronizing	25
2.10	The boride layer formation mechanism during conventional boronizing	
	(a) nucleation (b) and (c) growth	28
2.11	The boride layer formation mechanism during SPB	28
2.12	Microstructure of DSS	30
2.13	Fe-Cr-Ni phase diagram	31
2.14	Microstructure of fine grain DSS	33
3.1	Schematic diagram of thermo-mechanical treatment process of DSS	35
3.2	Sample preparation	35
3.3	Schematic diagram of boronizing crucible	37
3.4	Schematic diagram of experimental apparatus	38

3.5	Illustration of boronizing experiment	39
3.6	Optical microscope with image analyzer system	41
3.7	Scanning electron microscope	42
3.8	Microhardness tester	43
3.9	XRD machine	44
4.1	SEM image of microstructure of the coarse DSS	46
4.2	DSS microstructure after solution treated at 1573 K for 1 hour, water quenched and cold rolled up to 75%. (a) SEM image, (b) Optical micrograph	47
4.3	Side view of specimen before (left) and after (right) SPB at compressive strain of 0.2 at temperature 1223 K	48
4.4	Microstructure of a specimen after compression for 0.6 strains at 1223 K at $2 \times 10^{-4} \text{ s}^{-1}$ strain rate.	49
4.5	The XRD patterns of DSS before and after boronizing	50

4.6	Stress strain relation of specimens at 0.4 strains	51
4.7	Cross section images of SPB specimens at three different temperatures. (0.4 strains); (a) $T_1 = 1223$ K, (b) $T_2 = 1273$ K, (c) $T_3 = 1323$ K	54
4.8	Cross section images of SPB specimens at two different strain under 1273 K. (a) strain = 0.2, (b) strain = 0.6	55
4.9	The variation of boronized layer thickness with boronizing time and temperature for superplastically boronized DSS	56
4.10	Hardness gradient of cross-sectioned specimens deformed at strain 0.2	57
4.11	Surface hardness profiles	58
4.12	Microhardness profile measured on sectioned surface of superplastically boronized DSS for 2000 seconds at 1323 K	58
4.13	Square of boronized layer thickness versus boronizing time	60
4.14	Natural logarithm of boron growth rate ( $\ln K$ ) $\text{m}^2\text{s}^{-1}$ versus reciprocal boronizing temperature ( $T^{-1}$ ) s for superplastically boronized DSS	62

## List of Tables

<b>Table</b>	<b>Caption</b>	<b>Page</b>
3.1	Chemical composition of DSS	34
3.2	Experimental conditions for SPB study	39
4.1	Boronized layer thickness and surface hardness for SPB with a strain rate of $2 \times 10^{-4} \text{ s}^{-1}$ , at various temperatures and strains	55
4.2	Boronizing powder amount in conventional and superplastic boronizing of DSS	63