

LIST OF FIGURES

| Figure | Caption | Page |
|------------|--|------|
| Figure 2.1 | Conductivity-temperature dependence for chitosan-NH ₄ I | 9 |
| Figure 2.2 | Conductivity-temperature dependence for highest conducting film in methyl cellulose-NH ₄ NO ₃ complex system | 10 |
| Figure 2.3 | Activation energy and room temperature conductivity variation with NH ₄ CF ₃ SO ₃ concentration | 12 |
| Figure 2.4 | Structure of NH ₄ ⁺ cations | 13 |
| Figure 2.5 | H ⁺ ion transport mechanism in chitosan-salt system | 14 |
| Figure 2.6 | Structure of chitin | 15 |
| Figure 2.7 | Structure of chitosan | 15 |
| Figure 2.8 | Structure of PVA | 18 |
| Figure 2.9 | Structure of acetic acid | 24 |
| Figure 3.1 | Flow chart of the experimental work undertaken | 33 |
| Figure 3.2 | Conductivity holder with blocking stainless steel electrodes | 37 |
| Figure 3.3 | Dielectric constant-frequency plots for PVA-NH ₄ I, PVA-NH ₄ Br and PVA-NH ₄ Cl | 39 |
| Figure 3.4 | Dielectric constant-frequency plots for PVA-NH ₄ Br at different temperatures | 40 |
| Figure 3.5 | FTIR spectra of a (a) pure chitosan acetate (CA) film, (b) CA + 35 wt.% NH ₄ NO ₃ , (c) CA + 40 wt.% NH ₄ NO ₃ , (d) CA + 45 wt.% NH ₄ NO ₃ and (e) CA + 50 wt.% NH ₄ NO ₃ | 45 |
| Figure 3.6 | FTIR spectra of PVA-NH ₄ I system: (a) 5 mol%, (b) 10 mol%, (c) 15 mol%, (d) 20 mol%, (e) 25 mol% and (f) 30 mol% NH ₄ I | 46 |
| Figure 3.7 | XRD pattern of methyl cellulose-NH ₄ NO ₃ system | 48 |
| Figure 3.8 | XRD diffractogram of (a) pure PVA, (b) 85PVA:15NH ₄ Cl, (c) 75PVA:25NH ₄ Br and (d) 75PVA:25NH ₄ I | 49 |

| | | |
|-------------|---|----|
| Figure 3.9 | Room temperature (Ionic conductivity of microporous PVdF- $x\%$ PEO membranes (soaked in 1 mol L ⁻¹ LiClO ₄ /PC solution) at 25°C together with some SEM images | 50 |
| Figure 3.10 | (a) Schematic diagram and (b) picture of the battery holder | 52 |
| Figure 3.11 | Two readings of linear sweep voltammogram for methyl cellulose-NH ₄ NO ₃ polymer electrolyte at room temperature | 53 |
| Figure 3.12 | Open circuit voltage of proton battery during 24 hours of storage | 54 |
| Figure 3.13 | Discharge curves for proton battery at constant current drain of 1 mA | 55 |
| Figure 3.14 | Voltage-time plot of rechargeable PEO: NH ₄ ClO ₄ (85:15wt.%) + PC 5wt. % electrolyte based proton cell under a load of 57K Ω | 56 |
| Figure 3.15 | Schematic diagram of EDLC fabrication | 57 |
| Figure 3.16 | The 15 th cycle charge-discharge curves of EDLC at different current densities for working voltage of 0.85 V | 58 |
| Figure 3.17 | Discharge capacitance versus cycle number for EDLC | 59 |
| Figure 4.1 | XRD pattern of PVA, chitosan and PVA-chitosan blends with the corresponding ratio | 62 |
| Figure 4.2 | SEM surface morphology of pure C4P6 film | 64 |
| Figure 4.3 | SEM cross section morphology of pure C4P6 film | 65 |
| Figure 4.4 | SEM surface morphology of pure C7P3 film | 65 |
| Figure 4.5 | SEM surface morphology of pure C8P2 film | 66 |
| Figure 4.6 | SEM surface morphology of pure C1P9 film | 67 |
| Figure 4.7 | Enlarged portion of C1P9 showing the pores (white circles) that can be observed on the surface of a PVA-rich sample | 67 |
| Figure 5.1 | FTIR spectra of (i) pure chitosan powder, (ii) pure chitosan film and (iii) C4P6 film in the 1490 to 1690 cm ⁻¹ spectra region | 70 |
| Figure 5.2 | FTIR spectra of (i) pure PVA, (ii) PVA film, (iii) pure chitosan powder, (iv) pure chitosan film and (v) C4P6 film in the 3000 to 3700 cm ⁻¹ spectra region | 71 |

| | | |
|-------------|--|----|
| Figure 5.3 | Schematic diagram of PVA-chitosan blend having a hydrogen bonding | 73 |
| Figure 5.4 | FTIR spectra of (i) pure chitosan film and pure chitosan film with (ii) 10 wt.% NH_4NO_3 , (iii) 30 wt.% NH_4NO_3 , (iv) 50 wt.% NH_4NO_3 and (v) pure NH_4NO_3 salt in the 3000 to 3700 cm^{-1} spectra region | 74 |
| Figure 5.5 | Schematic diagram of chitosan having interaction with NH_4NO_3 at hydroxyl group | 75 |
| Figure 5.6 | FTIR spectra of (i) pure chitosan film and chitosan with (ii) 20 wt.% NH_4NO_3 , (iv) 30 wt.% NH_4NO_3 , (v) 40 wt.% NH_4NO_3 and (vi) 50 wt.% NH_4NO_3 in the 1490 to 1700 cm^{-1} spectra region | 76 |
| Figure 5.7 | Schematic diagram of complexation between amine group in chitosan with NH_4NO_3 salt | 78 |
| Figure 5.8 | FTIR spectra of (i) pure PVA film and PVA with (ii) 10 wt.% NH_4NO_3 , (iii) 20 wt.% NH_4NO_3 , (iv) 30 wt.% NH_4NO_3 , (v) 50 wt.% NH_4NO_3 and (vi) pure NH_4NO_3 salt in the 3000 to 3700 cm^{-1} spectra region | 79 |
| Figure 5.9 | Schematic diagram of complexation between OH group in PVA with NH_4NO_3 salt | 80 |
| Figure 5.10 | FTIR spectra of (i) pure chitosan film and chitosan with (ii) 10 wt.% EC, (iii) 30 wt.% EC and (iv) 50 wt.% EC in the 1450 to 1750 cm^{-1} spectra region | 81 |
| Figure 5.11 | FTIR spectra of (i) pure chitosan film and chitosan with (ii) 10 wt.% EC, (iii) 30 wt.% EC and (iv) 50 wt. % EC in the 2990 to 3590 cm^{-1} spectra region | 82 |
| Figure 5.12 | FTIR spectra of (i) pure PVA film and PVA with (ii) 10 wt.% EC, (iii) 30 wt.% EC and (iv) 50 wt.% EC in the 3000 to 3700 cm^{-1} spectra region | 83 |
| Figure 5.13 | FTIR spectra of (i) C4P6 and C4P6 with (ii) 10 wt.% EC, (iii) 30 wt.% EC and (iv) 50 wt.% EC in the 2990 to 3590 cm^{-1} spectra region | 84 |
| Figure 5.14 | FTIR spectra of (i) C4P6 and C4P6 with (ii) 10 wt.% EC, (iii) 30 wt.% EC and (iv) 50 wt.% EC in the 1505 to 1685 cm^{-1} spectra region. | 85 |
| Figure 5.15 | FTIR spectra of (i) pure EC, (ii) EC mixed with 0.5 wt.% NH_4NO_3 and (iii) EC mixed with 1.1 wt. % NH_4NO_3 in the region of C=O bending band | 86 |

| | | |
|-------------|---|-----|
| Figure 5.16 | FTIR spectra of (i) pure EC, (ii) EC mixed with 0.5 wt.% NH_4NO_3 and (iii) EC mixed with 1.1 wt.% NH_4NO_3 in the region of C=O stretching band | 87 |
| Figure 5.17 | FTIR spectra for (i) C4P6, (ii) 90[C4P6]-10AN, (iii) 80[C4P6]-20AN, (iv) 60[C4P6]-40AN and (v) 50[C4P6]-50AN in the 1500 to 1680 cm^{-1} spectra region | 89 |
| Figure 5.18 | FTIR spectra for (i)C4P6, (ii)90[C4P6]-10AN, (iii) 80[C4P6]-20AN, (iv) 60[C4P6]-40AN, (v)50[C4P6]-50AN and (vi) pure NH_4NO_3 in the 2970 to 3700 cm^{-1} spectra region | 90 |
| Figure 5.19 | H^+ conduction mechanism in salted system | 91 |
| Figure 5.20 | FTIR spectra for (i) 60[C4P6]-40AN, (ii) 30[60C4P6-40AN]-70EC and (iii) 20[60C4P6-40AN]-80EC in the region of C=O bending band | 92 |
| Figure 5.21 | FTIR spectra for (i)60[C4P6]-40AN, (ii)60[60C4P6-40AN]-40EC, (iii) 40[60C4P6-40AN]-60EC, (iv) 30[60C4P6-40AN]-70EC and (v) 20[60C4P6-40AN]-80EC in the region of C=O stretching band | 93 |
| Figure 5.22 | H^+ conduction mechanism in plasticized system | 94 |
| Figure 6.1 | Cole-Cole plot of the pure C4P6 film | 97 |
| Figure 6.2 | Cole-Cole plot of the sample film 60[C4P6]-40AN | 98 |
| Figure 6.3 | The dependence of ionic conductivity of salted system at room temperature | 99 |
| Figure 6.4 | XRD diffractogram of (a) 60[C4P6]-40AN film and (b) pure NH_4NO_3 | 100 |
| Figure 6.5 | SEM surface morphology of 60[C4P6]-40AN film | 101 |
| Figure 6.6 | XRD diffractogram of (a) 50[C4P6]-50AN film and (b) pure NH_4NO_3 | 102 |
| Figure 6.7 | SEM surface morphology of 50[C4P6]-50AN film | 103 |
| Figure 6.8 | XRD diffractogram of (a) 40[C4P6]-60AN film and (b) pure NH_4NO_3 | 103 |
| Figure 6.9 | SEM surface morphology of 40[C4P6]-60AN film | 104 |
| Figure 6.10 | Dielectric constant versus frequency for salted system at room temperature | 106 |

| | | |
|-------------|--|-----|
| Figure 6.11 | Dielectric constant versus frequency for sample 60[C4P6]-40AN at elevated temperatures | 107 |
| Figure 6.12 | Temperature dependent conductivity for salted system | 108 |
| Figure 6.13 | Activation energy for salted system | 109 |
| Figure 6.14 | Number density of mobile ions, n for salted system at different temperatures for $l = 10 \text{ \AA}$ | 113 |
| Figure 6.15 | Mobility of ions, μ for salted system at different temperatures for $l = 10 \text{ \AA}$ | 113 |
| Figure 6.16 | Number density of mobile ions, n for salted system at different temperatures for $l = 6 \text{ \AA}$ | 114 |
| Figure 6.17 | Mobility of ions, μ for salted system at different temperatures for $l = 6 \text{ \AA}$ | 114 |
| Figure 6.18 | Number density of mobile ions, n for salted system at different temperatures for $l = 3 \text{ \AA}$ | 115 |
| Figure 6.19 | Mobility of ions, μ for salted system at different temperatures for $l = 3 \text{ \AA}$ | 115 |
| Figure 6.20 | Cole-Cole plot of the sample 30[60C4P6-40AN]-70EC film | 116 |
| Figure 6.21 | The dependence of ionic conductivity on EC at room temperature | 117 |
| Figure 6.22 | XRD diffractogram of 60[60P40C-40AN]-40EC film | 118 |
| Figure 6.23 | SEM images of 60[60C4P6-40AN]-40EC film | 119 |
| Figure 6.24 | XRD diffractogram of 40[60C4P6-40AN]-60EC film | 119 |
| Figure 6.25 | SEM images of 40[60C4P6-40AN]-60EC film | 120 |
| Figure 6.26 | Enlarged portion of 40[60C4P6-40AN]-60EC showing the pores (white circles) that can be observed on the surface of the film | 121 |
| Figure 6.27 | XRD diffractogram of 30[60C4P6-40AN]-70EC film | 121 |
| Figure 6.28 | SEM images of 30[60C4P6-40AN]-70EC film | 122 |
| Figure 6.29 | Enlarged portion of 30[60C4P6-40AN]-70EC showing the pores (white circles) that can be observed on the surface of the film | 122 |
| Figure 6.30 | XRD diffractogram of 20[60C4P6-40AN]-80EC film | 123 |

| | | |
|-------------|---|-----|
| Figure 6.31 | SEM images of 20[60C4P6-40AN]-80EC film | 123 |
| Figure 6.32 | Enlarged portion of 20[60C4P6-40AN]-80EC showing the pores (white circles) that can be observed on the surface of the film | 124 |
| Figure 6.33 | Dielectric constant versus frequency for plasticized system with different EC concentration at room temperature | 126 |
| Figure 6.34 | Dielectric constant versus frequency for 30[60C4P6-40AN]-70EC sample at different temperature | 127 |
| Figure 6.35 | Temperature dependent conductivity for plasticized system with different plasticizer concentration | 128 |
| Figure 6.36 | Activation energy for plasticized system | 129 |
| Figure 6.37 | Number density of mobile ions, n as a function of temperature for plasticized system for $l = 10 \text{ \AA}$ | 133 |
| Figure 6.38 | Ionic mobility of ions, μ as a function of temperature for plasticized system for $l = 10 \text{ \AA}$ | 133 |
| Figure 6.39 | Number density of mobile ions, n as a function of temperature for plasticized system for $l = 6 \text{ \AA}$ | 134 |
| Figure 6.40 | Ionic mobility of ions, μ as a function of temperature for plasticized system for $l = 6 \text{ \AA}$ | 134 |
| Figure 6.41 | Number density of mobile ions, n as a function of temperature for plasticized system for $l = 3 \text{ \AA}$ | 135 |
| Figure 6.42 | Ionic mobility of ions, μ as a function of temperature for plasticized system for $l = 3 \text{ \AA}$ | 135 |
| Figure 7.1 | Linear sweep voltammogram at 5 mV s^{-1} | 138 |
| Figure 7.2 | OCP of $\text{Zn} + \text{ZnSO}_4 \cdot 7\text{H}_2\text{O}/30[60\text{C4P6-40AN}]-70\text{EC}/\text{MnO}_2$ cells during 24 hours of storage | 140 |
| Figure 7.3 | Discharge curves of primary proton batteries at 2 mA constant current | 141 |
| Figure 7.4 | Discharge curves of primary proton batteries at 1 mA and 3.5 mA current | 141 |
| Figure 7.5 | Voltage-Current-Power characteristic of primary proton batteries | 143 |
| Figure 7.6 | OCP of $\text{Zn} + \text{ZnSO}_4 \cdot 7\text{H}_2\text{O}/30[60\text{C4P6-40AN}]-70\text{EC}/\text{MnO}_2 + \text{liquid electrolyte}$ cells during 24 hours of storage | 144 |

| | | |
|-------------|--|-----|
| Figure 7.7 | Discharge-charge characteristic of secondary proton battery | 145 |
| Figure 7.8 | Discharge curve for secondary proton battery at cycle 1, 4 and 9 | 146 |
| Figure 7.9 | Discharge capacity of secondary proton battery | 147 |
| Figure 7.10 | Discharge capacity of secondary proton battery considering the active material (MnO_2) in the cathode | 147 |
| Figure 7.11 | Charged and discharged curves for the EDLC at 0.095 mA cm^{-2} current density | 148 |
| Figure 7.12 | Charged and discharged curves for the EDLC at 0.381 mA cm^{-2} constant current density | 149 |
| Figure 7.13 | Discharged curves for the EDLC at 0.095 mA cm^{-2} constant current density | 150 |
| Figure 7.14 | Discharged curves for the EDLC at 0.381 mA cm^{-2} constant current density | 150 |
| Figure 7.15 | Discharged capacitance versus cycle number for the EDLC at different current density | 151 |
| Figure 7.16 | Specific stored energy versus cycle number for the EDLC at different current density | 152 |