CONTENTS

Abstı	ract		i
Acknowledgement			iv
Contents			v
List o	of Figure	s	vii
List o	of Tables		xi
CHA	PTER (ONE: INTRODUCTION	1
1.1	History	y of Plastics	1
1.2	Plastic	Usage	2
	1.2.1	Malaysia	2
	1.2.2	World	3
1.3 Plastic Waste		7	
	1.3.1	Malaysia	7
	1.3.2	World	8
1.4	Object	ives	10
CHA	APTER T	TWO: LITERATURE REVIEW	13
2.1	Biodeg	gradable Plastics	13
	2.1.1	Definition of Biodegradable Plastics	14
	2.1.2	Types of Biodegradable Plastics	16
	2.1.3	Plastics Application	20
	2.1.4	Biodegradation Mechanisms	23
	2.1.5	Characterisation of Degradation	27
	2.1.6	Composting	29
2.2	Plastic	Waste Management	30
	221	Life Cycle Engineering	31

	2.2.2	Mechanical Recycling	3:
	2.2.3	Energy Recovery	4
	2.2.4	Biological Recycling	4
2.3	Enviro	nmental Impact of Plastic	5
	2.3.1	Plastics and Raw Materials	53
	2.3.2	Plastics and Energy	5-
	2.3.3	Plastics and Production Effluents	5
	2.3.4	Plastics and Waste	5
2.4	Releva	nce to Project	6
CHAPTER THREE: MATERIALS AND METHODS			6
3.1	Sample	es	6
3.2	Hydrolytic and Oxidative Exposure		6
3.3	Composting Exposure		6
3.4	Microbiological Exposure		7
CHAPTER FOUR: RESULTS AND DISCUSSION			7
4.1	Hydrol	ytic Exposure	7
4.2	Oxidative Exposure		8
4.3	Compo	osting Exposure	9
4.4	Microb	piological Exposure	10
CHA	PTER F	FIVE: GENERAL DISCUSSION	10
CHA	PTER S	SIX: CONCLUSION	11
REFERENCE			11
AST	APPENDIX 1 ASTM D 6002-96 ASTM D 6003-96		

ASTM G 22-76

LIST OF FIGURES

Figure 1.1	Market segments in Malaysia in year 2000	2
Figure 1.2	Resin consumption and per capita consumption in Malaysia	3
Figure 1.3	Total consumption and per capita consumption in Western	5
	Europe	
Figure 1.4	Market segments in for plastics United States in year 2000	5
Figure 1.5	Total post-user plastics waste by sector, Western Europe	9
	1999	
Figure 2.1	Drivers of materials technology shifts	14
Figure 2.2	Natural carbon cycle	16
Figure 2.3	Polymer derived from corn feedstock	17
Figure 2.4	Biodegradation trigger mechanisms	23
Figure 2.5	Formation of carboxylic acids and esters in the oxidation of	25
	polyethylene	
Figure 2.6	Properties of the ideal degradable plastic	26
Figure 2.7	Techniques to determine polymer degradation	28
Figure 2.8	Life cycle engineering practices	33
Figure 2.9	Plastic waste management options	35
Figure 2.10	Cost balance for recovery of source separated household	38
	plastic packaging and industrial waste	
Figure 2.11	Eco-efficiency of plastics packaging waste management	39
Figure 2.12	Influence of residue burn out	45
Figure 2.13	PCDD/F balance base case without additional plastics	46
Figure 2.14	PCDD/F balance with additional plastics	47
Figure 2.15	Degradation of materials containing C.H.O	50

Figure 2.16	input of energetically valuable resources in the production of	3-
	polymers	
Figure 3.1	Schematic drawing of the aerobic bioreactor	67
Figure 3.2	Schematic of the laboratory-scale composting system	68
Figure 4.1	Changes in mass of McD samples on exposure to thermal	73
	hydrolytic conditions (60°) for various time periods	
Figure 4.2	Changes in mass of LL samples on exposure to thermal	74
	hydrolytic conditions (60°) for various time periods	
Figure 4.3	Changes in mass of TDP samples on exposure to thermal	74
	hydrolytic conditions (60°) for various time periods	
Figure 4.4	Visual McD sample on exposure to thermal hydrolytic	75
	conditions after 60 days	
Figure 4.5	Visual LL sample on exposure to thermal hydrolytic	75
	conditions after 60 days	
Figure 4.6	Visual TDP sample on exposure to thermal hydrolytic	76
	conditions after 60 days	
Figure 4.7	Changes in functional group of McD sample on exposure to	77
	thermal hydrolytic conditions after 60 days	
Figure 4.8	Changes in functional group of LL sample on exposure to	77
	thermal hydrolytic conditions after 60 days	
Figure 4.9	Changes in functional group of TDP sample on exposure to	78
	thermal hydrolytic conditions after 60 days	
Figure 4.10	Changes in mass of McD samples on exposure to thermal	82
	oxidative conditions (60°) for various time periods	
Figure 4.11	Changes in mass of LL samples on exposure to thermal	82
	oxidative conditions (60°) for various time periods	

Figure 4.12	Changes in mass of IDP samples on exposure to thermal	8.
	oxidative conditions (60°) for various time periods	
Figure 4.13	Visual McD sample on exposure to thermal oxidative	84
	conditions after 60 days	
Figure 4.14	Visual LL sample on exposure to thermal oxidative	84
	conditions after 60 days	
Figure 4.15	Visual TDP sample on exposure to thermal oxidative	85
	conditions after 60 days	
Figure 4.16	Changes in functional group of McD on exposure to thermal	87
	oxidative conditions after 60 days	
Figure 4.17	Changes in functional group of LL sample on exposure to	87
	thermal oxidative conditions after 60 days	
Figure 4.18	Changes in functional group of TDP sample on exposure to	88
	thermal oxidative conditions after 60 days	
Figure 4.19	Changes in mass of McD sample on exposure to composting	91
	conditions for various time periods	
Figure 4.20	Changes in mass of LL sample on exposure to composting	92
	conditions for various time periods	
Figure 4.21	Changes in mass of TDP sample on exposure to composting	92
	conditions for various time periods	
Figure 4.22	Average pH and percentage moisture content of synthetic	93
	compost mixture variations against time	
Figure 4.23	Changes in functional group of McD sample on exposure to	95
	composting conditions after 60 days	
Figure 4.24	Changes in functional group of LL sample-on exposure to	95
	composting conditions after 60 days	

Figure 4.25	Changes in functional group of TDP sample on exposure to	96
	composting conditions after 60 days	
Figure 4.26	Viability control of microbiological exposure	103
Figure 4.27	Inoculated pre-degraded polyethylene sample plate after 28	104
	days of microbiological exposure	
Figure 4.28	Inoculated LL plate after 28 days of microbiological	104
	exposure	
Figure 4.29	Uninoculated pre-degraded polyethylene sample plate after	105
	28 days of microbiological exposure	

LIST OF TABLES

Table 1.1	Plastic consumption by industry sector in Western Europe	4
Table 1.2	Total sales and captive use of selected plastics by major	e
	markets in United States	
Table 1.3	Municipal solid waste composition in Kuala Lumpur and	8
	Labuan (% weight)	
Table 1.4	Total solid waste and total plastic post-user waste in Western	8
	Europe from 1997 to 1999	
Table 1.5	Increase of plastics components in United States MSW	10
Table 2.1	Crop yields with and without mulching films	20
Table 2.2	Calorific values plastics compared with conventional fuels	41
Table 2.3	Energy values of common materials in MSW	42
Table 2.4	Different feed conditions scenarios	44
Table 2.5	Clean gas emissions during packaging co-combustion	44
Table 2.6	Environmental impact of different recovery methods per tonne	48
	of post-separated plastic waste	
Table 2.7	Composition of gaseous products from pyrolysis of mixed	49
	plastics (wt%)	
Table 2.8	Advantages and disadvantages of polymer waste management	51
	options	
Table 2.9	Energy ^a requirements for the production of materials used in	55
	packaging	
Table 2.10	Energy requirements for similar beverage containers	56
Table 2.11	Air and water pollution associated with the production of	58
	50 000 carrier bags	

Plastic contents in wastes from a few locations in Petaling Jaya,	5
Malaysia	
Polymeric materials evaluated in the study	62
Urban municipal waste composition (% weight)	6:
Synthetic MSW mixture used in this trial	6
Normal saline solution	7
Carbon free medium	7
Changes in percentage elongation at break point on exposure to	70
thermal hydrolytic conditions	
Changes in percentage elongation at break point on exposure to	85
thermal oxidative conditions	
Changes in percentage elongation at break point on for samples	94
exposed to composting environment after 45 days	
Case studies on the biodegradability of EPI TDPATM plastics	97
according to data provided by EPI	
Changes in mass on of pre-degraded polyethylene sample	101
exposed to inoculation of Pseudomonas aeruginosa after 28	
days	
Changes in pre-degraded polyethylene samples mass in	102
uninoculated plates after 28 days	
Rating scheme based on visual assessment used by ISO 846 for	102
assessing fungal resistance of plastics	
	Malaysia Polymeric materials evaluated in the study Urban municipal waste composition (% weight) Synthetic MSW mixture used in this trial Normal saline solution Carbon free medium Changes in percentage elongation at break point on exposure to thermal hydrolytic conditions Changes in percentage elongation at break point on exposure to thermal oxidative conditions Changes in percentage elongation at break point on for samples exposed to composting environment after 45 days Case studies on the biodegradability of EPI TDPATM plastics according to data provided by EPI Changes in mass on of pre-degraded polyethylene sample exposed to inoculation of <i>Pseudomonas aeruginosa</i> after 28 days Changes in pre-degraded polyethylene samples mass in uninoculated plates after 28 days Rating scheme based on visual assessment used by ISO 846 for