# **CLOSED STACKS**

# PRODUCTION OF A LIPOPEPTIDE BIOSURFACTANT BY Bacillus licheniformis JF-2

SURESH KUMAR LACHIMPADI

A dissertation submitted to the Institute of Advanced Studies, University of Malaya, In partial fulfilment of the requirements for the Degree of Master of Biotechnology

January, 1997



	02.11.	2000
Dimikrofiskan pada No. Mikrofis	149	98
nedek Mikrofia	9	
HAMSIAH BT.	ALL DOLL	
TOTAL BI.	MICHARINE	U ZAHARI
IPR UNIT	REPRO	BRAFI

#### ACKNOWLEDGEMENT

I would like to specially thank my supervisors, Prof. Ho Coy Choke and Prof. Mohd Ali Hashim for their committed encouragement and support throughout my research at IPT. A special thanks to my former supervisor Dr. John J. Thambirajah who gave me the direction in my work and for the support during some difficult periods.

My stay at IPT was a happy one and this was made possible by my friends namely, Muru, Samina, Melor, Ching-Lee, Ahsan, Albert, Maha, and Vinitha.

Thin layer chromatography was made possible by the help of Mr. Yoganathan of the Chemistry Department, University of Malaya, and some preliminary work on HPLC and the use of equipments was made possible by Mr. Gopal of the Department of Genetics and Cellular Biology, University of Malaya.

A special thanks goes to all my lectures of the biotechnology course, namely Dr. Vikineswary, Dr. Phang Siew Moi, and Prof. C.A. Sastry. I must also thank all the staff of the office, in particular, Mr. Ghana, Cik Zubaidah, Pn Rodziah, Wan, Liza, Selvam, Mr. Ooi, Zul, En. Ismail, Azizi and the helpful staff of the IPT library.

Last but not least, I thank my wife, Saras for all the help given to me during this period. I dedicate this piece work to my loving parents, MUM and DAD.

# CONTENTS

		Page
ACF	KNOWLEDGEMENTS	ii
ABS	TRACT	viii
LIS	T OF TABLES	xi
LIS	T OF FIGURES	xiii
LIS	T OF PLATES	xvii
LIS	T OF APPENDICES	xix
LIS	T OF ABBREVIATIONS	xx
1.0	INTRODUCTION	1
2.0	LITERATURE REVIEW	7
	2.1 Biosurfactants in biotechnology	7
	2.2 Biosurfactants	8
	2.3 Classification of biosurfactant	11
	2.4 Bacillus licheniformis JF-2	17
	2.5 The industrial use of Bacillus licheniformis	20
	2.6 Biosynthesis of biosurfactants	22
	2.7 The physiology of microorganisms affecting the yield of biosurfactants	23
	2.7.1 Culture conditions affecting the yield of the lipopeptide biosurfactants	23
	2.7.2 Nutritional factors affecting the yield of the biosurfactant	24
	2.7.3 Carbon source for biosurfactant production	26
	2.8 Surfactants in the petroleum industry	29

# 3.0 MATERIALS AND METHODS

3.1	Culture		33
3.2	Media		33
	3.2.1	Inoculum preparation	33
	3.2.2	Fermentation	35
3.3	Physical	parameters	35
	3.3.1	Biomass	35
	3.3.2	pH	35
	3.3.3	Surface tension	36
	3.3.4	Emulsification Measurement (E <sub>24</sub> )	37
	3.3.5	Thin Layer Chromatography	37
3.4	Wastew	ater analysis	38
	3.4.1	Chemical Oxygen Demand (COD)	38
	3.4.2	Dissolved phosphate	40
	3.4.3	Determination of total sugar	42
	3.4.4	Determination of reducing sugar (Miller, 1959)	42
	3.4.5	Total Nitrogen	43
3.5	Determi	nation of crude lipopeptide yield (g/l)	44
	3.5.1	Acid precipitation method for shake flask cultures	44
	3.5.2	Foam fractionation method for isolating the biosurfactant from fermenter runs	44
3.6	Process	optimization	48
	3.6.1	Initial pH	48
	3.6.2	Temperature	48

3.7 Media op	ptimization	49
3.7.1	The effect of various concentrations of sodium chloride on the growth and biosurfactant production by <i>B. licheniformis</i> JF-2 without glucose	49
3.7.2	The effect of various concentrations of sodium chloride on the growth of <i>B. licheniformis</i> JF-2 in Nutrient broth supplemented with glucose	49
3.7.3	The effect of various concentrations of yeast extract on the growth and biosurfactant production by <i>B. licheniformis</i> JF-2.	50
3.7.4	A time course study of <i>B. licheniformis</i> JF-2 in the final optimized growth medium	50
3.8 Fermentation .		
3.8.1	The growth and biosurfactant production by B. licheniformis JF-2 in a 1.5L capacity Biolab fermenter	51
3.8.2	Production of biosurfactant by B. licheniformis JF-2 in selected media	52
3.9 Growth o	of <i>B. licheniformis</i> JF-2 in agro-industrial wastewater	53
3,10 Treatm	ent of edible palm oil processing wastewater	54
3.10.1	Acclimatisation of seed culture	54
3.10.2	2 Treatment of edible palm oil processing wastewater by the activated sludge process	54
3.10.3	Treatment of edible palm oil processing wastewater using B. licheniformis JF-2	55

# 4.0 RESULTS

4.1 Process (	Optimization	56
4.1.1	Temperature optimization for the growth of B. licheniformis JF-2	56
4.1.2	Determination of optimum pH for growth and production of the lipopeptide by <i>B. licheniformis</i> JF-2	58
4.2 Media O	ptimization	61
4.2.1	Effect of sodium chloride (NaCl) on the growth and lipopeptide synthesis by <i>B. licheniformis</i> JF-2	61
4.2.2	Effect of 5% and 10% glucose in the cultivation medium containing NaCl on the growth and lipopeptide production by <i>B. licheniformis</i> JF-2	63
4.2.3	Effect of various concetrations of Yeast extract (YE) on the growth and lipopeptide yield of <i>B. licheniformis</i> JF-2	65
4.2.4	Production of biomass and lipopeptide by B. licheniformis JF-2 in shake flask cultures using the Optimized medium (OM)	70
4.2.5	A comparison of Medium E (ME) and our Optimized Medium (OM) in shake flask culture for the production of biomass and lipoptide from <i>B. licheniformis</i> JF-2	72
	ation of the crude lipopeptide biosurfactant ayer chromatography	74
lipopepti JF-2 afte	Micelles Concentration (CMC) of the crude de obtained from the growth of <i>B. licheniformis</i> or 8 hours of fermentation in the Optimized in shake flask cultures	77
	ation studies on <i>B. licheniformis</i> JF-2 in a blab Fermenter	78
4.5.1	The production of biomass and lipopeptide from <i>B. licheniformis</i> JF-2 using the optimized medium (OM) in a 1.5L capacity fermenter (B. Braun Biolab)	78

		4.5.2	Production of the biosurfactant by B. licheniformis JF-2 in mineral salts medium compared to the optimized medium in a 1.5 litre fermenter (B. Braun Biolab)	84
	4.6		ormulation with locally available agro-industrial acts for the cultivation of <i>B. licheniformis</i>	89
		4.6.1	Palm oil mill effluent (POME) as a growth medium for <i>B. licheniformis</i> JF-2	90
		4.6.2	Rubber effluent (RE) as a growth medium for <i>B. licheniformis</i> JF-2	94
		4.6.3	Dairy wastewater as a cultivation medium for <i>B. licheniformis</i> JF-2	97
		4.6.4	Use of sugar cane molasses as an additional carbon source in dairy wastewater for cultivation of <i>B. licheniformis</i> JF-2	101
		4.6.5	Use of Fish Meal (FM) as a nitrogen source for the cultivation of <i>B. licheniformis</i> JF-2	105
	4.7		on of the biosurfactant in the removal of crude solid surfaces	108
	4.8	to a bioa	pplication of <i>B. licheniformis</i> JF-2 compared ugmentation culture (JAD 969P) for the tof edible palm oil processing wastewater	109
5.0	DISC	CUSSION		
	5.1	Process (	Optimization	114
	5.2	Scale-up	to a 1.5L capacity Biolab fermenter	117
	5.3		on of agro-industrial by-products in the on media for the growth of <i>B. licheniformis</i>	121
	5.4	Wastewat	er treatment	122
REF	ERE	NCES		125

#### ABSTRACT

A lipopeptide biosurfactant is produced by *Bacillus licheniformis* JF-2. The biosurfactant has found application in *in-situ* microbial enhanced crude petroleum recovery whereby the bacteria is able to grow facultatively and anaerobically under extreme conditions of temperature, pH and salinity (Javaheri *et al.*, 1985). An attempt was made in this thesis to formulate a cultivation medium which would enhance the growth of the microorganism in order to achieve high yields of biomass. Process optimization was achieved in Nutrient broth whereby the initial pH was recorded at 7.0, temperature of 40°C and at an agitation speed of 250 rpm in shake flask cultures. The maximum absorbance achieved was 1.14 at the end of the log phase (8 hours) which was similar to the maximum absorbance achieved by Jenneman *et al.* (1983) between 1.0 to 1.2 obtained after 20 hours of growth in Medium E. The log phase lasted 5 hours in our study, approximately 14 hours was reported in Medium E conducted by Jenneman *et al.* (1983) to achieve maximum absorbance.

Media optimization in shake flask studies resulted in the formulation of the Optimized Medium which consisted of 0.3% (w/v) yeast extract, 3% (w/v) sodium chloride and 5% (w/v) glucose added with nutrient broth. Bacillus licheniformis JF-2 grown in the Optimized Medium at an initial pH of 7.0, temperature of 40°C and shaken at 250 rpm achieved a maximum biomass yield averaging 1.61 g/L and crude lipopeptide yield of 1.82 g/L whereas the maximum absorbance read at 480 nm achieved a maximum of 1.58 at the 8th hour of fermentation.

Studies conducted in a 1.5L capacity Biolab fermenter at an optimum agitation speed of 400 rpm and at an air flow rate of 1000 cm<sup>3</sup>/min resulted in a yield of 3.15 g/L for biomass and 2.96 g/L of crude lipopeptide, respectively whereas the maximum absorbance achieved was 2.90 at the end of the 24th hour fermentation period. Biomass in terms of dry cell weight obtained by Lin et al. (1994b) were measured between 1.2 to 1.3 g/L under 30% saturation of dissolved oxygen when B. licheniformis JF-2 was grown in a Mineral Salts Medium supplemented with 1% glucose after approximately 12 hours of fermentation. There was a marked increase in the biomass when B. licheniformis JF-2 was grown on the Optimized Medium as shown by our laboratory studies.

Due to the intended application of *B. licheniformis* JF-2 in treating wastewater which requires the seed cultures to be produced in large volumes, the use of the Optimized Medium would be costly and impractical whereby making it unprofitable on a long term basis. Therefore, locally available wastewater, namely, dairy wastewater from the processing of sweetened condensed milk, rubber effluent and palm oil mill effluent were used in shake flask studies to cultivate *B. licheniformis* JF-2. Undiluted dairy wastewater with an initial pH of 7.0 was found to be suitable for the growth of *B. licheniformis* JF-2.

The maximum biomass obtained averaged 0.71 g/L at the 8th hour of fermentation. The surface tension of the inoculated dairy wastewater was reduced from an initial value of 48.4 mN/m to 38.8 mN/m, a reduction of 19.8 % after 8 hours of fermentation, indicating the presence of the lipopeptide biosurfactant in the dairy wastewater.

Bacillus licheniformis JF-2 was found to successfully treat edible palm oil processing wastewater during a 15 day treatment period. The Chemical Oxygen Demand (COD) of the palm oil processing wastewater was reduced by 65% in an activated sludge process and the surface tension of the treated wastewater was reduced by 49%. Bacillus licheniformis JF-2 has found a new application in the treatment of palm oil processing wastewater. The reduction of the surface tension by 49% indicates the presence of the lipopeptide biosurfactant in the treated wastewater.

# LIST OF TABLES

Table 1:	Biosurfactant functions most likely to be needed and potential industrial users (Kosaric et al., 1987)	3
Table 2:	Surface tension of the cultivation media containing various concentrations of NaCl after 8 hours of fermentation with <i>B. licheniformis</i> JF-2 in shake flask culture	63
Table 3:	Surface tension of the Nutrient broth containing various concentration of yeast extract after 8 hours fermentation with <i>B. licheniformis</i> JF-2 at 40°C and shaken at 250 rpm	69
Table 4:	$\boldsymbol{R}_{\mathrm{f}}$ values of the migrated spots and stained with anisaldehyde reagent in TLC	75
Table 5:	Surface tension measurements of the collapsed foam and the crude lipopeptide yield from the various media from the B. Braun Biolab fermentation studies	89
Table 6:	The characteristics of selected effluents used for the cultivation of <i>B. licheniformis</i> JF-2 in the shake flask studies	90
Table 7:	The reducing sugar profile of POME during the growth of <i>B. licheniformis</i> JF-2 for 8 hours in shake flask cultures	92
Table 8:	Percent reduction of the reducing sugar in Rubber effluent during the growth of <i>B. licheniformis</i> JF-2 in shake flasks after 8 hours of fermentation at 40°C and shaken at 250 rpm	97
Table 9:	Reducing sugar concentrations in various dilutions of dairy wastewater during the growth of B. licheniformis JF-2 in shake flasks at 40°C and shaken at 250 rpm	98
Table 10	D: Colony Forming Units (CFU) of B. licheniformis JF-2 grown on dairy wastewater supplemented with molasses after 8 hours of fermentation in shake flask culture. 1mL of the cultivation medium is serially diluted in sterile distilled water and plated on Nutrient agar plates and left to incubate for 24 hours at 30°C	103

Table 11:	Surface tension of cultivation medium consisting of molasses after 8 hours of fermentation in shake flasks at 40°C and shaken at 250 rpm	103
Table 12:	pH of the dairy wastewater with molasses, recorded during the growth of <i>B. licheniformis</i> JF-2 after 8 hours of fermentation at 40°C, 250 rpm and at an initial pH of 7.0	105
Table 13:	pH of the cultivation medium consisting of dairy wastewater and fish meal after 8 hours of fermentation with <i>B. licheniformis</i> JF-2 at 40°C and shaken at 250 rpm	106
Table 14:	Colony Forming Units (per ml) of <i>B. licheniformis</i> JF-2 obtained from the cultivation medium consisting of dairy wastewater supplemented with FM after 8 hours of incubation at 40°C and shaken at 250 rpm	106
Table 15:	Surface tension of the cultivation medium supplemented with FM, after 8 hours of fermentation in shake flask culture at 40°C and shaken at 250 rpm	. 107
Table 16:	The absorbance of Medium E and Nutrient broth supporting the growth of <i>B. licheniformis</i> 1F-2, with an initial pH of 7.0, at 40°C and shaken at 250 rpm in an orbital type incubator shaker	115
Table 17:	The biomass and crude biosurfactant production after 8 hours of growth in various modified Nutrient broth media at 40°C, initial pH of 7.0 and shaken at 250 rpm in shake flasks	116
Table 18:	The scale-up to a 1.5L capacity Biolab fermenter using various cultivation medium at $40^{\circ}\text{C}$ , an initial pH of 7.0 and with an impeller speed of $400\text{rpm}$	118

# LIST OF FIGURES

Fig. 1:	Surfactants are characterized by an amphipathic structure. Hydrophobic and hydrophilic properties	
	depend on the charge of the polar group (anionic, cationic, neutral or amphoteric). They tend to associate at interfaces or in micelles, favouring a minimal free energy charge of the system. The minimal surface-tension value attained due to the	
	activity of the surfactant, and the critical micelle concentration (cmc) required, give a measure of the efficiency of the surface-active compound.	10
Fig. 2:	Lactonic sophorose lipid	12
Fig. 3:	Acidic sophorose lipid	13
Fig. 4:	Structure of surfactin from Bacillus subtilis	14
Fig. 5:	The structure of ornithine containing lipid from Thiobacillus thiooxidans	16
Fig. 6:	Structure of the surface-active lipopeptide of Bacillus licheniformis JF-2	19
Fig. 7:	Biomass and Optical density profiles of the growth of B. licheniformis JF-2 in Nutrient Broth, incubated at 35°C, 40°C and 45°C, and shaken at 250 rpm.	57
Fig. 8:	Final pH and Surface tension (ST) profiles of B. licheniformis JF-2 in a time course study at 35°C, 40°C and 45°C, and shaken at 250 rpm.	59
Fig. 9:	pH optimization with respect to biomass, optical density and surface tension measurements of the cultures of <i>B. licheniformis</i> JF-2 grown in Nutrient broth in shake flasks at 40°C and 250 rpm after 8 hours of growth.	60
Fig. 10:	The Biomass, Optical density and Crude Lipopeptide Yield (CLY) and the Emulsification Index profiles in various concentrations of NaCl after 8 hours of fermentation with <i>B. licheniformis</i> JF-2 in Nutrient broth at 40°C and shaken at 250 rpm.	62
Fig. 11:	Optical density and Biomass profiles of B. licheniformis JF-2 after 8 hours of growth in Nutrient broth containing various concentrations of NaCl and glucose at 40°C and shaken at 250 rpm (BM - Biomass, OD - Optical density).	66

Fig. 12:	Surface tension (ST) measurements and Crude lipopeptide yield (CLY) by <i>B. licheniformis</i> JF-2 in Nutrient broth containing NaCl between 1-5% (w/v) and glucose at 5% and 10% in shake flask at 40°C and shaken at 250 rpm.	67
Fig. 13:	The effect of yeast extract on cell density (OD), Biomass and Crude lipopeptide yield (CL) in Nutrient broth at pH 7.0, 40°C and shaken at 250 rpm in shake flasks.	68
Fig. 14:	Fermentation kinetic profiles of <i>B. licheniformis</i> JF-2 in the Optimized Medium in shake flasks at 40°C and shaken at 250 rpm (CL - Crude lipopeptide yield).	71
Fig. 15:	The Optical density, Surface tension and final pH profile of Medium E (ME) and the Optimized Medium (OM) during the growth of <i>B. licheniformis</i> JF-2 in shake flask culture at $40^{\circ}$ C and $250$ -rpm (The data shown for the OM is the same as in Fig. 14).	73
Fig. 16:	Critical Micelle Concentrations (CMC) of the crude biosurfactant from <i>B. licheniformis</i> JF-2 after 8 hours of growth in the Optimized Medium (OM) at 40°C and shaken at 250 rpm.	79
Fig. 17:	Biomass, Optical density, pH and Surface tension monitored during the growth of <i>B. licheniformis</i> JF-2 using the Optimized Medium (OM) in a 1.5L Biolab fermenter at 40°C, initial pH of 7.0 and agitation speed of 400 rpm. There is no significant drop in the surface tension of the cultivation medium as the lipopeptide biosurfactant is effectively removed from the cultivation medium by the foam fractionation method.	80
Fig. 18:	Optical density profile of the growth of <i>B. licheniformis</i> JF-2 in the MSM-I and MSM-II compared to the Optimized Medium (OM) conducted in a 1.5L capacity Biolab fermenter at 40°C and at an agitation speed of 400 rpm.	85
Fig. 19:	pH profile of two mineral salts based medium compared to the Optimized Medium (OM) during the growth of <i>B. licheniformis</i> JF-2 in a 1.5L capacity Biolab fermenter at 40°C and at an agitation speed of 400 rpm.	86

Fig. 20:	Surface tension profile of two mineral salts based medium compared to the Optimized Medium (OM) during the growth of <i>B. licheniformis</i> JF-2 in a 1.5L capacity Biolab fermenter at 40 °C and at an agitation speed of 400 rpm. In both the Optimized Medium (OM) and MSM-II, there was no drop in the surface tension measured due to the effecient removal of the lipopeptide biosurfactant by the foam fractionation method whereas for the MSM-I,	
	less foam was produced and the foam fractionation method was ineffective.	88
Fig. 21:	The various paramenters measured during the growth of <i>B. licheniformis</i> JF-2 in palm oil mill effluent at 40C and shaken at 250 rpm in an orbital type incubator shaker.	93
Fig. 22:	Surface tension and Biomass profiles of <i>B. licheniformis</i> JF-2 during 8 hours of growth in rubber effluent diluted with distilled water in shake flasks at $40^{9}$ C in an orbital type incubator shaker at 250 rpm.	95
Fig. 23:	pH and Reducing sugar (RS) profiles of the diluted rubber effluent during 8 hours of growth of <i>B.</i> licheniformis JF-2 in shake flasks at 40°C and shaken at 250 rpm.	96
Fig. 24:	Biomass of <i>B. licheniformis</i> JF-2 during the growth in various dilutions of dairy wastewater in shake flasks at 40°C, initial pH of 7.0 and shaken at 250 rpm (diluted with distilled water to dilutions of 1:10, 1:1 and 1:0).	99
Fig. 25:	pH profiles of the various dilutions of dairy wastewater supporting the growth of $B$ . Licheniformis JF-2 during 8 hours of fermentation at $40^{\circ}$ C, initial pH of 7.0 and shaken at 250 rpm.	100
Fig. 26:	Surface tension profiles of the various dilutions of dairy wastewater supporting the growth of <i>B. licheniformis</i> JF-2 during 8 hours of growth in shake flasks at 40°C, initial pH of 7.0 and shaken at 250 rpm.	102
	•	

Fig. 27: COD profiles of the edible palm oil processing wastewater treated with B. licheniformis IF-2 and JAD 969P bioaugmentation culture complex at room temperature and with an air flow rate of 1000 cm³/min (C1 - control for the JF-2 treated wastewater; C2 - control for JAD 969P bioaugmentation culture complex). [C1 and JF-2 contains 100ml of waste palm oil; C2 and JAD 969P 10ml of waste palm oil].

112

Fig. 28: Surface tension profiles of the edible palm oil processing wastewater treated with B. licheniformis JF-2 during the 15 day treatment period with an initial pH of 7.0 and an air flow rate of 1000 cm<sup>3</sup>/min [CI - control for the JF-2 treated wastewater].

113

# LIST OF PLATES

Plate 1:	Photomicrograph of <i>Bacillus licheniformis</i> JF-2 (magnified 1000x)	18
Plate 2:	Bacillus licheniformis JF-2 grown on Nutrient agar (96 hours)	34
Plate 3:	Crude lipopeptide produced by <i>B. licheniformis</i> JF-2 obtained from Nutrient broth during 24 hours of fermentation (Freeze dried)	46
Plate 4:	Bacillus licheniformis JF-2 grown in a 1.5L Biolab fermenter using Nutrient broth as cultivation medium (8 hours of fermentation)	47
Plate 5:	The Emulsification Index (E <sub>24</sub> ) measured at six concentrations of NaCl in Nutrient broth after 8 hours of growth with <i>B. licheniformis</i> JF-2 at 40°C and shaken at 250 rpm. The Emulsification Index was measured after 24 hours of settling at room temperature.	64
Plate 6:	Plates stained with anisaldehyde reagent to visualise the spots from extracts using Thin Layer Chromatography (TLC).	76
Plate 7:	The amount of cells present during different sampling periods (harvest time) from 0 hour to 24 hours (with half an hour of settling). These samples were obtained during the growth of <i>B. licheniformis</i> 1F-2 in the Optimized medium, using a 1.5L capacity Biolab ferrmenter at 40°C, with an agitation speed of 400 rpm.	81
Plate 8:	Foam collected by the foam fractionation method during the cultivation of <i>B.licheniformis</i> JF-2 using the Optimized medium (OM) in a 1.5 litre Biolab fermenter.	83
Plate 9:	Colony Forming Units of <i>B. licheniformis</i> JF-2 per ml of dairy wastewater supplemented fish meal (FM) grown on Nutrient agar plate after 24 hours of incubation at 30°C. A slight containation is observed at the bottom left hand corner of the	
	photograph.	104

Plate 10: Emulsification of crude oil (Vietnam crude) by the culture of *B. licheniformis* JF-2 grown in OM. Set A (duplicate) consisted of 30 ml of sterile OM (control) and 30 ml of crude oil while set B contained 30 ml of a 8 hour old culture of *B. licheniformis* JF-2 with 30 ml of crude oil. The contents were shaken for 1 hour in an orbital incubator shaker at 250 rpm at 40°C.

110

# LIST OF APPENDICES

Appendix I : Optimized Medium	139
Appendix II : Mineral Salts Medium (MSM I)	140
Appendix III : Mineral Salts Medium (MSM II)	141
Appendix IV : Medium E	142
Appendix V: Micororganisms present in JAD 969P bioaugmentation culture complex	143
Appendix VI : Standard Reducing Sugar Curve (DNS method)	144
Appendix VII : Standard curve to determine Total Sugar Content	145
Appendix VIII : Summary of selected experimental results	146

#### LIST OF ABBREVIATIONS

MEOR - Microbial Enhanced Oil Recovery

POME - Palm Oil Mill Effluent

RE - Rubber effluent

TLC - Thin layer chromatography

DW - Dairy wastewater

FM - Fish meal

CFU - Colony forming units

EOR - Enhanced oil recovery

CMC - Critical micelle concentration

COD - Chemical oxygen demand

ST - Surface tension

CLY - Crude lipopeptide yield

OD - Optical density

BM - Biomass

RS - Reducing sugar