

***ERBIUM-DOPED FIBER AMPLIFIER:
EFFECTS OF OPTICAL FEEDBACK***

by

TEYO TUAN CHIN

DEPARTMENT OF PHYSICS
FACULTY OF SCIENCE
UNIVERSITY OF MALAYA

DISSERTATION PRESENTED FOR THE
DEGREE OF DOCTOR OF PHILOSOPHY
UNIVERSITY OF MALAYA

2003

Perpustakaan Universiti Malaya



A511029399

Abstract

In this thesis, a study of the erbium-doped fiber amplifier (EDFA) with optical feedback is described. The characterization of the amplifier performance concerns the effects of the existence of wavelength selective element in the cavity and different feedback schemes, namely counter-feedback, co-feedback and regenerative-feedback. Comparison with the conventional EDFA system without feedback is presented. Existence of oscillating laser in the cavity either improves or degrades the amplifier performance, depending on the feedback scheme. Gain-clamping effect is exhibited in the system with optical feedback. Laser-induced saturation is observed in the counter-feedback scheme, resulting in deterioration of the noise figure. In contrast, the oscillating laser in co-feedback and regenerative-feedback scheme suppresses the amplified spontaneous emission (ASE) induced self-saturation and significantly improves the noise performance. The thesis ends with the conclusions of the results presented. Suggestions for future work are also given.

Abstract

In this thesis, a study of the erbium-doped fiber amplifier (EDFA) with optical feedback is described. The characterization of the amplifier performance concerns the effects of the existence of wavelength selective element in the cavity and different feedback schemes, namely counter-feedback, co-feedback and regenerative-feedback. Comparison with the conventional EDFA system without feedback is presented. Existence of oscillating laser in the cavity either improves or degrades the amplifier performance, depending on the feedback scheme. Gain-clamping effect is exhibited in the system with optical feedback. Laser-induced saturation is observed in the counter-feedback scheme, resulting in deterioration of the noise figure. In contrast, the oscillating laser in co-feedback and regenerative-feedback scheme suppresses the amplified spontaneous emission (ASE) induced self-saturation and significantly improves the noise performance. The thesis ends with the conclusions of the results presented. Suggestions for future work are also given.

Abstrak

Dalam tesis ini, penyelidikan terhadap sistem pembesar gentian berdop erbium dengan suap-balik diuraikan. Pencirian prestasi pembesar gentian adalah mengenai kesan wujudnya elemen pemilihan panjang gelombang di dalam rongga dan skim-skim suap-balik yang berlainan. Perbandingan dengan konfigurasi konvensional tanpa suap-balik telah dibuat. Bergantung kepada jenis skim suap-balik, kewujudan laser di dalam rongga samada memperbaiki atau memburukkan prestasi sistem. Kesan gandaan tercengkam dapat diperhatikan di dalam system dengan suap-balik. Penepuan akibat daripada ayunan laser dalam arah bertentangan dengan suap-balik telah memburukkan prestasi kebisingan. Sebaliknya, ayunan laser di dalam suap-balik bersama dan penjananan semua telah menekan pancaran spontan terganda dan memperbaiki prestasi kebisingan. Tesis ini diakhiri dengan kesimpulan dari keputusan-keputusan yang dilaporkan. Cadangan-cadangan untuk kerja masa depan juga diberikan.

Acknowledgement

I would like to gratefully acknowledge the contribution made by many members of Photonics Laboratory, such as Leong Mun Kiat, Nor Shahida Mohd. Shah, Prabakaran Poopalan and other members.

In particular, I would like to thank my supervisor, Professor Harith Ahmad for providing useful advice, encouragement and motivation.

Finally, I wish to thank National Science Fellowship for financial support. This work was funded by National Photonics Top-Down Project.

CONTENTS

Abstract	I
Abstrak	II
Acknowledgement	III
Chapter I Introduction	1
1.1 Brief History of Erbium-Doped Fiber Amplifiers	1
1.2 Principles of Amplification Mechanism	3
1.3 Recent Development in Erbium-doped Fiber Amplifiers With Optical Feedback	4
1.4 Outline of this Thesis	6
References	10
Chapter II Basic Principles of Erbium-Doped Fiber Amplifiers	15
2.1 Introduction	15
2.2 Doped Glass Structure and Properties	15
2.3 Energy Levels of Er^{3+} Ions	18
2.3.1 Stark Effects	18
2.3.2 Rate Equations	20
2.3.3 Nonradiative Relaxation	22
2.3.4 Pump Bands and Excited/Ground State Absorption	24
2.4 Broadening	26
2.5 Spontaneous and Stimulated Emission	27
2.6 Absorption and Small-signal Gain Coefficient	30
2.7 Principles of Gain-clamping in Erbium-Doped Fiber Amplifiers	32
2.8 Key Issues For Optical Amplifiers	35
2.8.1 Signal Gain	35
2.8.2 Noise	37
2.9 Simulation Using <i>OptiAmplifier</i>	38
2.9.1 Introduction to <i>OptiAmplifier</i>	38
2.9.2 Simulation Setup	41
2.9.3 Comparison of Simulation Results with Experimental Results	43
References	48

Chapter III	Components Characterization and Measurement Methods	50
3.1	Introduction	50
3.2	Basic Experimental Setup and Components Characterization	51
3.3	Study of Back Reflection	57
3.4	Selection of Pumping Scheme	62
3.5	Measurement Methods	67
3.5.1	Principle of Interpolation Method	67
3.5.2	Principles of Time-Domain-Extinction (TDE) Method	68
3.5.3	Results Comparison between Different Measurement Methods	71
3.6	Study of Boosted Signal Source	73
3.7	Conclusions	77
	References	78
Chapter IV	Experimental Results and Discussion I: Erbium-Doped Fiber Amplifier with Optical Counter-Feedback	80
4.1	Introduction	80
4.2	Experimental Setup	81
4.3	Amplifier Performance without Wavelength Selective Element	83
4.3.1	Output Spectrums	83
4.3.2	Effects of Pump Power Variation	85
4.3.3	Effects of Input Signal Power Variation	87
4.3.4	Effects of Signal Wavelength Variation	90
4.4	Performance Comparison Among The Systems	92
4.4.1	Output Spectrums	92
4.4.2	Effects of Pump Power Variation	94
4.4.3	Effects of Input Signal Power Variation	99
4.4.4	Effects of Signal Wavelength Variation	103
4.5	Variation of Lasing Wavelength	106
4.5.1	Effects of Lasing Wavelength Variation	106
4.5.2	Performance Comparison for Different Lasing Wavelengths	111

4.6	Conclusions	118
	References	119
Chapter V	Experimental Results and Discussion II:	
	Erbium-Doped Fiber Amplifier with Optical Co-Feedback	122
5.1	Introduction	122
5.2	Experimental Setup	123
5.3	Amplifier Performance – Comparison Among The Systems	124
5.3.1	Output Spectrums	124
5.3.2	Effects of Pump Power Variation	125
5.3.3	Effects of Input Signal Power Variation	130
5.3.4	Effects of Signal Wavelength Variation	137
5.4	Variation of Lasing Wavelength	140
5.5	Study of Cavity Loss	148
5.6	Effects of Input Signal on Oscillating signal	160
5.7	Conclusions	165
	References	166
Chapter VI	Experimental Results and Discussion III:	
	Erbium-Doped Fiber Amplifier with Optical Regenerative-Feedback	169
6.1	Introduction	169
6.2	Experimental Setup	170
6.3	Unidirectional-Feedback with Wavelength Selective Element	172
6.3.1	Comparison between Different Measurement Methods	172
6.3.2	Comparison with System Without Feedback	175
6.4	Unidirectional-Feedback without Wavelength Selective Element	177
6.4.1	Operation Below Threshold	177
6.4.1.1	Amplifier Performance	177
6.4.1.2	Saturation Characteristics	185
6.4.1.3	Amplification Bandwidth	188
6.4.1.4	Comparison with the System Without Feedback	190
6.4.2	Operation Above Threshold	199
6.4.2.1	Amplifier Performance	199

6.4.2.2 Comparison with the System Without Feedback	210
6.4.2.3 Comparison with Co-feedback Scheme	220
6.5 Injection Locking	232
6.6 Regenerative Amplifier Subject To External Injection	238
6.7 Bidirectional-Feedback Regenerative Amplifier	253
6.7.1 Output Spectrums	253
6.7.2 Operation Below Threshold	254
6.7.3 Operation Above Threshold	259
6.8 Conclusions	266
References	268
Chapter VII Conclusions	271
7.1 Introduction	271
7.2 Counter-Feedback	271
7.3 Co-Feedback	272
7.4 Regenerative-Feedback	273
7.5 Summary of the Work	274
7.6 Suggestions for Future Work	276
References	277
 APPENDIXES	
A Giles Model	279
B Theory of Regenerative Amplifier Model	281
C Injection Locking Theory Based on Adler's Model	284
D Publication List	286