

## **REFERENCES**

---

## REFERENCES

---

- Amitabha Ghosh and Ashok Kumar Mallik. (1985). *Manufacturing Science*. New Delhi: Affiliated East-West Press Private Limited.
- Boothroyd, G. and Winston, A.K. (1989). Non-conventional machining processes. In: *Fundamentals of Machining and Machine Tools*. New York: Marcel Dekker. Inc. (p. 491)
- Brink, D. *EDM: Principles of Operation*, EDM Technology Transfer. <http://www.edmtt.com>.
- Chen, S.L., Yan, B.H., and Huang, F.Y. (1999). Influence of kerosene and distilled water as dielectrics on the electric discharge machining characteristics of Ti-6Al-4V. *J. Mater. Process. Technol.* **87**. 107-111.
- Chen, Y. and Mahdavian, S.M. (1999). Parametric study into erosion wear in a computer numerical controlled electro-discharge machining process. *Wear*. **236**. 350-354.
- Chow, H.-M., Yan, B.-H., Huang, F.-Y. and Hung, J.-C. (2000). Study of added powder in kerosene for the micro-slit machining of titanium alloy using electro-discharge machining. *J. Mater. Process. Technol.* **101**. 95-103.
- Erden, A., and Bilgin, A. (1980). Role of impurities in electrical discharge machining, in: *Proceedings of the XXI IMTDR Conference*, Swansea. 345.
- George, P.M., Raghunath, B.K., Manocha, L.M. and Ashish M. Warrier. (2004a). EDM machining of carbon-carbon composites – a Taguchi approach. *J. Mater. Process. Technol.* **145**. 66-71.
- George, P.M., Raghunath, B.K., Manocha, L.M. and Ashish M. Warrier. (2004b). Modelling of machinability parameters of carbon-carbon composites – a response surface approach. *J. Mater. Process. Technol.* **153-154**. 920-924.
- Guu, Y.H. (2004). AFM surface imaging of AISI D2 tool steel machined by the EDM process. *Applied Surface Science*. **xxx**. xxx-xxxx.

Guu, Y.H., Hocheng, H., Chou, C.Y. and Deng, C.S. (2003). Effect of electrical discharge machining on surface characteristics and machining damage of AISI D2 tool steel. *Mater. Science and Engineering.* **A358**. 37-43.

Ho, K.H. and Newman, S.T. (2003). State of the art electrical discharge machining (EDM). *Int. J. Mach. Tools Manuf.* **43**. 1287-1300. *Int. J. Mach. Tools Manuf.* **28(4)**. 359-372.

<http://www.mse.iastate.edu/microscopy/whatsem.html>

Instruction Manual, Volume 1.1, *Machining Condition Parameter Setting and Jigs/Tools and Flushing*, Mark-20 Series, Sodick Co., Ltd.

Jeswani, M.L. (1981). Effects of the addition of graphite powder to kerosene used as the dielectric fluid in electrical discharge machining. *Wear.* **70**. 133-139.

Kausalya Gopal. (2002). Study of main and interaction effects of some input variables on some output parameters in EDM process. Undergraduate Thesis, Department of Engineering Design and Manufacture, University of Malaya.

Kunieda, M. and Kobayashi, K. (2004). Clarifying mechanism of determining tool electrode wear ratio in EDM using spectroscopic measurement of vapor density. *J. Mater. Process. Technol.* **149**. 284-288.

Kunieda, M. and Yoshida, M. (1997). Electrical discharge machining in gas. *Ann. CIPR.* **46(1)**. 143-146.

Kunieda, M., Furuya, M. and Taniguchi, N. (1991). Improvement of EDM efficiency by supplying oxygen gas into gap. *Ann. CIPR.* **40(1)**. 215-218.

Lee, H.T. and Tai, T.Y. (2003). Relationship between EDM parameters and surface crack formation. *J. Mater. Process. Technol.* **142**. 676-683.

Lee, H-T., Hsu, F-C. and Tai, T-Y. (2004). Study of surface integrity using the small area EDM process with a copper tungsten electrode. *Mater. Science and Engineering.* **A364**. 346-356.

Lee, L.C., Lim, L.C., Narayanan, V., and Venkatesh, V.C. (1988). Quantification of surface damage of tool steels after EDM. *Int. J. Mach. Tools Manuf.* **28(4)**. 359-372.

Lee, L.C., Lim, L.C., Wong, Y.S., and Lu, H.H. (1990). Towards a better understanding of the surface features of electro-discharge machined tool steels. *Int. J. Mach. Tools Manuf.* **24**. 513-523.

Lee, S.H. and Li, X.P. (2001). Study of the effect of machining parameters on the machining characteristics in electrical discharge machining of tungsten carbide. *J. Mater. Process. Technol.* **115**. 344-358.

Lee, S.H. and Li, X.P. (2003). Study of the surface integrity of the machined workpiece in the EDM of tungsten carbide. *J. Mater. Process. Technol.* **139**. 315-321.

Li Li, Wong, Y.S., Fuh, J.Y.H. and Lu, L. (2001). EDM performance of TiC/copper-based sintered electrodes. *Materials and Design*. **22**. 669-678.

Lim, L.C., Lee, L.C., Wong, Y.S., and Lu, H.H. (1991). Solidification microstructure of electrodiscahrge machined surfaces of tool steels. *Mater. Sci. Technol.* **7**. 239-248.

Lin, J.L. and Lin, C.L. (2002). The use of the orthogonal array with grey relational analysis to optimize the electrical discharge machining process with multiple performance characteristics. *Int. J. Mach. Tools Manuf.* **42**. 237-244.

Lin, J.L., Wang, K.S., Yan, B.H. and Tarn, Y.S. (2000). Optimization of the electrical discharge machining process based on the Taguchi method with fuzzy logics. *Int. J. Mach. Tools Manuf.* **102**. 48-55.

Liu, C.-C. (2003). Microstructure and tool electrode erosion in EDMed of TiN/Si<sub>3</sub>N<sub>4</sub> composites. *Mater. Science and Engineering*. **A363**. 221-227.

Lonardo, P.M. and Bruzzone, A.A. (1999). Effect of flushing and electrode material on die sinking EDM. *Ann. CIRP*. **48(1)**. 123-126.

Mamalis, A.G., Voaniakos, G.C., and Vaxevanidis, N.M. (1987). Macroscopic and microscopic phenomena of electro-discharge machined steel surfaces: an experimental investigation. *J. Mech. Working Technol.* **15**. 335-356.

Mathews, P.S. and Philip, P.K. (1997). Effect of manufacturing variables on EDM process stability while using pm electrodes. *J. Ins. Eng. (India)-PR*. **78**. 39-43.

McGeough, J.A. (1988). Electro-discharge machining. In: *Advanced Methods of Machining*. London: Chapman & Hall. (p. 130)

Narender Singh, P., Raghukandan and Pai, B.C. (2004a). Optimization by Grey relational analysis of EDM parameters on machining Al-10%SiCp composites. *J. Mater. Process. Technol.* **155-156**. 1658-1661.

Narender Singh, P., Raghukandan, K., Rathinasabapathi, M. and Pai, B.C. (2004b). Electric discharge machining of Al-10%SiCp as-cast metal matrix composites. *J. Mater. Process. Technol.* **155-156**. 1653-1657.

Narumiya, H., Mohri, N., Saito, N., Ootake, H., Tsunekawa, Y., Takawashi, T. and Kobayashi, K. (1989). EDM by powder suspended working fluid. *Proc. Int. Symp. on Electro-Machining (ISEM-9)*, 5-8.

Pecas, P. and Henriques, E. (2003). Influence of silicon powder-mixed dielectric on conventional electrical discharge machining. *Int. J. Mach. Tools Manuf.* **43**. 1465-1471.

Puertas, I. and Luis, C.J. (2003). A study on the machining parameters optimization of electrical discharge machining. *J. Mater. Process. Technol.* **143-144**. 512-526.

Puertas, I. and Luis, C.J. (2004). A study on the electrical discharge machining of conductive ceramics. *J. Mater. Process. Technol.* **153-154**. 1033-1038.

Puertas, I., Luis, C.J. and Álvarez, L. (2004). Analysis of the influence of EDM parameters on surface quality, MRR and EW of WC-Co. *J. Mater. Process. Technol.* **153-154**. 1026-1032.

Ramasawmy, H. and Blunt, L. (2004). Effect of EDM process parameters on 3D surface topography. *J. Mater. Process. Technol.* **148**. 155-164.

Rebelo, J.C., Dias, A.M., Kremer, D., and Lebrun, J.L. (1998). Influence of EDM pulse energy on the surface intergrity of martensitic steels. *J. Mater. Process. Technol.* **84**. 90-96.

Shamila Aravindan. (2003). Determination of optimum process variables in EDM Die Sinking. Undergraduate Thesis, Department of Engineering Design and Manufacture, University of Malaya.

Shanker Singh, Maheshwari, S. and Pandey, P.C. (2004). Some investigations into the electric discharge machining of hardened tool steel using different electrode materials. *J. Mater. Process. Technol.* **149**. 272-277.

Shobert, E.I. (1993). What happen in EDM. In: Jameson, E.C. (ed), *Electrical Discharges Machining: Tooling, Methods and Applications*. Dearborn, MI: Society of Manufacturing Engineers. (p. 3-4)

Singh, U.P., Miller, P.P. and Urquhart, W. (1985). The influence of electrical-discharge machining parameters on machining characteristics, in: *Proceedings of the 25<sup>th</sup> International Machine Tool Design and Research Conference*. pp.337-345.

Stovicek, D.R. (1993). The State of the art EDM Science: Tooling and Production. **59 (2)**. Ohio, USA: Nelson Publishing Inc. (p. 42)

Sung, H.P. (1996). *Robust Design and Analysis for Quality Engineering*, 1<sup>st</sup> ed. London: Chapman & Hall.

Takawashi, T., Kobayashi, K., Ito, H., Sakakibara, T., and Saito, N. (1983). Study of the mirror surface finishing by planetary EDM. *Proc. Int. Symp. on Electro-Machining (ISEM-7)*. 137-146.

Tsai, H.C., Yan, B.H. and Huang, F.Y. (2003). EDM performance of Cr/Cu-based composite electrodes. *Int. J. Mach. Tools Manuf.* **43 (3)**. 245-252.

Tsai, K.M. and Wang, P.J. (2001). Semi-empirical model of surface finish on electrical discharge machining. *Int. J. Mach. Tools Manuf.* **41**. 1455-1477.

Tzeng, Y.-F. and Chen, F-C. (2003). A simple approach for robust design of high-speed electrical discharge machining technology. *Int. J. Mach. Tools Manuf.* **43**. 217-227.

Williams, R.A. (1970). *Handbook of the Atomic Elements*. Philosophical Library.

Wong, Y.S., Lim, L.C., Iqbal Rahuman and Tee, W.M. (1998). Near-mirror-finish phenomenon in EDM using powder-mixed dielectric. *J. Mater. Process. Technol.* **79**. 30-40.

[www.nedians.8m.com/edm.htm](http://www.nedians.8m.com/edm.htm)

[www.statsoft.com/textbooks/stexdes.html](http://www.statsoft.com/textbooks/stexdes.html)

Zaw, H.M., Fuh, J.Y.H., Nee, A.Y.C. and Lu, L. (1999). Formation of a new EDM electrode material using sintering techniques. *J. Mater. Process. Technol.* **89-90**. 182-186.

Zhao, W.S., Meng, Q.G. and Wang, Z.L. (2002). The application of research on powder mixed EDM in rough machining. *J. Mater. Process. Technol.* **129**. 30-33.