

TABLE OF CONTENTS

<u>CONTENTS</u>	<u>PAGE</u>	
TITLE	i	
ABSTRACT	ii	
ABSTRAK	iii	
ACKNOWLEDGEMENTS	iv	
TABLE OF CONTENTS	v	
LIST OF FIGURES	viii	
LIST OF TABLES	xi	
LIST OF SYMBOLS AND ABBREVIATIONS	xii	
CHAPTER 1	INTRODUCTION	1
	1.1 Project Background	1
	1.2 Project Objective	2
	1.3 Project Scope	2
	1.4 Outline of Dissertation	3
CHAPTER 2	LITERATURE REVIEW	4
	2.1 Introduction	4
	2.2 Lightning Phenomenon	4
	2.2.1 Mechanism of Lightning	4
	2.2.2 Breakdown Process	5
	2.2.3 Lightning Problems in Power System	5
	2.3 Back Flashover	7
	2.4 Travelling Wave	8

2.5	Transmission Line System	8
2.6	Transmission Tower	10
2.7	Cross-arms	12
2.8	Line-Insulator Flashover	13
2.8.1	Leader Progression Model	13
2.9	Lightning Source	14
2.10	Tower Surge-Impedance	16
2.11	Tower-Footing Resistance	17
CHAPTER 3	METHODOLOGY	18
3.1	Introduction	18
3.2	Alternative Transient Program (ATP)	18
3.2.1	Introduction	18
3.2.2	Operating Principle of ATP	19
3.2.3	ATPDraw	20
3.2.4	Plotting on ATP	22
3.2.5	ATP-EMTP Domain Solution Method	26
3.2.5.1	Frequency-Domain Solution Method	27
3.2.5.2	Time-Domain Solution Method	27
3.2.6	Typical ATP-EMTP Applications	30
3.3	Flow Chart of Project Methodology	30
CHAPTER 4	MODELLING OF 132kV OVERHEAD TRANSMISSION LINES	34
4.1	Introduction	34
4.2	Transmission Line and Tower Model	34

4.3	Cross-Arms Model	37
4.4	Insulator Strings Model	39
4.5	Lightning Source Model	39
4.6	Tower Surge-Impedance Model	42
4.7	Tower-Footing Resistance Model	42
4.8	AC Voltage Source Model	43
CHAPTER 5	RESULTS AND DISCUSSIONS	46
5.1	Introduction	46
5.2	Part 1: Lightning Surge Simulation on 132kV Overhead Transmission Lines	46
5.3	Part 2: Effect of Tower-Footing Resistance on Back-Flashover Voltage	53
5.4	Discussion	81
CHAPTER 6	CONCLUSIONS AND RECOMMENDATIONS	83
6.1	Conclusions	83
6.2	Recommendations	84
REFERENCES		85
APPENDIX A		91
APPENDIX B		93
APPENDIX C		112
APPENDIX D		115

LIST OF FIGURES

FIGURE	TITLE	PAGE
Figure 2.1	Charges induced on transmission line	5
Figure 2.2	Lightning leader strike and transmission line	7
Figure 2.3	Tower configuration of 132kV transmission line system	10
Figure 2.4	Multistory Tower Model	11
Figure 2.5	Simple Distributed Line Model	12
Figure 2.6	Lightning Strike, Heidler Model	15
Figure 2.7	Lightning- Strike Waveform	15
Figure 3.1	Main components of ATPDraw	22
Figure 3.2	Plotting program in ATP	22
Figure 3.3	Two main windows for PLOTXY	23
Figure 3.4	Fourier Chart	24
Figure 3.5	Execution in DOS Window	24
Figure 3.6	Harmonic Analysis via DISLIN	25
Figure 3.7	Methodology Flow Chart	31
Figure 4.1	Span of five towers	35
Figure 4.2	Model for Line/ Cable Data	35
Figure 4.3	Line/ Cable Data	36
Figure 4.4	Data for the cross-arms impedance	38
Figure 4.5	Model of the insulator strings	39
Figure 4.6	Heidler type of lightning source	40
Figure 4.7	Data for the Heidler Surge Model	40

Figure 4.8	Output waveform for Lightning stroke at 34.5kA peak; 1.0 μ s front duration, 30.2 μ s strike duration	41
Figure 4.9	Model of the Tower Surge Impedance	42
Figure 4.10	Model of the Tower-Footing Resistance	43
Figure 4.11	Model of the AC Voltage Source in ATP- EMTP software	44
Figure 4.12	Three Phase AC Voltage Source in ATP- EMTP software	44
Figure 5.1	Part of the ATP- EMTP model of the 132kV double circuit transmission lines	47
Figure 5.2(a)	Voltage across insulator strings, for 20kA lightning- strike current	49
Figure 5.2(b)	Close-up of 20kA waveform	49
Figure 5.3(a)	Voltage across insulator strings, for 34.5kA lightning- strike current	50
Figure 5.3(b)	Close-up of 34.5kA waveform	50
Figure 5.4(a)	Voltage across insulator strings, for 50kA lightning- strike current	51
Figure 5.4(b)	Close-up of 50kA waveform	51
Figure 5.5(a)	Voltage across insulator strings, for 100kA lightning- strike current	52
Figure 5.5(b)	Close-up of 100kA waveform	52
Figure 5.6	Voltage across insulator strings, for 20kA lightning-strike current (a) 5 Ω , (b) 10 Ω , (c) 15 Ω , (d) 20 Ω , (e) 25 Ω , (f) 30 Ω , (g) 35 Ω , (h) 40 Ω , (i) 45 Ω , (j) 50 Ω	59
Figure 5.7	Graph of maximum voltage across insulator strings versus tower-footing resistance, for 20kA lightning-strike current	59

Figure 5.8	Voltage across insulator strings, for 34.5kA lightning-strike current (a) 5Ω, (b) 10Ω, (c) 15Ω, (d) 20Ω, (e) 25Ω, (f) 30Ω, (g) 35Ω, (h) 40Ω, (i) 45Ω, (j) 50Ω	65
Figure 5.9	Graph of maximum voltage across insulator strings versus tower-footing resistance, for 34.5kA lightning-strike current	66
Figure 5.10	Voltage across insulator strings, for 50kA lightning-strike current (a) 5Ω, (b) 10Ω, (c) 15Ω, (d) 20Ω, (e) 25Ω, (f) 30Ω, (g) 35Ω, (h) 40Ω, (i) 45Ω, (j) 50Ω	71
Figure 5.11	Graph of maximum voltage across insulator strings versus tower-footing resistance, for 50kA lightning-strike current	72
Figure 5.12	Voltage across insulator strings, for 100kA lightning-strike current (a) 5Ω, (b) 10Ω, (c) 15Ω, (d) 20Ω, (e) 25Ω, (f) 30Ω, (g) 35Ω, (h) 40Ω, (i) 45Ω, (j) 50Ω	77
Figure 5.13	Graph of maximum voltage across insulator strings versus tower-footing resistance, for 100kA lightning-strike current	78
Figure 5.14	Circuit location and TLA placement for a double circuit line	81

LIST OF TABLES

NO.	TITLE	PAGE
Table 5.1	Lightning Amplitudes, Front Time, and Tail Time	48
Table 5.2	Back flashover across insulator strings at each phase, for 20kA lightning-strike current	60
Table 5.3	Back flashover across insulator strings at each phase, for 34.5kA lightning-strike current	66
Table 5.4	Back flashover across insulator strings at each phase, for 50kA lightning-strike current	72
Table 5.5	Back flashover across insulator strings at each phase, for 100kA lightning-strike current	78
Table 5.6	Strategy for Arrester Installation	80

LIST OF SYMBOLS AND ABBREVIATIONS

ATP – Alternative Transient Program

BIL – Basic Insulation Level

CFO – Critical Flashover Voltage

CIGRE – International Council on Large Electric Systems

EMTP – Electromagnetic Transient Program

IEEE – Institution Electrical Electronic Engineering

LA – Lightning Arrester

TACS – Transient Analysis of Control Systems

TNB – Tenaga Nasional Berhad