

REFERENCES

- AbdelKhaleq, R. A., & Ahmed, I. A. (2007). Rainwater harvesting in ancient civilizations in Jordan. *Water Science and Technology -Water Supply*, 7(1), 85-94.
- Abdullah, A. H., Meng, Q., Zhao, L., & Wang, F. (2009). Field study on indoor thermal environment in an atrium in tropical climates. *Building and Environment*, 44(2), 431-436.
- Aboulnaga, M. M. (2006). Towards green buildings: Glass as a building element--the use and misuse in the gulf region. *Renewable Energy*, 31(5), 631-653.
- Abu-Hijleh, B. A. K., & Mousa, H. A. (1997). Water film cooling over the glass cover of a solar still including evaporation effects. *Energy*, 22(1), 43-48.
- Agarwal, K. N., & Verma, V. V. (1977). Thermal characteristics of glazing and shading materials. *Building and Environment*, 12(1), 57-62.
- Akbari, H., Pomerantz, M., & Taha, H. (2001). Cool surfaces and shade trees to reduce energy use and improve air quality in urban areas. [doi: DOI: 10.1016/S0038-092X(00)00089-X]. *Solar Energy*, 70(3), 295-310.
- Al-Mofleh, A., Taib, S., Mujeebu, M. A., & Salah, W. (2009). Analysis of sectoral energy conservation in Malaysia. *Energy*, 34(6), 733-739.
- Alvarez, G., Flores, J. J., Aguilar, J. O., Gómez-Daza, O., Estrada, C. A., Nair, M. T. S., et al. (2005). Spectrally selective laminated glazing consisting of solar control and heat mirror coated glass: preparation, characterization and modelling of heat transfer. *Solar Energy*, 78(1), 113-124.
- Ambrosini, W., Forgione, N., & Oriolo, F. (2002). Statistical characteristics of a water film falling down a flat plate at different inclinations and temperatures. *International journal of multiphase flow* 28, 1521-1540.
- Amin, M. T., & Han, M. Y. (2009). Roof-harvested rainwater for potable purposes: Application of solar collector disinfection (SOCO-DIS). *Water Research*, 43 5225 - 5235.
- ASHRAE. (2008). *Advanced Energy Design Guide for Small Office Buildings*: American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. (www.ashrae.org).
- Askar, H., Probert, S. D., & Batty, W. J. (2001). Windows for buildings in hot arid countries. *Applied Energy*, 70(1), 77-101.
- Bahaj, A. S., James, P. A. B., & Jentsch, M. F. (2008). Potential of emerging glazing technologies for highly glazed buildings in hot arid climates. *Energy and Buildings*, 40(5), 720-731.
- Baldinelli, G. (2009). Double skin facades for warm climate regions: Analysis of a solution with an integrated movable shading system. *Building and Environment*, 44(6), 1107-1118.

Bansal, N. K. (1994). combined heating and cooling. In G. H. Narenda K. Bansal, Gernot Minke (Ed.), *Passive building design* Netherlands: Elsevier Science B.V.

Bansal, N. K. (1994). Concepts and Elements of Natural Climate Control. In G. H. Narenda K. Bansal, Gernot Minke (Ed.), *Passive building design* Netherlands: Elsevier Science B.V.

Belarbi, R., Ghiaus, C., & Allard, F. (2006). Modeling of water spray evaporation: Application to passive cooling of buildings. *Solar Energy*, 80(12), 1540-1552.

Bessoudo, M., Tzempelikos, A., Athienitis, A. K., & Zmeureanu, R. (2010). Indoor thermal environmental conditions near glazed facades with shading devices - Part I: Experiments and building thermal model. *Building and Environment*, 45(11), 2506-2516.

Breitenbach, J., Lart, S., Längle, I., & Rosenfeld, J. L. J. (2001). Optical and thermal performance of glazing with integral venetian blinds. *Energy and Buildings*, 33(5), 433-442.

Butera, F. M. (2005). Glass architecture: is it sustainable? Paper presented at the International Conference "Passive and Low Energy Cooling for the Built Environment".

Button, D., & Waldron, B. (Eds.). (1993). *Glass in Building: A guide to Modern Architectural Glass Performance*. Spain: Pilkington Glass Limited.

Caissie, D., Satish, M. G., & El-Jabi, N. (2007). Predicting water temperatures using a deterministic model: Application on Miramichi River catchments (New Brunswick, Canada). *Journal of Hydrology* 336, 303- 315.

Capeluto, I. G. (2003). Energy performance of the self-shading building envelope. *Energy and Buildings*, 35(3), 327-336.

Castro, A. P. A. S., Labaki, L. C., Gutierrez, G. C. R., & Assis, R. M. C. d. (2005). Thermal performance of different glazing surfaces in a hot climate. Paper presented at the International conference "Passive and low energy cooling for the built environment".

Chabas, A., Gentaz, L., Lombardo, T., Sinagre, R., Falcone, R., Verità, M., et al. (2010). Wet and dry atmospheric deposition on TiO₂ coated glass. [doi: DOI: 10.1016/j.envpol.2010.04.003]. *Environmental Pollution*, 158(12), 3507-3512.

Chan, H. Y., Riffat, S. B., & Zhu, J. (2010). Review of passive solar heating and cooling technologies. *Renewable and Sustainable Energy Reviews*, 14(2), 781-789.

Cheng, V., Ng, E., & Givoni, B. (2005). Effect of envelope colour and thermal mass on indoor temperatures in hot humid climate. *Solar Energy*(78), 528-534.

Chow, T.-t., Li, C., & Lin, Z. (2010). Innovative solar windows for cooling-demand climate. *Solar Energy Materials and Solar Cells*, 94(2), 212-220.

Chowdhury, H., & Cortie, M. B. (2007). Thermal stresses and cracking in absorptive solar glazing. *Construction and Building Materials*, 21(2), 464-468.

Compagno, A. (2002). *Intelligent Glass Facades*. Berlin: Birkhauser-Publisher for architecture.

Darus, Z. M. (2009). Potential Development of Rainwater Harvesting in Malaysia. Paper presented at the The 3rd WSEAS International Conference on ENERGY PLANNING, ENERGY SAVING, ENVIRONMENTAL EDUCATION, Canary Islands, Spain.

Datta, G. (2001). Effect of fixed horizontal louver shading devices on thermal performance of building by TRNSYS simulation. *Renewable Energy*, 23(3-4), 497-507.

Davies, C. M., Roser, D. J., Feitz, A. J., & Ashbolt, N. J. (2009). Solar radiation disinfection of drinking water at temperate latitudes: Inactivation rates for an optimised reactor configuration. *Water Research*, 43, 643 - 652.

Davies, M. G. (2004). *Building Heat Transfer*. UK: John Wiley & Sons.

Deal, B. M., Nemeth, R. J., & DeBaille, L. P. (1998). *Energy Conservation Strategies for Windows and Glazed Surfaces: US army corps of engineers, Construction Engineering Research Laboratories*.

DOE. (1998). *Spectrally Selective Glazings: A Well Proven Window Technology to Reduce Energy Costs While Enhancing Daylight and View: Federal Energy Management Program, United States Department of Energy*.

Edwards, R., & Lake, J. (1965). Transmission of solar radiation in a large-span East-West glasshouse: II. Distinction between the direct and diffuse components of the incident radiation. *Journal of Agricultural Engineering Research*, 10(2), 125-131.

El Demery, I. M. (2010). *Sustainable Architectural Design: Reviving Traditional Design and Adapting Modern Solutions*. *International Journal of Architectural Research*, 99.

Elminir, H. K., Areed, F. F., & Elsayed, T. S. (2005). Estimation of solar radiation components incident on Helwan site using neural networks. *Solar energy*, 79(3), 270-279.

Elminir, H. K., Azzam, Y. A., & Younes, F. I. (2007). Prediction of hourly and daily diffuse fraction using neural network, as compared to linear regression models. *Energy*, 32(8), 1513-1523.

Erell, E., Etzion, Y., Carlstrom, N., Sandberg, M., Molina, J., Maestre, I., et al. (2004). "SOLVENT": development of a reversible solar-screen glazing system. *Energy and Buildings*, 36(5), 467-480.

Expo. (1992). EXP880AA-011, The British pavilion at Seville World Expo 1992. Retrieved 19-08, 2011

Fairuz, S. F. S., & Sia, S.-J. (2004). Sunlight control and daylight distribution analysis: the KOMTAR case study. *Building and Environment*, 39(6), 713-717.

Fisette, P. (1998). Understanding Energy-Efficient Windows. *Fine Homebuilding*, 114(4).

Fisk, W. J. (2000). Health and productivity gains from better indoor environments and their relationship with building energy efficiency. *Annual Review of Energy and the Environment*, 25(1), 537-566.

Fong, F. A., & Chong, T. Y. (1999). *Designing with Glass, a design guide for glass architecture in tropics*. Singapore: National University of Singapore, Faculty of Architecture, Building and Real Estate.

Fong, K. F., Chow, T. T., Li, C., Lin, Z., & Chan, L. S. (2010). Effect of neutral temperature on energy saving of centralized air-conditioning systems in subtropical Hong Kong. [doi: DOI: 10.1016/j.applthermaleng.2010.03.024]. *Applied Thermal Engineering*, 30(13), 1659-1665.

Fraenkel, J. R., & Wallen, N. E. (2006). *How to Design and Evaluate Research in Education*. New York: McGraw-Hill.

GBI. (2009). *Green Building Index (GBI), rating system*. 2009

Gissen, D. (2002). *Big and Green: Toward Sustainable Architecture in the 21st Century*. China: Princeton Architectural Press.

Gleick, P. H. (2000). *The world's water 2000-2001: the biennial report on freshwater resources*: Island Pr.

Gratia, E., & De Herde, A. (2007). Greenhouse effect in double-skin facade. *Energy and Buildings*, 39(2), 199-211.

Gratia, E., & De Herde, A. (2007). The most efficient position of shading devices in a double-skin facade. *Energy and Buildings*, 39(3), 364-373.

Groat, L., & Wang, D. (2002). *Architectural Research Methods* New York: John Wiley & Sons.

GSB. (2009). *Green Building Index Design Reference Guide*.

Gueymard, C. A., & duPont, W. C. (2009). Spectral effects on the transmittance, solar heat gain, and performance rating of glazing systems. [doi: 10.1016/j.solener.2008.12.012]. *Solar Energy*, 83(6), 940-953.

Han, M. Y., & Mun, J. S. (2007). Particle behaviour consideration to maximize the settling capacity of rainwater storage tanks. *Water Science and Technology*, 56(11), 73-80.

Hassall, D. N. H. (1977). *Reflective Insulation and the Control of Thermal Environment* Sydney: ST REGIS-ACI PTY LTD.

Hauser, N., G., MinG. (1994). *passive building design in combined heating and cooling*: Elsevier Science B.V.

He, J., & Hoyano, A. (2008). A numerical simulation method for analyzing the thermal improvement effect of super-hydrophilic photocatalyst-coated building surfaces with water film on the urban/built environment. *Energy and Buildings*, 40(6), 968-978.

He, J., & Hoyano, A. (2010). Experimental study of cooling effects of a passive evaporative cooling wall constructed of porous ceramics with high water soaking-up ability. *Building and Environment*, 45(2), 461-472.

Helmreich, B., & Horn, H. (2009). Opportunities in rainwater harvesting. *Desalination*, Elsevier B.V., 248, 118–124.

Hong, W., Chiang, M. S., Shapiro, R. A., & Clifford, M. L. (2007). *Building Energy Efficiency, Why Green Buildings Are Key to Asia's Future*. Hong Kong: Asia Business Council.

James, P. A. B., & Bahaj, A. S. (2005). Smart glazing solutions to glare and solar gain: a 'sick building' case study. *Energy and Buildings*, 37(10), 1058-1067.

Kasturi, H. (2006). Hijjas Kasturi Associates Retrieved 18Feb.2010, 2010

Kerr, T. (2008). The green future of buildings. *FUTURARC*, 10.

Kim, G., & Kim, J. T. (2003). Projecting performance of reintroduced direct sunlight based on the local meteorological features. *Solar energy materials and solar cells*, 80(1), 85-94.

Kimmins, T. W. a. S. (2000). *Green building, hand book, a guid to building products and their impact on the environment*, (Vol. 2). Lond: Spon Press.

Klems, J., & Warner, J. (1997). Solar heat gain coefficient of complex fenestrations with a venetian blind for differing slat tilt angles. *ASHRAE Transactions*, 103(1), 1026-1034.

Krauter, S. (2004). Increased electrical yield via water flow over the front of photovoltaic panels. [doi: DOI: 10.1016/j.solmat.2004.01.011]. *Solar energy materials and solar cells*, 82(1-2), 131-137.

Krauter, S., & Grunow, P. (2006). Optical simulation to enhance PV module encapsulation. Paper presented at the Proc. 21st Eur. Photovoltaic Solar Energy Conf. Exhib. .

Kuehn, T. H. (2005). *ASHRAE Handbook of Fundamentals*, . New York, : American Society of Heating, Refrigerating, and Air Conditioning Engineering.

Kumano, T., & Hanamura, K. (2004). Spectral Control of Transmission of Diffuse Irradiation using Piled AR Coated Quartz Glass Filters. *AIP Conference Proceedings*, 738(1), 230-236.

Laar, M., & Grimme, F. W. (2002). *Sustainable Buildings in the Tropics*. Paper presented at the RIO 02 - World Climate & Energy Event, January 6-10, 2002, Rio de Janeiro, Brazil.

Langford, V. S., McKinley, A. J., & Quickenden, T. I. (2001). Temperature Dependence of the Visible-Near-Infrared Absorption Spectrum of Liquid Water. *The Journal of Physical Chemistry A*, 105(39), 8916-8921.

Lechner, N. (2009). *Heating, Cooling, Lighting: Sustainable Design Methods for Architects*. U.S.: John Wiley & Sons, Inc.

Li, D. H. W., & Lam, J. C. (2000). Measurements of solar radiation and illuminance on vertical surfaces and daylighting implications. *Renewable energy*, 20(4), 389-404.

Li, D. H. W., & Lam, J. C. (2001). Analysis of solar heat gain factors using sky clearness index and energy implications. *Energy Conversion and Management*, 42(5), 555-571.

- Ma, Q.-B., He, H.-P., Ye, Z.-Z., Zhu, L.-P., Huang, J.-Y., Zhang, Y.-Z., et al. (2008). Effects of Mg doping on the properties of highly transparent conductive and near infrared reflective Zn_{1-x}Mg_xO:Ga films. *Journal of Solid State Chemistry*, 181(3), 525-529.
- Machida, M., Norimoto, K., Watanabe, T., Hashimoto, K., & Fujishima, A. (1999). The effect of SiO₂ addition in super-hydrophilic property of TiO₂ photocatalyst. *Journal of Materials science*, 34(11), 2569-2574.
- Malaysia. (2007). Code of Practice on Energy Efficiency and Use of Renewable Energy for Non-Residential Buildings. MS 1525.
- Manz, H. (2004). Total solar energy transmittance of glass double façades with free convection. [doi: DOI: 10.1016/j.enbuild.2003.10.003]. *Energy and Buildings*, 36(2), 127-136.
- Mason, M., & Kingston, T. (2010). Why determining thermal loads through windows is such a pane. *ECOLIBRIUM*, AIRAH
- Menzies, G. F., & Wherrett, J. R. (2005). Windows in the workplace: examining issues of environmental sustainability and occupant comfort in the selection of multi-glazed windows. *Energy and Buildings*, 37(6), 623-630.
- Mingfang, T. (2002). Solar control for buildings. *Building and Environment*, 37(7), 659-664.
- Miyazaki, T., Akisawa, A., & Kashiwagi, T. (2005). Energy savings of office buildings by the use of semi-transparent solar cells for windows. *Renewable energy*, 30(3), 281-304.
- Mohelnikova, J. (2009). Materials for reflective coatings of window glass applications. *Construction and Building Materials*, 23(5), 1993-1998.
- Morrison, G. (1992). Solar radiation data for Indonesia. *Solar energy*, 49(1), 65-76.
- Moss, K. J. (2007). *Heat and Mass Transfer in Buildings*. London and New York: Taylor & Francis.
- MSG. (2009). Technical Data, Glass Performance Data. Retrieved 13-9, 2009
- Muneer, T. (1997). *Solar Radiation and Daylight Models for the Energy Efficient Design of Buildings*: British Library
- Nagamedianova, Z., Ramírez-García, R., Flores-Arèvalo, S., Miki-Yoshida, M., & Arroyo-Ortega, M. (2011). Solar heat reflective glass by nanostructured sol-gel multilayer coatings. *Optical Materials*.
- Nitz, P., & Hartwig, H. (2005). Solar control with thermotropic layers. *Solar Energy*, 79(6), 573-582.
- Oh, T. H., & Chua, S. C. (2010). Energy efficiency and carbon trading potential in Malaysia. [doi: DOI: 10.1016/j.rser.2010.03.029]. *Renewable and Sustainable Energy Reviews*, 14(7), 2095-2103.

- Pal, S., Roy, B., & Neogi, S. (2009). Heat transfer modelling on windows and glazing under the exposure of solar radiation. *Energy and Buildings*, 41(6), 654-661.
- Paoli, C., Voyant, C., Muselli, M., & Nivet, M. L. (2010). Forecasting of preprocessed daily solar radiation time series using neural networks. *Solar energy*, 84(12), 2146-2160.
- Pedrin, A. (2003). Integration Of Low Energy Strategies To The Early Stages Of Design Process Of Office Buildings In Warm Climate. The University of QUEENSLAND, Australia.
- Pfrommer, P., Lomas, K. J., Seale, C., & Kupke, C. (1995). The radiation transfer through coated and tinted glazing. *Solar Energy*, 54(5), 287-299.
- Pfrommer, P., Lomas, K. J., Seale, C., & Kupke, C. (1995). The radiation transfer through coated and tinted glazing. *Solar Energy*, 54(5), 287-299.
- Pieters, J., Pollet, I., & DE CLERCQ, S. (1997). Measuring facility for light transmittance and diffusion of condensation or rain covered glazing materials.
- Pollet, I. V., & Pieters, J. G. (2000). Condensation and Radiation Transmittance of Greenhouse Cladding Materials, Part 2: Results for a Complete Condensation Cycle. [doi: 10.1006/jaer.1999.0487]. *Journal of Agricultural Engineering Research*, 75(1), 65-72.
- Pollet, I. V., Pieters, J. G., & Verschoore, R. (2003). Impact of water drops on the visible radiation transmittance of glazings under outside radiant conditions. Elsevier Science Ltd., 73.
- Posadillo, R., & López Luque, R. (2009). Hourly distributions of the diffuse fraction of global solar irradiation in Córdoba (Spain). *Energy Conversion and Management*, 50(2), 223-231.
- PTM. (2008). Energy Efficiency and Conservation Guidelines for Malaysian Industries. Part 1 – Electrical Energy-use Equipment.
- Qahtan, A., Keumala, N., Rao, S., & Abdul-Samad, Z. (2011). Experimental determination of thermal performance of glazed-fa ades with water film, under direct solar radiation in the tropics. *Building and Environment*, 46(11), 2238-2246.
- Qahtan, A., Keumala, N., Rao, S., & Alashwal, A. M. (2012). A Case Study to Assess the near-Glazed Workplace Thermal Performance. *Advanced Materials Research*, 374, 1724-1732.
- Qahtan, A. M., Keumala, N. I. M., & Rao, S. P. (2010). Occupant satisfaction in respect to indoor environmental quality in energy efficient certified buildings in malaysia. Paper presented at the 16th International Conference of the CIB W104 Open Building Implementation on “Open and Sustainable Building”, Bilbao, Spain.
- Reimann, G. (2010). Daylight for Greener Buildings. Paper presented at the SB10SEA.
- Reppel, J., & Edmonds, I. R. (1998). Angle-selective glazing for radiant heat control in buildings: theory. *Solar Energy*, 62(3), 245-253.
- ResearchInChina. (2010). Global and China Low-E Glass Industry Report. China.

- Rijal, H., Tuohy, P., Humphreys, M., Nicol, J., Samuel, A., & Clarke, J. (2007). Using results from field surveys to predict the effect of open windows on thermal comfort and energy use in buildings. *Energy and Buildings*, 39(7), 823-836.
- Rincón, J., Almaro, N., & González, E. (2001). Experimental and numerical evaluation of a solar passive cooling system under hot and humid climatic conditions. *Solar Energy*, 71(1), 71-80.
- Roller, W., & Goldman, R. (1967). Estimation of solar radiation environment. *International Journal of Biometeorology*, 11(3), 329-336.
- Russell, M. B., & Surendran, P. N. (2001). Influence of active heat sinks on fabric thermal storage in building mass. *Applied Energy*, 70(1), 17-33.
- Saidur, R. (2009). Energy consumption, energy savings, and emission analysis in Malaysian office buildings. *Energy Policy*, 37(10), 4104-4113.
- Saleh, M. A., Kaseb, S., & El-Refaie, M. F. (2004). Glass-azimuth modification to reform direct solar heat gain. *Building and Environment*, 39(6), 653-659.
- Shafii, F., Ali, Z. A., & Othman, M. Z. (2006). Achieving Sustainable Construction in the Developing Countries of Southeast Asia. Paper presented at the The 6th Asia-Pacific Structural Engineering and Construction Conference, APSEC
- Simmler, H., & Binder, B. (2008). Experimental and numerical determination of the total solar energy transmittance of glazing with venetian blind shading. *Building and Environment*, 43(2), 197-204.
- Snyder, J. C. (Ed.). (1984). *Architectural Research* New York: Van Nostrand.
- Sottile, G. M. (2005). 2004 Survey of United States architects on the subject of switchable glazings. *Materials Science and Engineering B*, 119(3), 240-245.
- Takata, Y., Hidaka, S., Yamashita, A., & Yamamoto, H. (2004). Evaporation of water drop on a plasma-irradiated hydrophilic surface. [doi: DOI: 10.1016/j.ijheatfluidflow.2003.11.008]. *International Journal of Heat and Fluid Flow*, 25(2), 320-328.
- Taufiq, B. N., H.H. Masjuki, T.M.I. Mahlia, M.A. Amalina, M.S. Faizul, R. Saidur. (2007). Exergy analysis of evaporative cooling for reducing energy use in a Malaysian building. *Desalination, Elsevier B.V.*, 209, 238-243.
- Tsuge, Y., Kim, J., Sone, Y., Kuwaki, O., & Shiratori, S. (2008). Fabrication of transparent TiO₂ film with high adhesion by using self-assembly methods: Application to super-hydrophilic film. *Thin Solid Films*, 516(9), 2463-2468.
- Tuchinda, C., Srivannaboorn, S., & Lim, H. W. (2006). Photoprotection by window glass, automobile glass, and sunglasses. [doi: DOI: 10.1016/j.jaad.2005.11.1082]. *Journal of the American Academy of Dermatology*, 54(5), 845-854.

Tzempelikos, A. (2008). The impact of venetian blind geometry and tilt angle on view, direct light transmission and interior illuminance. *Solar Energy*, 82(12), 1172-1191.

U.S.DOE. (1994). *Advances in Glazing Materials for Windows*.

Underwood, C. P., & Yik, F. W. H. (2004). *Modelling Methods for Energy in Buildings*. Oxford, UK: Blackwell Science.

USGBC. (2009). *Introductory Presentation*. 2009

Van Moeseke, G., Bruyère, I., & De Herde, A. (2007). Impact of control rules on the efficiency of shading devices and free cooling for office buildings. *Building and Environment*, 42(2), 784-793.

Vangtook, P., & Chirarattananon, S. (2006). An experimental investigation of application of radiant cooling in hot humid climate. *Energy and Buildings*, 38(4), 273-285.

Vangtook, P., & Chirarattananon, S. (2007). Application of radiant cooling as a passive cooling option in hot humid climate. *Building and Environment*, 42(2), 543-556.

Vangtook, P. C., Surapong (2005). Application of radiant cooling as a passive cooling option in hot humid climate. *Building and Environment*, 42, 543–556.

Vijayakumar, G., Kummert, M., Klein, S. A., & Beckman, W. A. (2005). Analysis of short-term solar radiation data. *Solar Energy*, 79(5), 495-504.

Vorster, W. J. J., Schwindt, S. A., Schupp, J., & Korsunsky, A. M. (2009). Analysis of the spray field development on a vertical surface during water spray-quenching using a flat spray nozzle. *Applied Thermal Engineering*, 29(7), 1406-1416.

Voss, K., Kubn, T. E., Nitz, P., Herkel, S., Wall, M., & Hellstrom, B. (2007). Solar Control. In M. Santamouris (Ed.), *Advances in passive cooling*. London: Earthscan in the UK & USA.

Wasley, J. H., & Utzinger, M. (1996). *Vital Signs: Glazing Performance Package*. Retrieved 12-5, 2008

Watkin, D. (2005). *A history of Western architecture*: Laurence King Publishers.

Wendelstorf, J., Spitzer, K. H., & Wendelstorf, R. (2008). Spray water cooling heat transfer at high temperatures and liquid mass fluxes. *International Journal of Heat and Mass Transfer*, 51(19-20), 4902-4910.

West, S. (2001). Improving the sustainable development of building stock by the implementation of energy efficient, climate control technologies. *Building and Environment*, 36(3), 281-289.

West, S. (2001). Improving the sustainable development of building stock by the implementation of energy efficient, climate control technologies. *Building and Environment*, 36(3), 281-289.

Woolley, T., & Kimmins, S. (2002). *Green building, hand book, a guid to building products and their impact on the environment (Vol. volume2)*. London: Tom Woolley.

- Wu, C.-W., & Lin, T.-H. (2007). Full-scale evaluations on heat resistance of glass panes incorporated with water film or sprinkler in a room fire. *Building and Environment*, 42(9), 3277-3284.
- Yamtraipat, N., Khedari, J., Hirunlabh, J., & Kunchornrat, J. (2006). Assessment of Thailand indoor set-point impact on energy consumption and environment. [doi: DOI: 10.1016/j.enpol.2004.07.009]. *Energy Policy*, 34(7), 765-770.
- Yang, L., Lam, J. C., & Tsang, C. L. (2008). Energy performance of building envelopes in different climate zones in China. *Applied Energy*, 85(9), 800-817.
- Yeang, K. (2006). *Ecodesign, a Manual for Ecological design* London: John Wiley and Sons.
- Yu, J., Yang, C., & Tian, L. (2008). Low-energy envelope design of residential building in hot summer and cold winter zone in China. *Energy and Buildings*, 40(8), 1536-1546.
- Yuan, T., Fengmin, L., & Puhai, L. (2003). Economic analysis of rainwater harvesting and irrigation methods, with an example from China. *Agricultural water management*, 60(3), 217-226.
- Yuen, B. (2005). Romancing the high-rise in Singapore. *Cities*, 22(1), 3-13.
- Zain, Z. M., Taib, M. N., & Baki, S. M. S. (2007). Hot and humid climate: prospect for thermal comfort in residential building. *Desalination*, 209(1-3), 261-268.
- Zain-Ahmad, A. (2000). *Daylighting and Shading for Thermal Comfort in Malaysian Buildings*. University of Hertfordshire, Hertfordshire.
- Zain-Ahmed, A. (2008). *Integrating Sustainable Energy in Buildings :A Case Study in Malaysia* Paper presented at the FAU.
- Zain-Ahmed, A. (2009). *Climate Change, Green Technology and Sustainable Buildings*. Kula Lumpur: University Publication Center,UiTM.
- Zain-Ahmed, A., Sopian, K., Zainol Abidin, Z., & Othman, M. Y. H. (2002). The availability of daylight from tropical skies--a case study of Malaysia. *Renewable Energy*, 25(1), 21-30.
- Zhou, D. W., Gambaryan-Roisman, T., & Stephan, P. (2009). Measurement of water falling film thickness to flat plate using confocal chromatic sensing technique. *Experimental Thermal and Fluid Science*, 33(2), 273-283.