

## References

- [1] A. M. Morales and C. M. Lieber, "A Laser Ablation Method for the Synthesis of Crystalline Semiconductor Nanowires," *Science*, vol. 279, no. 5348, pp. 208-211, January 9, 1998 1998.
- [2] J. Chen, M. A. Reed, A. M. Rawlett, and J. M. Tour, "Large On-Off Ratios and Negative Differential Resistance in a Molecular Electronic Device," *Science*, vol. 286, no. 5444, pp. 1550-1552, November 19, 1999 1999.
- [3] J. Westwater, D. P. Gosain, S. Tomiya, S. Usui, and H. Ruda, "Growth of silicon nanowires via gold/silane vapor--liquid--solid reaction," *Journal of Vacuum Science & Technology B: Microelectronics and Nanometer Structures*, vol. 15, no. 3, pp. 554-557, 1997.
- [4] G. Brambilla, V. Finazzi, and D. Richardson, "Ultra-low-loss optical fiber nanotapers," *Opt. Express*, vol. 12, no. 10, pp. 2258-2263, 2004.
- [5] A. M. Clohessy, N. Healy, D. F. Murphy, and C. D. Hussey, "Short low-loss nanowire tapers on singlemode fibres," *Electronics Letters*, vol. 41, no. 17, pp. 954-955, 2005.
- [6] X. Xing, Y. Wang, and B. Li, "Nanofibers drawing and nanodevices assembly in poly(trimethylene terephthalate)," *Opt. Express*, vol. 16, no. 14, pp. 10815-10822, 2008.
- [7] S. Harun, K. Lim, A. Jasim, and H. Ahmad, "Fabrication of tapered fiber based ring resonator," *Laser Physics*, vol. 20, no. 7, pp. 1629-1631, 2010.
- [8] F. Bilodeau, K. O. Hill, S. Faucher, and D. C. Johnson, "Low-loss highly overcoupled fused couplers: fabrication and sensitivity to external pressure," *Lightwave Technology, Journal of*, vol. 6, no. 10, pp. 1476-1482, 1988.

- [9] P. Hoffmann, B. Dutoit, and R.-P. Salathé, "Comparison of mechanically drawn and protection layer chemically etched optical fiber tips," *Ultramicroscopy*, vol. 61, no. 1-4, pp. 165-170, 1995.
- [10] D. R. C. T. Turner, Morris County, NJ), "Etch procedure for optical fibers," United States Patent, 1984.
- [11] P. K. Wong, Wang, T., Ho, C.,, "Optical fiber tip fabricated by surface tension controlled etching," in *Proceedings of Solid. State Sensor Actuator and Microsystems Workshop Transducers Research Foundation*, Cleveland, Ohio, 2002, pp. 94-97.
- [12] R. Stockle, C. Fokas, V. Deckert, R. Zenobi, B. Sick, B. Hecht, and U. P. Wild, "High-quality near-field optical probes by tube etching," *Applied Physics Letters*, vol. 75, no. 2, pp. 160-162, 1999.
- [13] J. C. Graf, S. A. Teston, P. V. de Barba, J. Dallmann, J. A. S. Lima, H. J. Kalinowski, and A. S. Paterno, "Fiber taper rig using a simplified heat source and the flame-brush technique," in *Microwave and Optoelectronics Conference (IMOC), 2009 SBMO/IEEE MTT-S International*, 2009, pp. 621-624.
- [14] T. A. Birks and Y. W. Li, "The shape of fiber tapers," *Lightwave Technology, Journal of*, vol. 10, no. 4, pp. 432-438, 1992.
- [15] L. Ding, C. Belacel, S. Ducci, G. Leo, and I. Favero, "Ultralow loss single-mode silica tapers manufactured by a microheater," *Appl. Opt.*, vol. 49, no. 13, pp. 2441-2445, 2010.
- [16] F. Orucevic, V. Lefèvre-Seguin, and J. Hare, "Transmittance and near-field characterization of sub-wavelength tapered optical fibers," *Opt. Express*, vol. 15, no. 21, pp. 13624-13629, 2007.

- [17] J. D. Love, W. M. Henry, W. J. Stewart, R. J. Black, S. Lacroix, and F. Gonthier, "Tapered single-mode fibres and devices. I. Adiabaticity criteria," *Optoelectronics, IEE Proceedings J*, vol. 138, no. 5, pp. 343-354, 1991.
- [18] O. Frazão and et al., "Chirped Bragg grating fabricated in fused fibre taper for strain-temperature discrimination," *Measurement Science and Technology*, vol. 16, no. 4, p. 984, 2005.
- [19] J. Mora, A. Diez, M. V. Andres, P. Y. Fonjallaz, and M. Popov, "Tunable dispersion compensator based on a fiber Bragg grating written in a tapered fiber," *Photonics Technology Letters, IEEE*, vol. 16, no. 12, pp. 2631-2633, 2004.
- [20] N. Q. Ngo, S. Y. Li, R. T. Zheng, S. C. Tjin, and P. Shum, "Electrically tunable dispersion compensator with fixed center wavelength using fiber Bragg grating," *Lightwave Technology, Journal of*, vol. 21, no. 6, pp. 1568-1575, 2003.
- [21] J. Zhang, P. Shum, X. P. Cheng, N. Q. Ngo, and S. Y. Li, "Analysis of linearly tapered fiber Bragg grating for dispersion slope compensation," *Photonics Technology Letters, IEEE*, vol. 15, no. 10, pp. 1389-1391, 2003.
- [22] Z. Liu, C. Guo, J. Yang, and L. Yuan, "Tapered fiber optical tweezers for microscopic particle trapping: fabrication and application," *Opt. Express*, vol. 14, no. 25, pp. 12510-12516, 2006.
- [23] F. Xu, G. Brambilla, and D. J. Richardson, "Adiabatic SNOM tips for optical tweezers," ed, 2006.
- [24] G. Brambilla, F. Xu, and X. Feng, "Fabrication of optical fibre nanowires and their optical and mechanical characterisation," *Electronics Letters*, vol. 42, no. 9, pp. 517-519, 2006.
- [25] F. Xu and G. Brambilla, "Embedding optical microfiber coil resonators in Teflon," *Opt. Lett.*, vol. 32, no. 15, pp. 2164-2166, 2007.

- [26] Y. Jung, G. S. Murugan, G. Brambilla, and D. J. Richardson, "Embedded Optical Microfiber Coil Resonator With Enhanced High-Q," *Photonics Technology Letters, IEEE*, vol. 22, no. 22, pp. 1638-1640, 2010.
- [27] R. Zhang, J. Teipel, X. Zhang, D. Nau, and H. Giessen, "Group velocity dispersion of tapered fibers immersed in different liquids," *Opt. Express*, vol. 12, no. 8, pp. 1700-1707, 2004.
- [28] T. A. Birks, W. J. Wadsworth, and P. S. J. Russell, "Supercontinuum generation in tapered fibers," *Opt. Lett.*, vol. 25, no. 19, pp. 1415-1417, 2000.
- [29] M. D. Pelusi, F. Luan, E. Magi, M. R. Lamont, D. J. Moss, B. J. Eggleton, J. S. Sanghera, L. B. Shaw, and I. D. Aggarwal, "High bit rate all-optical signal processing in a fiber photonic wire," *Opt. Express*, vol. 16, no. 15, pp. 11506-11512, 2008.
- [30] M. Rusu, R. Herda, S. Kivistö, and O. G. Okhotnikov, "Fiber taper for dispersion management in a mode-locked ytterbium fiber laser," *Opt. Lett.*, vol. 31, no. 15, pp. 2257-2259, 2006.
- [31] Fei Lu, Yujun Deng, and Wayne H. Knox, "Generation of broadband femtosecond visible pulses in dispersion-micromanaged holey fibers," *Opt. Lett.* vol. 30, no. 12, pp.1566-1568, 2005.
- [32] J. Hult, R. S. Watt, and C. F. Kaminski, "Dispersion Measurement in Optical Fibers Using Supercontinuum Pulses," *Lightwave Technology, Journal of*, vol. 25, no. 3, pp. 820-824, 2007.
- [33] B. Costa, M. Puleo, and E. Vezzoni, "Phase-shift technique for the measurement of chromatic dispersion in single-mode optical fibres using LEDs," *Electronics Letters*, vol. 19, no. 25, pp. 1074-1076, 1983.

- [34] L. F. Mollenauer, P. V. Mamyshev, and M. J. Neubelt, "Method for facile and accurate measurement of optical fiber dispersion maps," *Opt. Lett.*, vol. 21, no. 21, pp. 1724-1726, 1996.
- [35] H.-T. Shang, "Chromatic dispersion measurement by white-light interferometry on metre-length single-mode optical fibres," *Electronics Letters*, vol. 17, no. 17, pp. 603-605, 1981.
- [36] Q. Ye, C. Xu, X. Liu, W. H. Knox, M. F. Yan, R. S. Windeler, and B. Eggleton, "Dispersion Measurement of Tapered Air-Silica Microstructure Fiber by White-Light Interferometry," *Appl. Opt.*, vol. 41, no. 22, pp. 4467-4470, 2002.