

LIST OF FIGURES

	Page
Figure 2.1: Structure of LiCoO_2	6
Figure 2.2: XRD of (a) HT- LiCoO_2 (b) LT- LiCoO_2	7
Figure 2.3: Structure of LiNiO_2	9
Figure 2.4: XRD of LiNiO_2	10
Figure 2.5: Structure of LiMn_2O_4	13
Figure 2.6: XRD of LiMn_2O_4 (a) spray drying method (b) solid state reaction	13
Figure 2.7: Structure of LiFePO_4	17
Figure 2.8: Structure of LiNiVO_4	19
Figure 2.9: XRD patterns of LiNiVO_4 at different pH	20
Figure 2.10: Voltage versus discharge capacity	21
Figure 2.11: Specific capacity of (a) complex-precipitate gel method (b) solid state reaction	22
Figure 3.1: Chitosan modified solution evaporation method. By passing step 6 gives the solution evaporation method.	34
Figure 3.2: Preparation of ZnO coated LiNiVO_4	35
Figure 3.3: Reflection of Bragg's law	35

Figure 4.1:	XRD of LiNiVO_4 by solution evaporation method at sintering temperatures of (a) 500 °C (b) 600°C (c) 700 °C (d) 800 °C	41
Figure 4.2:	Crystallite size of LiNiVO_4 by solution evaporation method different sintering temperatures	44
Figure 4.3:	TEM images of LiNiVO_4 by solution evaporation method at sintering temperature of 500 °C	45
Figure 4.4:	TEM images of LiNiVO_4 by solution evaporation method at sintering temperature of 600 °C	46
Figure 4.5:	TEM images of LiNiVO_4 by solution evaporation method at sintering temperature of 700 °C	47
Figure 4.6:	TEM images of LiNiVO_4 by solution evaporation method at sintering temperature of 800 °C	48
Figure 4.7:	SEM image of LiNiVO_4 by solution evaporation method at sintering temperature of 500 °C	49
Figure 4.8:	SEM image of LiNiVO_4 by solution evaporation method at sintering temperature of 600 °C	50
Figure 4.9:	SEM image of LiNiVO_4 by solution evaporation method at sintering temperature of 700 °C	50
Figure 4.10:	Distribution of surface area of LiNiVO_4 by solution evaporation method at sintering temperature of 700 °C	51
Figure 4.11:	Distribution of diameter of LiNiVO_4 by solution evaporation method at sintering temperature of 700 °C	52
Figure 4.12:	SEM image of LiNiVO_4 by solution evaporation method at sintering temperature of 800 °C	52
Figure 4.13:	Distribution of surface area of LiNiVO_4 by solution evaporation method at sintering temperature of 800 °C	53
Figure 4.14:	Distribution of diameter of LiNiVO_4 by solution evaporation method at sintering temperature of 800 °C	54
Figure 4.15:	Cyclic voltammetry of LiNiVO_4 by solution evaporation method at sintering temperature of 700 °C	55

Figure 4.16:	Charge-discharge studies of LiNiVO_4 by solution evaporation method	56
Figure 4.17:	Cycling efficiency of LiNiVO_4 by solution evaporation method	57
Figure 4.18:	Capacity retention of LiNiVO_4 by solution evaporation method	57
Figure 5.1:	XRD of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperatures of (a) 500 °C (b) 600°C (c) 700 °C (d) 800 °C	60
Figure 5.2:	Crystallite size of LiNiVO_4 by chitosan modified solution evaporation method different sintering temperatures	63
Figure 5.3:	TEM images of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperature of 500 °C	64
Figure 5.4:	TEM images of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperature of 600 °C	65
Figure 5.5:	TEM images of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperature of 700 °C	66
Figure 5.6:	TEM images of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperature of 800 °C	67
Figure 5.7:	SEM image of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperature of 500 °C	68
Figure 5.8:	SEM image of LiNiVO_4 by chitosan modified solution evaporation method at sintering temperature of 600 °C	69
Figure 5.9:	SEM image of LiNiVO_4 by chitosan modified solution	69

	evaporation method at sintering temperature of 700 °C	
Figure 5.10:	Distribution of surface area of LiNiVO ₄ by chitosan modified solution evaporation method at sintering temperature of 700 °C	70
Figure 5.11:	Distribution of diameter of LiNiVO ₄ by chitosan modified solution evaporation method at sintering temperature of 700 °C	71
Figure 5.12:	SEM image of LiNiVO ₄ by chitosan modified solution evaporation method at sintering temperature of 800 °C	71
Figure 5.13:	Distribution of surface area of LiNiVO ₄ by chitosan modified solution evaporation method at sintering temperature of 800 °C	72
Figure 5.14:	Distribution of diameter of LiNiVO ₄ by chitosan modified solution evaporation method at sintering temperature of 800 °C	73
Figure 5.15:	Cyclic voltammetry of LiNiVO ₄ by chitosan modified solution evaporation method at sintering temperature of 700 °C	74
Figure 5.16:	Charge-discharge studies of LiNiVO ₄ by chitosan modified solution evaporation method	75
Figure 5.17:	Cycling efficiency of LiNiVO ₄ by chitosan modified solution evaporation method	76
Figure 5.18:	Capacity retention of LiNiVO ₄ by chitosan modified solution evaporation method	76
Figure 6.1:	XRD of ZnO coated LiNiVO ₄ at sintering temperature of 700 °C	78
Figure 6.2:	TEM images at 0.2 wt.% ZnO	82
Figure 6.3:	TEM images at 0.5 wt.% ZnO	83
Figure 6.4:	TEM images at 1.0 wt.% ZnO	84

Figure 6.5:	SEM images at 0.2 wt.% ZnO	85
Figure 6.6:	Distribution of surface area of 0.2 wt.% ZnO coated LiNiVO ₄	86
Figure 6.7:	Distribution of diameter of 0.2 wt.% ZnO coated LiNiVO ₄	86
Figure 6.8:	SEM images at 0.5 wt.% ZnO	87
Figure 6.9:	Distribution of surface area of 0.5 wt.% ZnO coated LiNiVO ₄	88
Figure 6.10:	Distribution of diameter of 0.5 wt.% ZnO coated LiNiVO ₄	88
Figure 6.11:	SEM images at 1.0 wt.% ZnO	89
Figure 6.12:	Distribution of surface area of 1.0wt.% ZnO coated LiNiVO ₄	90
Figure 6.13:	Distribution of diameter of 1.0 wt.% ZnO coated LiNiVO ₄	90
Figure 6.14:	Cyclic voltammetry of 0.2 wt.% of ZnO coated sample	92
Figure 6.15:	Cyclic voltammetry of 0.5 wt.% of ZnO coated sample	94
Figure 6.16:	Cyclic voltammetry of 1.0wt.% of ZnO coated sample	96
Figure 6.17:	Charge-discharge studies of 0.2 wt% ZnO coated LiNiVO ₄	97
Figure 6.18:	Charge-discharge studies of 0.5 wt% ZnO coated LiNiVO ₄	97
Figure 6.19:	Charge-discharge studies of 1.0 wt% ZnO coated LiNiVO ₄	98

Figure 6.20:	Cycling efficiency of ZnO coated LiNiVO ₄	98
Figure 6.21:	Capacity retention of ZnO coated LiNiVO ₄	99