## LIST OF FIGURES

			Page
Figure	1.0:	Repeating unit of PET	3
Figure	2.1:	The relationship between the equivalent weight ratio of PET:Gly and glycolysis conversion (%) of recycled PET flakes at 210°C and glycolysis time of 2.0 hours	20
Figure	2.2:	The relationship between the glycolysis temperature and glycolysis conversion of recycled PET flakes with a glycolysis time of 2.0 hours and 1:6 ratio of PET:Gly	21
Figure	2.3:	ln k versus 1/T	22
Figure	2.4:	The relationship between the glycolysis time and glycolysis conversion of recycled PET flakes with a glycolysis temperature at 210°C and ratio of PET:Gly of 1:6	24
Figure	2.5:	FTIR spectra for PET flakes before (A) and after (B) glycolysis	27
Figure	2.6:	NMR spectrum of the glycolysed product, GP3B	29
Figure	2.7:	Possible structure for the glycolysed product obtained in the glycolysis reaction of PET and glycerol	30
Figure	2.8:	TGA thermogram of the glycolyzed product, GP1B	32
Figure	2.9:	Thermogram of (a) glycerol-blue curve and (b) PET flakes-red curve	33
Figure	3.1:	Position of samples taken from cup-rise foam and direction of foam rise	45
Figure	3.2:	Schematic of the compression loading: (a) parallel to foaming direction and (b) perpendicular to foaming direction	46
Figure	3.3:	Effect of variation of glycolysed PET in the polyol mixture on viscosity	47
Figure	3.4:	Urethane reaction	48
Figure	3.5:	Semi-rigid PU foams	50
Figure	3.6:	Water reactions with isocyanate	52
Figure	3.7:	FTIR spectra of PU foam, polyol mixture and isocyanate	54
Figure	3.8:	FTIR spectrum of foaming process at a) 1 minute b) 90 min	55

]	Figure	3.9:	Optical microscope images of the semi-rigid foam	56
]	Figure	3.10:	Effect of top and bottom core of PU foam on density (a) and compression strength (b)	58
]	Figure	3.11:	Stress-strain curves of foam cells position at (a) 25% and (b) 50% compressive strain.	59
]	Figure	3.12:	Cell models of foams. Xu (2011)	61
]	Figure	3.13:	Effect of isocyanate index on the compression strength and density of the foam.	63
]	Figure	3.14:	Allophanate reactions	64
]	Figure	3.15:	Effect of percentage of glycolysed PET on the compression strength and density of the foam	66