

LIST OF FIGURES

Figure 1.1	Catalytic reaction of A and B become product; P
Figure 1.2	Potential energy diagram of a heterogeneous catalytic reaction with gaseous reactants, products and solid catalysts.
Figure 1.3	Potential energy profile for an exothermic reaction showing the lower E_a of catalysed reaction
Figure 1.4	Examples of commercial catalysts shapes.
Figure 1.5	Contrasting patterns of catalyst decay, a > < a, catalyst 1 discharged and new catalyst charged in; b > < b, catalyst 2 discharged and new charged in.
Figure 1.6	Flow-chart on work program
Figure 2.1	Structure and formula molecule of acrylic acid
Figure 2.2	Acrylic acid & acrylates esters process by Dow Celanese Chemicals (www.ebcohost.com/acrylic acid).
Figure 2.3	World consumption of crude acrylic acid until 2010 (http://www.sriconsulting.com/CEH/Public/Reports/606.4000/25 july 2011)
Figure 2.4	World consumption of crude acrylate esters until 2010 (http://www.sriconsulting.com/CEH/Public/Reports/606.4000/25 july 2011)
Figure 2.5	Products derived from acrylic acid (Widi 2004)
Figure 2.6	Global supply/ demand of crude acrylic acid
Figure 2.7	Global demand for production of acrylic acid until 2010 (Source: Tecnom Orbichem (London))
Figure 2.8	Global merchant sales of crude acrylic acid basis in 2007
Figure 2.9	Preparation scheme for precipitated catalysts. Optional preparation steps are indicated by square brackets (Ertl G. 1997)
Figure 2.10	Simplified scheme for the formation of a solid product from solution (Ertl G. 1997)
Figure 2.11	Parameters affecting the properties of the precipitate and main properties influenced (Ertl G. 1997)
Figure 2.12	Schematic diagram of spray dryer.

Figure 3.1	LabMax Reactor
Figure 3.2	In-situ profiles obtained from LabMax experiment
Figure 3.3	Spray dryer Büchi spray dryer B-290
Figure 3.4	Functional principle of the drying air
Figure 3.5	Functional principle of the feed and dispersion
Figure 3.6	LabMax
Figure 3.7	Spray Dryer
Figure 3.8	The urn reactor for calcinations of precursor sample
Figure 3.9	Schematic diagram for a diffractometers system
Figure 3.10	D8 Bruker X-Ray Diffraction
Figure 3.11	X-Ray Florescence S4 EXPLORER
Figure 3.12	Preparation of pressed pallet
Figure 3.13	Preparation of beads for powder sample
Figure 3.14	Liquid and loose powder method.
Figure 3.15	Scanning Electron Microscope with EDX
Figure 3.16	The IUPAC classification of adsorption isotherms
Figure 3.17	Quantachrome autosorb automated gas sorption system 6B
Figure 3.18	Fourier transform infra-red
Figure 3.19	Mettler Toledo TGA/SDTA851 ^e thermobalance
Figure 3.20	METTLER TOLEDO DSC 822 ^e equipment with an intra cooler
Figure 3.21	Temperature programmed desorption /reduction/ oxidation (TPD/R/O)
Figure 3.22	Temperature programmed reaction spectroscopy
Figure 3.23	The tubular micro reactor filled with the catalyst
Figure 3.24	Highthroughput nanoflow system
Figure 3.25	The COMBICAT nanoflow catalytic reactor system
Figure 3.26	Process flow diagram of Combicat Nanoflow automated catalytic reactor system
Figure 3.27	Reactor channel to the reactor blocks
Figure 3.28	Reactor tube
Figure 3.29	Online GC Agilent HP6890N GC
Figure 4.1:	The material balance during reproducibility testing using COMBICAT nanoflow
Figure 4.2:	Propane oxidation over undiluted MoVTeNbO _x catalysts at different methods. (a) Acrylic acid yield as a function of the reaction temperature.(b) The conversion of propane and selectivity of acrylic acid towards reaction temperature 653, 663,673,683 and 693 K. (c) The corresponding selectivity of CO _x and CO in different reaction time
Figure 4.3:	Propane oxidation over diluted MoVTeNbO _x catalysts at different methods. (a) Acrylic acid yield as a function of the reaction

	temperature.(b) The conversion of propane and selectivity of acrylic acid towards reaction temperature 653, 663, 673,683 and 693 K. (c) The corresponding selectivity of CO _x and CO in different reaction time.
Figure 5.1:	In-situ LabMax dried precursor. (a) Ammonium heptamolybdate heat up to 353 K, (b) Addition of Ammonium metavanadate at same temperature, (c) Addition of Telluric acid at 353 K and (d) Formation of slurry after adding Niobium oxalate solution at 313 K.
Figure 5.2:	Plot of different measurements recorded during the preparation of catalyst using Labmax.
Figure 5.3:	In-situ Raman spectra for aqueous solution of (a) AHM (pH 5.2, T=333K), (b) AHM (pH 5.0, T= 353 K), (c) AMV (pH 5.7, T=333 K), (d) Te(OH) ₆ (pH=3.7, T=296 K) and (e) (NH ₄) ₂ Nb ₂ (C ₂ O ₄) ₅ (pH=0.8, T=296 K)
Figure 5.4:	In-situ Raman spectra of (a) the binary MoV solution (pH=5.5, T= 353 K), (b) the ternary MoVTe solution (pH=5.0,T=353 K) and (c) the formation of MoVTeNb slurry
Figure 5.5:	a) Structure of typical Anderson-type anion (Cabello, I.L.Botto <i>et al.</i> 2000) and; b) Schematic representation of Anderson-type anion (Beato, A. Blume <i>et al.</i> 2006).
Figure 5.6:	Raman spectra of the spray dried precursors ; (a) MoVTeNb and (b) MoVTe
Figure 5.7:	Functional principle of the drying air
Figure 5.8:	Mini Spray Dryer Büchi B-290
Figure 5.9:	The formation of orange fine powder by mini spray drying unit
Figure 5.10:	Orange fine powder (MoVTeNb precursor) and black fine powder (MoVTeNb oxide catalyst)
Figure 5.11:	Experiment of evidence on Te evaporation during calcinations in inert atmosphere at 898 K.
Figure 5.12:	X-Ray diffraction patterns of (a) standard recipe for undiluted and (b) diluted Mo ₁ V _{0.3} Te _{0.23} Nb _{0.12} with reference to M1 and M2 phase simulation.
Figure 5.13:	X-ray diffraction pattern for precursor and activated Mo ₁ V _{0.3} Te _{0.23} Nb _{0.125} oxide catalyst.
Figure 5.14:	XRD patterns for catalyst A1 (standard sample) and catalyst A2 (addition of oxalic acid) of the MoVTeNbO catalyst with reference peaks: (●) M1 Phase or Te ₂ Mo ₂₀ O ₅₇ , (■) M2 phase or Te _{0.33} Mo _{3.33} , (○) MoO ₃ and (▨) TeMo ₅ O ₁₆
Figure 5.15	The crystalline and amorphous phases in TEM images for standard MoVTeNb oxide catalyst.

Figure 5.16	XRD patterns for catalyst B1 (standard diluted MoVTeNb oxide) and catalyst B2 (diluted MoVTeNb oxide with oxalic acid) with reference peaks: (●) M1 phase or $\text{Te}_2\text{Mo}_{20}\text{O}_{57}$, (■) M2 phase or $\text{Te}_{0.33}\text{Mo}_{3.33}$, (○) MoO_3 and (◻) $\text{TeMo}_5\text{O}_{16}$
Figure 5.17	Typical SEM images of the spray-dried MoVTeNb undiluted system, (a) MoVTeNb dried precursor (b) dried precursor after calcined at 548 K in air and (c) After heat treatment at 873 K in Argon
Figure 5.18	SEM images and EDX of undiluted $\text{Mo}_1\text{V}_{0.3}\text{Te}_{0.23}\text{Nb}_{0.125}\text{Ox}$ catalyst system after activation
Figure 5.19	SEM-images and EDX of undiluted $\text{Mo}_1\text{V}_{0.3}\text{Te}_{0.23}\text{Nb}_{0.125}\text{Ox}$ with oxalic acid after activation
Figure 5.20	SEM-images and EDX of the diluted $\text{Mo}_1\text{V}_{0.3}\text{Te}_{0.23}\text{Nb}_{0.125}\text{Ox}$ without oxalic acid after activation
Figure 5.21	SEM-images and EDX of the diluted $\text{Mo}_1\text{V}_{0.3}\text{Te}_{0.23}\text{Nb}_{0.125}\text{Ox}$ with oxalic acid after activation
Figure 5.22	FTIR spectra precursor for undiluted system before calcined
Figure 5.23	FTIR spectra catalyst for undiluted MoVTeNb oxide system after calcined
Figure 5.24	FTIR spectra precursor for undiluted MoVTeNb oxide system before calcined
Figure 5.25	FTIR spectra precursor for diluted MoVTeNb oxide system after calcined.
Figure 5.26	Distribution of surface area for undiluted and diluted MoVTeNbOx system
Figure 5.27	BET isotherm for undiluted (above) and diluted (below) system
Figure 5.28	TG curve in air and argon flow of the undiluted MoVTeNb oxide system (top) TGA and DTG data; (bottom) MS traces of gas evolved
Figure 5.29	TG curve in air and argon flow of the diluted MoVTeNb oxide system (top) TGA and DTG data; (bottom) MS traces of gas evolved
Figure 5.30	DSC signal of catalyst A1 and catalyst A2 (with oxalic acid) in undiluted system
Figure 5.31	DSC signal of catalyst B1 and catalyst B2 (with oxalic acid) in diluted system
Figure 5.32	Temperature-programmed reduction profile for undiluted (top) and diluted (bottom) MoVTeNb oxide catalyst.
Figure 6.1	TEM images of crystalline phase MoVTeNb oxide.
Figure 6.2	Conductivity curves undiluted MoVTeNbIOx samples leached in different solvents
Figure 6.3	Catalytic data on the non-leached sample (422), leached in water (551), leached in ammonia (562) and leached in nitric acid (566)
Figure 6.4	XRD patterns of calcined MoVTeNb catalyst leached at different solvent with reference peaks ; (●) M1 (■) M2
Figure 6.5	SEM images for MoVTeNbOx before and after leaching. (i); before leaching, (ii) after leaching bi-distilled water,(iii); after leaching in

	ammonia and (iv); after leaching in nitric acid.
Figure 6.6	Development of conductivity in undiluted & diluted MoVTeNbIOx samples during leaching in water for 1 and 24 hrs
Figure 6.7	Catalytic reactivity studies of undiluted and diluted MoVTeNb oxide leached in water for 1 and 24 hours.
Figure 6.8	Catalytic performance of undiluted and diluted MoVTeNb oxide catalyst
Figure 6.9	Catalytic performance of leached sample for 1 hr (679) and 24 hrs (680) and non-leached (675) of undiluted MoVTeNb oxide.
Figure 6.10	Catalytic performance of leached sample for 1 hr (676) and 24 hrs (678) and non -leached (675) of diluted MoVTeNb oxide.
Figure 6.11	XRD patterns of undiluted & diluted MoVTeNb catalyst leached in water with reference peaks: (●) M1phase and (■) M2 phase.
Figure 6.12	Morphology of undiluted MoVTeNb oxide before and after leached in water for 1 and 24 hours
Figure 6.13	Morphology of diluted MoVTeNb oxide before and after leached in water for 1 and 24 hours
Figure 6.14	XRF analysis of undiluted and diluted MoVTeNb oxide catalyst for non-leached and leached at 1 and 24 hours.
Figure 6.15	Schematic representation on the effect of phase formation and stability in the MoVTeNb mixed oxide catalyst.
Figure 6.16	Phase composition and catalytic performance of MoVTeNb oxide catalyst