

BIBLIOGRAPHY

- B Miller (2000). Rationale and challenges for optical interconnects to electronic chips. *Proc. IEEE*, vol. 88, no. 6, pp. 728–749.
- Banerjee, J. Drake, J. P. Lang, & B. Turner (2001). Generalized multiprotocol label switching: an overview of routing and management enhancements. *IEEE Comm. Mag.*, pp. 144-150.
- B. Dai, & X. Wang (2010). Security improvement using $\pm\pi/2$ -phase-shifted SSFBG en/decoder in time-spreading OCDMA. *Photon. Tech. Lett.*, vol. 22, pp. 881–883.
- B. Djordjevic, B. Vasic, & J. Rorison (2004). Multi weight unipolar codes for spectral-amplitude coding optical CDMA systems. *IEEE Comm. Lett.*, vol. 8, pp. 259-261.
- B. Miller (2009). Device requirements for optical interconnects to silicon chips. *Proceeding IEEE*, vol. 97, no. 7, pp. 1166–1185.
- B. Mukherjee (2000). WDM optical communication networks: progress and challenges. *IEEE J. Select. Areas Commun.*, vol. 18, pp. 1810–1824.
- Baliga, R. Ayre, K. Hinton, & R. S. Tucker (2007). Photonic switching and the energy bottleneck. *Photonic Switching*, San Francisco, CA.
- Bannister, J. Touch, P. Kamath, & A. Patel (2001). An optical booster for Internet routers. *Proc. 8th Int'l IEEE/ACM Conf. High Perform. Comput.*, pp. 339–413.
- Benner, M. Ignatowski, J. A. Kash, D. M. Kuchta, & M. B. Ritter (2005). Exploitation of optical interconnects in future server architectures. *IBM Journal. Res. Dev.*, vol. 49.
- Biberman, B. G. Lee, N. Sherwood-Droz, M. Lipson, & K. Bergman (2010). Broadband operation of nano photonic router for silicon photonic networks-on-chip. *IEEE Photon. Technol. Lett.* 22, 926–928.

- Biberman, H. L. R. Lira, K. Padmaraju, N. Ophir, M. Lipson, & K. Bergman (2010). Broadband CMOS-compatible silicon photonic electro-optic switch for photonic networks-on-chip. *Proc. Conf. Lasers and Electro-Optics*.
- C. Lam (2000), To spread or not to spread: The myths of optical CDMA. *IEEE Lasers and Electro-Optics Society Annual Meeting*, vol. 2, 2000, pp. 810–811.
- Chaskar et al. (2000). A framework to support IP over WDM using optical burst switching. *Workshop of Optical Networking*, Dallas.
- Cheng-Mu Tsai, & Tsair-Chun Liang (2011). Performance analysis of wavelength/spatial coding system with fixed in-phase code matrices in OCDMA network. *Optics Comm.*, Elsevier, 5572–5577.
- Cianfrani, V. Eramo, A. Germoni, C. Raffaelli, & M. Savi (2009). Loss analysis of multiple service classes shared-per-wavelength optical packet switches. *IEEE J. Opt. Commun. Netw.*, vol. 1, no. 2, pp. A69–A80.
- D. Benhaddou, A. Al-Fuqaha, & G. Chaudhry (2001). New multiprotocol WDM/CDMA-based optical switch architecture. *Proceeding 34th Annu. Simulation Symp*, pp. 285–291.
- D. Blumenthal, P. Prucnal, & J. Sauer (2000). Photonic packet switches: architectures and experimental implementations. *Proc. IEEE*, vol. 82, no. 11, pp. 1650–1667.
- D. Chiaroni (2001). Status and applications of optical packet switching. *27th European Conference on Optical Communication ECOC*, vol. 5, pp.126-162.
- D. Chiaroni (2003). Packet switching matrix: A key element for the backbone and the metro. *IEEE Journal Sel. Areas Commun.*, vol. 21, no. 7, pp. 1018–1025.
- D. K. Hunter, & I. Andonovic (2000). Approaches to optical internet packet switching. *IEEE Commun. Mag.*, vol. 38, no. 9, pp. 116–122.

- D. Klionidis, C. Politi, M. O'Mahony, & D. Simeonidou (2004). Fast and widely tunable optical packet switching scheme based on tunable laser and dual pump four-wave mixing. *IEEE Photon. Technol. Lett.*, vol. 16, no. 5, pp. 1412–1414.
- D. Klionidis, C. T. Politi, R. Nejabati, M. J. O'Mahony, & D. Simeonidou (2005). OPSnet: design and demonstration of an asynchronous high-speed optical packet switch. *Journal Lightwave Technol.*, vol. 23, no. 10, pp. 2914–2925.
- D. Wischik (2006). Fairness, QoS, and buffer sizing. *Comput. Commun. Rev.*, vol. 36, pp. 93–93.
- Dhamdhere, & C. Dovrolis (2006). Open issues in router buffer sizing. *Comput. Commun. Rev.*, vol. 36, pp. 87–92.
- Dinesh A. (2011). Effect of effective refractive index of grating in FBG splitter. Vol. 3, No. 9, *IJEST*.
- E. F. Burmeister, J. P. Mack, H.N. Poulsen, M. L. Masanovic, B. Stamenic, D. J. Blumenthal, & J. E. Bowers (2009). Photonic integrated circuit optical buffer for packet-switched networks. *Optical Express*, vol. 17, pp. 6629–6635.
- E. I. Babekir, N. M. Saad, N. Elfadel, A. Mohammed, A. A. Aziz, M. S. Anuar, S. A. Alijunid, & M. K. Abdullah (2007). Study of optical spectral CDMA zero cross correlation codes. *IJCSNS*, Vol. 7, No. 7.
- F. R. K. Chung, J. A. Salehi, & V. K. Wei (1989). Optical orthogonal codes: Design, analysis, and applications. *IEEE Trans. Inform. Theory*, vol. IT-35, pp. 595-604.
- G. Appenzeller, I. Keslassy, & N. McKeown (2004). Sizing router buffers. *Comput. Commun. Rev.*, vol. 34, pp. 281–292.
- G. Cincotti, N. Wada, S. Yoshima, N. Kataoka, & K. Kitayama (2006). 200 Gchip/s, 16-label simultaneous multiple-optical encoded decoder and its application to optical packet switching. *Optical Fiber Commun Conference.*, Anaheim, USA.

- G. I. Papadimitriou, C. Papazoglou, & A. S. Pomportsis (2003). Optical switching: switch fabrics, techniques, and architecture. *IEEE J. Lightwave Technol.*, Vol. 21, No. 2, pp. 384-405.
- G. Lee, A. Biberman, A. C. Turner-Foster, M. A. Foster, M. Lipson, L. Gaeta, & K. Bergman (2009). Demonstration of broadband wavelength conversion at 40 Gb/s in silicon waveguides. *IEEE Photon. Technol. Lett.*, vol. 21, no. 3, pp. 182–184.
- G. Lee, A. Biberman, N. Sherwood-Droz, C. B. Poitras, M. Lipson, & K. Bergman (2009). High-speed 2×2 switch for multi wavelength silicon photonic networks-on-chip. *Journal of Lightwave Technol.* 27, 2900–2907.
- G. Lee, A. Biberman, P. Dong, M. Lipson, & K. Bergman (2008). All optical comb switch for multi wavelength message routing in silicon photonic networks. *IEEE Photon. Technol. Lett.*, 767–769.
- G. K. Chung, K. I. Sato, & D. K. Hunter (2000). Special issue on optical networks. *Journal of Lightwave Technology*.
- Gunn (2006). CMOS photonics for high speed interconnects. *Proc. ECS 210th Meeting*, pp. 58–66.
- Haji Mohsin (2012). Optical code division multiple access systems in AlGaInAs/InP. *Thesis PhD*, University of Glasgow.
- H. J. Chao (2000). Saturn, A Terabit packet switch using dual Round-Robin. *Proceeding IEEE Communication Magazine*, vol. 38, no. 12, pp. 78-84.
- H. J. Chao (2002). Next generation routers. *IEEE Proceeding*, vol. 90, no. 9, pp. 1518-1558, Sep. 2002.
- H. J. Chao, & X. Guo (2001). Quality of service control in high-speed networks. John Wiley & Sons, Inc.

- H. J. Chao (2000). A Terabit IP switch router using optoelectronic technology. *IEEE Communications Magazine*, pp. 78-84.
- H. J. Chao, K-L. Deng, & Z. Jing (2003). A Petabit photonic packet switch. *IEEE INFOCOM*, San Francisco.
- H. J. Yang, & S. J. B. Yoo (2005). All-optical variable buffering strategies and switch fabric, architectures for future all-optical data routers. *Journal of Lightwave Technol.*, vol. 23, no. 10, pp. 3321–3330.
- H. S. Chung, R. Inohara, K. Nishimura, & M. Usami (2005). All-optical multi wavelength conversion of 10 Gbit/s NRZ/RZ signals based on SOA-MZI for WDM multicasting. *Electron. Lett.*, vol. 41, no. 7, pp. 432–433.
- H. Yang, H. Junqiang, P. Zhong, X. Fei, & S. J. B. Yoo (2004). An asynchronous, variable length two-stage packet switch fabric architecture with look-ahead and load-balance scheduling schemes for optical-label switching networks. *Proc. IEEE Global Telecommun. Conf., Piscataway, NJ*, vol. 3, pp. 1828–1834.
- H. Yang, V. Akella, C. N. Chuah, & S. J. B. Yoo (2005). Scheduling optical packets in wavelength, time, and space domains for all-optical packet switching routers. *Proceeding IEEE Int. Conf. Commun. Piscataway, NJ*, vol. 3, pp. 1836–1842.
- H. Zang, J. P. Jue, & B. Mukherjee (2000). A review of routing and wavelength assignment approaches for wavelength-routed optical WDM networks. *Optical Networks*.
- Himanshu M., & R.S. Kaler (2011). Performance analysis and improvement of spectrally amplitude encoded/decoded OCDMA system. *Optik*, Elsevier, 2006–2010.
- J. Blanton, H. Badt, G. Damm, & P. Golla (2001). Iterative scheduling algorithms for optical packet switches. *ICC 2001 Workshop*, Helsinki.
- J. Buus, & E. J. Murphy (2006). Tunable lasers in optical networks. *Journal Lightwave Technol.*, vol. 24, no. 1, pp. 5–11.

- J. Chabarek, J. Sommers, P. Barford, C. Estan, D. Tsiang, & S. Wright (2008). Power awareness in network design and routing. *Proceeding IEEE INFOCOM*, pp. 457–465.
- J. Chan, G. Hendry, A. Biberman, & K. Bergman (2010). Architectural exploration of chip-scale photonic interconnection network designs using physical-layer analysis. *Journal of Lightwave Technol.* 28, 1305–1315.
- J. Chao (2000). *A terabit IP switch router using optoelectronic technology*. IEEE Communications Magazine, pp. 78-84.
- J. Chao, C. Lam, & E. Oki, Broadband Packet Switching Technologies (2001). A Practical Guide to ATM Switches and IP Routers. *John Wiley & Sons, Inc.*
- J. J. V. Olmos, I. T. Monroy, Y. Liu, M. G. Larrode, J. Turkiewicz, H. J. S. Dorren, & A.M. J. Koonen (2004). Asynchronous, self-controlled, all optical label and payload separator using nonlinear polarization rotation in a semiconductor optical amplifier. *Opt. Exp.*, vol. 12, pp. 4214–4219.
- J. J. V. Olmos, J. Zhang, P. V. Holm-Nielsen, I. T. Monroy, V. Polo, A. M. J. Koonen, C. Peucheret, & J. Prat (2004). Simultaneous optical label erasure and insertion in a single wavelength conversion stage of combined FSK/IM modulated signals. *IEEE Photon. Technol. Lett.*, vol. 16, no. 9, pp. 2144–2146.
- J. P. Mack, H. N. Poulsen, & D. J. Blumental (2008). Variable length optical packet synchronizer. *IEEE Photon. Technol. Lett.*, vol. 20, no. 14, pp. 1252–1254.
- J. Salehi (1989). Code division multiple-access techniques in optical fiber networks - Part 1: fundamental principles. *IEEE Transactions on Communications*, vol. 37, no. 8, pp. 824–833.
- J. Salehi, & C. Brakett (1989). Code division multiple-access techniques in optical fiber networks - Part 2: systems performance analysis. *IEEE Transactions on Communications*, vol. 37, no. 8, pp. 834–842.

- Karl Dexter (2010). Noise suppression in OCDMA networks using nonlinear optical Devices. *Thesis PhD*, DCU.
- K. Hinton, G. Rakutti, P. Farrel, & R. S. Tucker (2008). Switching energy and device size limits on digital photonic signal processing technologies. *IEEE J. Sel. Top. Quantum Electron.*, vol. 14, no. 3, pp. 938–945.
- K. J. Christensen, C. Gunaratne, B. Nordman, & A.D.George (2004). The next frontier for communications networks: Power management. *Computer. Communication*, vol. 27, pp. 1758–1770.
- K. Kitayama, N. Wada, & H. Sotobayashi (2000). Architectural considerations for photonic IP router based upon optical code correlation. *Journal of Lightwave Technol.*, vol. 18, pp. 1834–1844.
- K. Kodi, & A. Louri (2006). Rapid for high-performance computing: Architecture and performance evaluation. *OSA Appl. Opt.*, vol. 45, pp. 6326–6334.
- K. Onohara, K. Kitayama, & N. Wada (2004). Photonic MPLS internetworking using an optical code label stack. *Photonic Netw. Commun.*, vol. 8, no. 3, pp. 341–350.
- K. Zhu, & B. Mukherjee (2002). Traffic grooming in optical WDM mesh networks. *IEEE J. Sel. Areas Commun.*, vol. 20, no. 1, pp. 122–133.
- K. D. Langer, J.Vathke, K.Habel, & C.Arellano (2006). Recent developments in WDM-PON technology. *Proc. ICTON*.
- Lin Lu, Weilei Wu, Hui Peng, Tao Pu, & Yuquan Li (2007). 2.5 Gbps 60 km OCDMA Transmission Experiment Using EPS-SSFBG En/decoder. *AOE*, 103-105.
- L.P. Barry, K. Bondarczuk, K. J. Dexter, P.J. Maguire, & D.A. Reid (2008). All Optical Pulse Processing for Advanced Photonic Communication System. *ICTON*.
- Md. Jahedul I, & Md. Rafiqul I. (2012). The BER performance improvement of optical CDMA using FBG-based compensator. *Procedia Engineering*, 821 – 827, Elsevier.

- M. Gagnaire, M. Koubaa, & N. Puech (2007). Network dimensioning under scheduled and random lightpath demands in all-optical WDM networks. *IEEE J. Sel. Areas Commun.*, vol. 25, no. 9, pp. 58–67.
- M. Gupta, & S. Singh (2003). Greening of the internet. *Proceeding ACM SIGCOMM*, pp. 19–26. 2003.
- M. J. O’Mahony, D. Simeonidou, D. K. Hunter, & A. Tzanakaki (2001). The application of optical packet switching in future communication networks. *IEEE Commun. Mag.*, vol. 39, pp. 128–135.
- M. Murata, & K. Kitayama (2001). A perspective on photonic multiprotocol label switching. *IEEE Network*, vol. 15, pp. 56–63.
- M. R. Watts, D. C. Trotter, & R. W. Young (2008). Maximally confined high-speed second-order silicon micro disk switches. *Proc. Optical Fiber Communications Conf.*
- M. Yamada, T. Yazaki, N. Matsuyama, & T. Hayashi (2009). Power efficient approach and performance control for routers. *Proc. IEEE International Conference Communication Workshops*, pp. 1–5.
- M.S. Anuar, S.A. Aljunid, N.M. Saad, & S.M. Hamzah (2009). New design of spectral amplitude coding in OCDMA with zero cross-correlation. *Optics Communications*, Elsevier.
- M. S. Anuar, S.A. Aljunid, R. Badlishah, N.M. Saad, & I. Andonovic (2007). Performance analysis of optical zero cross correlation in OCDMA system. *Journal of Applied Sciences*, 3819-3822.
- Moritsuka, N. Wada, T. Sakamoto, T. Kawanishi, Y. Komai, S. Anzai, M. Izutsu, & K. Kodate (2007). Multiple optical code-label processing using multi-wavelength frequency comb generator and multi-port optical spectrum synthesizer. *Optical Express*, 7515-7521.

- N. Ahmed, S.A. Aljunid, A. Fadil, R.B. Ahmad, M.A. Rashid (2012). Performance enhancement of OCDMA system using NAND detection with modified double weight (MDW) code for optical access network. *Optik*, Elsevier.
- N. Chi, L. Xu, L. Christiansen, K. Yvind, J. Zhang, P. Holm-Nielsen, C. Peucheret, C. Zhang, & P. Jeppesen (2003). Optical label swapping and packet transmission based on ASK/DPSK orthogonal modulation format in IP-over-WDM networks. *Proceeding Opt. Fiber Commun. Conf., Washington, DC*, vol. 2.
- N. Golmie, T. D. Ndousse, & D.H. Su (2000). A differentiated optical services model for WDM networks. *IEEE Communication Magazine*, pp. 68–73.
- N. H. Sun, & J. J. Liao (2009). Numerical analysis of apodized fiber bragg grating using coupled mode theory. *PIER* 99, 289-306.
- N. Kataoka, N. Wada, G. Cincotti, K. Kitayama, & T. Miyazaki (2007). A novel multiplexed optical code label processing with huge number of address entry for scalable optical packet switched network. *Proc. 33th Eur. Conf. Optical Communication*, Berlin, Germany.
- N. Wada, H. Harai, & W. Chujo (2002). Multi-hop, 40 Gbit/s variable length photonic packet routing based on multi-wavelength label switching, waveband routing and label swapping. *Proc. Opt. Fiber Commun. Conf. Washington, DC*, vol. 1, pp. 216–217.
- N. Wada, W. Chujo, & K. Kitayama (2001). 1.28 Tbit/s throughput variable length packet switching using optical code based label switch. *Proc. 27th Eur. Conf. Opt. Commun. IEEE*, vol.6, Piscataway, NJ, vol. 6, pp. 62–63.
- Nag., M. Tornatore (2008). Transparent optical network design with mixed line rates. *Proceeding IEEE Adv. Netw. Telecommu. Syst.*, pp. 1–3.
- O. Gerstel, B. Li, A. McGuire, G. N. Rouskas, K. Sivalingam, & Z. Zhang (2000). Special issue on protocols and architectures for next generation optical WDM networks. *IEEE Journal Selected Areas in Communications*.

- Okada (2002). All-optical packet routing in AWG-based wavelength routing networks using an out-of-band optical label. *Optical Fiber Commun. Conf.*, vol. 1, pp. 213–215.
- Okada, H. Tanobe, & M. Matsuoka (2005). Reconfigurable information sharing network system based on a cyclic-frequency AWG and wavelength-tunable lasers. *IEICE Trans. Commun.*, vol. E88B, pp. 2449–2455.
- P. C. Teh (2003). Application of Superstructure Fiber Bragg Grating for Optical Code Division Multiple Access and Packet Switched Networks. *Thesis PhD*. SOTON.
- P. C. Teh, P. Petropoulos, M. Ibsen, & D. J. Richardson (2001). A comparative study of the performance of seven and 63-chip optical code division multiple-access encoders and decoders based on super structured fiber Bragg gratings. *Journal of Lightwave Technol.* 19, 1352–1365.
- P. Kamath, J. D. Touch, & J. A. Bannister (2004). The need for media access control in optical CDMA networks. *IEEE Infocom*, vol. 4, pp. 2208–2219.
- P. Krishnamurthy, R. Chamberlain, & M. Franklin (2003). Dynamic reconfiguration of an optical interconnect. *Proceeding 36th Annu. Simul. Symp.*
- P. Petropoulos, M. Ibsen, A. D. Ellis, & D. J. Richardson (2001). Rectangular pulse generation based on pulse reshaping using a super structured fiber Bragg grating. *J. Lightwave Technol.*, vol. 19, pp. 746–752.
- P. R. Prucnal, M. A. Santoro, & T. R. Fan (1986). Spread spectrum fiber-optic local area network using optical processing. *J. Lightwave Technol.*, vol. LT-4, pp. 547–554.
- P. Seddighian, S. Ayotte, J. B. Rosas-Fernández, J. Penon, L. A. Rusch, & S. LaRochelle (2007). Label stacking in photonic packet-switched networks with spectral amplitude code labels. *Journal of Lightwave Technol.* 25, 463–471.
- Q. Xu, S. Manipatruni, B. Schmidt, J. Shakya, & M. Lipson (2007). 12.5 Gbit/s carrier-injection-based silicon micro-ring silicon modulators. *Optical Express* 15, 430–436.

- Ralf H., & Christoph L. (2010). Topology analysis of the access/aggregation network structure in future optical access networks. *Photonische Netze*, Leipzig, Paper 11.
- Rocío B., Daniel P., Waldimar A., & Victor G. (2012). Chromatic dispersion compensation and coherent direct sequence OCDMA operation on a single super structured FBG. *Optic Express*. Vol. 20, No. 13.
- R. S. Tucker (2006). The role of optics and electronics in high-capacity routers. *Journal of Lightwave Technol.*, vol. 24, no. 12, pp. 4655–4673.
- R. S. Tucker, K. Hinton, & G. Raskutti (2007). Energy consumption limits in high-speed optical and electronic signal processing. *Electron. Lett.*, vol. 43, pp. 906–908.
- R. S. Tucker, R. Parthiban, J. Baliga, K. Hinton, R. W. A. Ayre, & W. V. Sorin (2009). Evolution of WDM optical IP networks: A cost and energy perspective. *Journal of Lightwave Technol.*, vol. 27, no. 3, pp. 243–252, Jan./Feb. 2009.
- R. Takahashi, & H. Suzuki (2003). 1-Tb/s 16-b all-optical serial-to-parallel conversion using a surface-reflection optical switch. *IEEE Photon. Technol. Letter*, vol. 15, no. 2, pp. 287–289.
- R. Takahashi, R. Urata, H. Takenouchi, & T. Nakahara (2009). Hybrid optoelectronic router for asynchronous optical packets. *Proceeding Int. Conf. Photon. Switching*, pp. 1–2.
- R. Takahashi, T. Nakahara, H. Takenouchi, & H. Suzuki (2004). 40-Gbit/s label recognition and 1×4 self-routing using self-serial-to-parallel conversion. *IEEE Photon. Technol. Lett.*, vol. 16, no. 2, pp. 692–694.
- R. Takahashi, T. Nakahara, K. Takahata, H. Takenouchi, T. Yasui, N. Kondo, & H. Suzuki (2004). Photonic random access memory for 40-Gb/s 16-b burst optical packets. *IEEE Photon. Technol. Lett.*, vol. 16, no. 4, pp. 1185–1187.

- R. Takahashi, T. Nakahara, K. Takahata, H. Takenouchi, T. Yasui, N. Kondo, & H. Suzuki (2004). Ultrafast optoelectronic packet processing for asynchronous, optical-packet-switched networks. *Journal of Opt. Networking*, vol. 3, pp. 914–930, Dec.
- Salehi, J. A, (1989). Emerging Optical Code-Division Multiple Access Communications Systems. *IEEE Network Magazine*, Vol. 1, No. 2, 31-39.
- Salehi, J. A., Weiner, A. M., Heritage, J. P (1990). Coherent Ultra short Light Pulse Code-Division Multiple Access Communication Systems. *Journal of Light wave Technology*, Vol. 8, 478–491.
- R. Tucker (2006). The role of optics and electronics in high-capacity routers. *IEEE/OSA J. Lightw. Technol.*, vol. 24, no. 12, pp. 4655–4673.
- S. Aleksic (2009). Analysis of power in future high capacity network nodes. *Journal Commun. Netw.*, vol. 1, no. 3, pp. 245–258.
- S. A. Aljunid, M. Ismail, A.R. Ramli, Borhanuddin M. A, & M.K. Abdullah (2004). A new family of optical code sequences for spectral amplitude coding optical CDMA Systems. *IEEE Photonics Technology Lett.*, vol. 16, No. 10.
- S. A. Aljunid (2005). Development and implementation of a novel optical code division multiplexing technique for metropolitan area network. *Thesis PhD*, UPM.
- S. Huang, B. Mukherjee, & C. Martel (2008). Survivable multipath provisioning with differential delay constraint in telecom mesh networks. *Proceeding IEEE INFOCOM*, pp. 718–725.
- S. Iyer, R. Zhang, & N. McKeown (2002). Routers with a single stage of buffering. *Computer. Communication. Rev.*, vol. 32, pp. 251–264.
- S. J. B. Yoo, F. Xue, Y. Bansal, J. Taylor, Z. Pan, J. Cao, M. Jeon, T. Nady, G. Goncher, K. Boyer, K. Okamoto, S. Kamei, & V. Akella (2003). High-performance optical-label switching packet routers and smart edge routers for the next-generation Internet. *IEEE Journal Sel. Areas Commun.*, vol. 21, no. 7, pp. 1041–1051.

- S. J. Ben Yoo (2006). Optical packet and burst switching technologies for the future photonic internet. *Journal of Lightwave Technol.* 24, 4468–4492.
- S. J. B. Yoo, H. J. Lee, Z. Pan, J. Cao, Y. Zhang, K. Okamoto, & S. Kamei (2002). Rapidly switching all-optical packet routing system with optical-label swapping incorporating tunable wavelength conversion and a uniform loss cyclic frequency AWGR. *IEEE Photon. Technol. Lett.*, vol. 14, no. 8, pp. 1211–1213.
- S. Xiao, Q. Zeng, J. Wang, J. Xu, & Y. Wang (2003). Realization of multi wavelength label optical packet switching. *IEEE Photonic Technol. Lett.*, Vol. 15, No. 4, pp. 605-607.
- S. Yao, B. Mukherjee, & S. Dixit (2000). Asynchronous optical packet-switched networks: a preliminary study of contention resolutions. *Proceedings of Optical Network Workshop*, Dallas.
- S. Yoshima, K. Onohara, N. Wada, F. Kubota, & K. Kitayama (2006). Multicast-capable optical code label switching and its experimental demonstration. *Journal of Lightwave Technol.* 24, 713–722.
- Shacham, B. Small, O. Liboiron L., & K. Bergman (2005). A fully implemented 12×12 data vortex optical packet switching interconnection network. *Journal of Lightwave Technol.*, vol. 23, no. 10, pp. 3066–3075.
- Shun Yao, Sudhir Dixit, & Biswanath Muthurjee (2000). Advances in photonic packet switching: an overview. *IEEE Communications Magazine*, Vol. 38, No.2, pp.84-94.
- Special issue on protocols and architectures for next-generation optical WDM networks (2000). *IEEE J. Select. Areas Commun.*, vol. 18, Oct. 2000.
- Thanaa H. A., S. A. Aljunid, Hilal A. Fadhil, R. A. Ahmad, & N. M. Saad (2011). Development of a new code family based on SAC-OCDMA system with large cardinality for OCDMA network. *Optical Fiber Technology*. Elsevier.

- T. Koonen, G. Morthier, J. Jennen, H. deWaardt, & P. Demeester (2001). Optical packet routing in IP-over-WDM networks deploying two-level optical labeling. *Proceeding 27th Eur. Conf. Opt. Commun. IEEE*, vol.4, Piscataway, NJ, pp. 608–609, vol. 4.
- T. Monroy, J. J. V. Olmos, A. M. J. Koonen, F. M. Huijskens, H. de Waardt, & G. D. Khoe (2004). Optical label switching by using differential phase shift keying and in-band subcarrier multiplexing modulation format. *Opt. Eng.*, vol. 43, pp. 1476–1477.
- T. Nakahara, H. Takenouchi, R. Takahashi, K. Takahata, & H. Suzuki (2004). 32-bit label swapping of 40-Gbit/s burst optical packets with intensity tracking of input label. *30th Eur. Conf. Opt. Commun.*, Stockholm, Sweden.
- T. Sakamoto, A. Okada, M. Hirayama, Y. Sakai, O. Moriwaki, I. Ogawa, R. Sato, K. Noguchi, & M. Matsuoka (2002). Optical packet synchronizer using wavelength and space switching. *IEEE Photon. Technol. Lett.*, vol. 14, no. 9, pp. 1360–1362.
- T. Ye, L. Benini, & G. D. Micheli (2002). Analysis of power consumption on switch fabrics in network routers. *Proc. ACM/IEEE Des. Autom. Conf.*, August, pp. 524–529.
- V. Eramo (2010). Comparison in power consumption of synchronous and asynchronous optical packet switches. *Journal of Lightw. Technol.*, vol. 28, no. 5, pp. 847–857.
- V. Eramo, & M. Listanti (2000). Packet loss in a bufferless WDM switch employing shared tuneable wavelength converters. *Journal of Lightwave Technol.*, vol. 18, no. 12.
- V. Eramo, & M. Listanti (2009). Power consumption in bufferless optical packet switches in SOA technology. *Journal Commun. Netw.*, vol. 1, no. 3, pp. B15– B29.
- V. Eramo, A. Germoni, C. Raffaelli, & M. Savi (2008). Multifiber shared per- wavelength all-optical switching: Architectures, control, and performance. *Journal of Lightwave Technol.*, vol. 26, pp. 537–551.
- V. Eramo, A. Germoni, C. Raffaelli, & M. Savi (2008). Packet loss analysis of shared-per wavelength multi-fiber all-optical switch with parallel scheduling. *Elsevier Comput. Netw.*, vol. 53, pp. 202–216.

- V. Eramo, M. Listanti, & P. Pacifici (2003). A comparison study on the number on the number of wavelength converters needed in synchronous and asynchronous all-optical switching architectures. *Journal of Lightwave Technol.*, vol. 21, no. 2, pp. 340–355.
- V. Eramo, M. Listanti, C. Nuzman, & P. Whiting (2002). Optical switch dimensioning and the classical occupancy problem. *International Journal Commun. Syst.*, vol. 15.
- Vishav Jyoti, & R.S. Kaler (2011). Design and implementation of 2-dimensional wavelength/time codes for OCDMA. *Optik*, Elsevier, 851–857.
- W. D. Zhong, & R. S. Tucker (2001). A new wavelength-routed photonic packet buffer combining traveling delay lines with delay-line loops. *Journal Lightwave Technol.*, vol. 19, no. 10, pp. 1085–1092.
- W. Hung, K. Chan, L. K. Chen, C. K. Chan, & F. Tong (2002). A routing loop control scheme in optical layer for optical packet networks. *Conference Opt. Fiber Communication*.
- Waldimar A., Daniel P., Rocío B. & Victor G. (2011). Multi-channel en/decoding devices for WDM coherent direct sequence OCDMA applications based on super structured Fiber brag gratings. *ICTON*.
- X. Wang, & N. Wada (2006). Experimental demonstration of OCDMA traffic over optical packet switching network with hybrid PLC and SSFBG en/decoders. *Journal Lightwave Technol.* 24, 3012–3020.
- X. Wang, Naoya Wada & Kenich K. (2007). Multi-user asynchronous coherent OCDMA system. OSA.
- X. Wang, K. Matsushima, A. Nishiki, N. Wada, F. Kubota, & K. Kitayama (2005). High performance optical code generation and recognition using 511-chip 640 Gchip/s phase-shifted super structured FBG. *Optics Letters*, vol.30, pp. 355-357.

- X. Wang, Z. Gao, N. Kataoka, & N. Wada (2010). Time domain spectral phase encoding/DPSK data modulation using single phase modulator for OCDMA application. *Opt. Exp.*, vol. 18, no. 10, pp. 9879–9890.
- Xue, Z. Pan, H. Yang, J. Yang, J. Cao, K. Okamoto, S. Kamei, V. Akella, & S. J. B. Yoo (2004). Design and experimental demonstration of a variable-length optical packet routing system with unified contention resolution. *Journal Lightwave Technol.*, vol. 22, no. 11.
- Y. Li, S. S. Panwar, & H. J. Chao (2002). The dual Round Robin matching switch with exhaustive service. *Proc. IEEE HPSR*.
- Y. Liu, E. Tangdiongga, Z. Li, H. deWaardt, A.M. J. Koonen, G. D. Khoe, B. Xuewen, I. Shu, & H. J. S. Dorren (2007). Error-free 320-Gb/s all-optical wavelength conversion using a single semiconductor optical amplifier. *J. Lightw. Technol.*, vol. 25, no. 1, pp. 03–108.
- Y. Ueno, J. Sakaguchi, R. Nakamoto, & T. Nishida (2009). Ultrafast, low-energy-consumption, semiconductor-based, all-optical devices. *4th APMP*, Beijing, China.
- Yanan Cao, & Chaoqin Gan (2012). A scalable hybrid WDM/OCDMA-PON based on wavelength-locked RSOA Technology. *Optik*, Elsevier, 176– 180.
- Y. Zouine , I. Dayoub, S. Haxha, & J.M. Rouvaen (2008). Analyses of constraints on high speed optical code division multiplexing access (OCDMA) link parameters due to fiber optic chromatic dispersion. *Optics Communications*, Elsevier.
- Z. Pan, et al. (2002). All-optical programmable time-slot-interchanger using optical-label switching with tunable wavelength conversion and N by N arrayed waveguide grating routers. *Optical Fiber Commun. Conf., Washington, DC, Anaheim, CA*, vol. 1, pp. 267–268.
- Z. Si, F. Yin, M. Xin, H. Chen, M. Chen, & S. Xie (2010). Code extraction from encoded signal in time-spreading optical code division multiple access. *Opt. Lett.*, vol. 35, pp. 229–231.