

## List of Figures

	Page
<b>Figure 1.1:</b> Typical structure of (a) multilayer and (b) single-layer OLEDs. The organic active layer are consist of electron injection layer (EIL), electron transporting layer (ETL), emissive layer (EML), hole transporting layer (HTL) and hole injection layer (HIL). The arrow indicates the direction of light emission from the OLED devices.	3
<b>Figure 1.2:</b> Several commercialize device based on OLED technology	6
<b>Figure 1.3:</b> Flexible Active Matrix OLED (AMOLED)	8
<b>Figure 1.4:</b> Samsung AMOLED laptop with transparent display	8
<b>Figure 1.5:</b> Comparison of image destruction between other display and OLED display	8
<b>Figure 1.6:</b> OLED Lighting Manufacturing Participant Roadmap	9
<b>Figure 1.7:</b> Research flow for this work	12
<b>Figure 2.1:</b> Typical molecular structure of polymers (top) and small molecules (bottom) used in organic electronic devices.	17
<b>Figure 2.2:</b> Molecular structure of benzene and its orbitals system	18
<b>Figure 2.3:</b> Franck-Condon transitions	20
<b>Figure 2.4:</b> Energy diagram for singlet and triplet excited state	22
<b>Figure 2.5:</b> Schematic diagram of electroluminescence mechanism in organic device where 1) injection, 2) transportation, 3) recombination, and 4) emission process.	26
<b>Figure 2.6:</b> Comparison of thermionic injection and F-N tunneling mechanisms. $\Phi$ hole and $\Phi$ electron are energy barrier for hole and electron injection, respectively.	29
<b>Figure 2.7:</b> Equivalent circuit of impedance in space-charge-limited-current condition in organic semiconductor.	37
<b>Figure 2.8:</b> Molecular structure of organic materials used in this work	39
<b>Figure 3.1:</b> Diagram of patterned ITO	49
<b>Figure 3.2:</b> Laurell WS-400B-6NPP/LITE spin coater system	51

<b>Figure 3.3:</b>	Thin film fabrication processes using spin coating technique	52
<b>Figure 3.4:</b>	OLED fabrication processes	53
<b>Figure 3.5:</b>	Typical thermal evaporation deposition system	55
<b>Figure 3.6:</b>	Typical construction of layers of OLED devices fabricated in this work. (a) side view and (b) top view of the fabricated OLED device.	55
<b>Figure 3.7:</b>	Schematic diagram of optical path in FTIR measurement	56
<b>Figure 3.8:</b>	Light path of the UV-Vis-NIR spectrometer	59
<b>Figure 3.9:</b>	Optical path of photoluminescence spectrometer	62
<b>Figure 3.10:</b>	Typical measurement of thickness using step height difference method.	63
<b>Figure 3.11:</b>	(a) Konica Minolta CS-200 and (b) experimental setup for electrical and luminescence characteristic of the device.	66
<b>Figure 3.12:</b>	Schematic diagram of the device holder.	67
<b>Figure 4.1:</b>	Molecular structure of Alq <sub>3</sub> used in this work	71
<b>Figure 4.2:</b>	Schematic structure of a single layer Alq <sub>3</sub> based OLED fabricated in this work.	72
<b>Figure 4.3:</b>	FTIR transmittance spectrum of Alq <sub>3</sub> thin film	73
<b>Figure 4.4:</b>	XRD pattern of Alq <sub>3</sub> thin film	74
<b>Figure 4.5:</b>	Normalized UV-Vis absorption spectra of Alq <sub>3</sub> thin film	75
<b>Figure 4.6:</b>	Tauc plot of Alq <sub>3</sub> thin film	76
<b>Figure 4.7:</b>	Typical molecular orbital level of Alq <sub>3</sub>	77
<b>Figure 4.8:</b>	Normalized photoluminescence spectra of Alq <sub>3</sub> thin film	78
<b>Figure 4.9:</b>	Current density -voltage-luminance ( <i>J-V-L</i> ) relationship of the Alq <sub>3</sub> based OLED	80
<b>Figure 4.10:</b>	F-N plot of Alq <sub>3</sub> -OLED	80
<b>Figure 4.11:</b>	Log <i>J</i> -Log <i>V</i> plot of the Alq <sub>3</sub> based OLED	81
<b>Figure 4.12:</b>	Dependency of current efficiency with driven voltage of the Alq <sub>3</sub> based OLED	82
<b>Figure 4.13:</b>	Impedance Cole-Cole plots for Alq <sub>3</sub> OLED with different driven voltage. The insert show the plot at low impedance range.	84
<b>Figure 4.14:</b>	<i>Z</i>   versus frequency for Alq <sub>3</sub> OLED with different driven voltage	84

<b>Figure 4.15:</b>	Equivalent circuit of Alq <sub>3</sub> OLED	86
<b>Figure 4.16:</b>	Simulated of impedance data for Alq <sub>3</sub> device at different voltage. The insert shows the simulated result at low impedance range.	86
<b>Figure 4.17:</b>	(a) Frequency dependent real (circle) and imaginary (square box) part of the impedance of Alq <sub>3</sub> device. (b) Bias voltage dependence of the peak frequency and dielectric relaxation time.	88
<b>Figure 5.1:</b>	Normalized UV-Vis absorption of TPD and PBD in thin film form. The spectra were normalized with respect to the highest absorption intensity for each material.	97
<b>Figure 5.2:</b>	$(\alpha h\nu)^2$ vs E plot of TPD and PBD	98
<b>Figure 5.3:</b>	Molecular energy level of TPD and PBD	98
<b>Figure 5.4:</b>	Normalized PL spectra of TPD and PBD in thin film form excited at 280 nm excitation energy.	100
<b>Figure 5.5:</b>	FTIR spectrum of small molecules and their blends in the wavenumber range from 800 to 2000 cm <sup>-1</sup>	101
<b>Figure 5.6:</b>	XRD pattern of Alq <sub>3</sub> , TPD, PBD and blend of TPD:Alq <sub>3</sub> and TPD:PBD:Alq <sub>3</sub> in thin film form	102
<b>Figure 5.7:</b>	Normalized UV-Vis absorption of blend in thin film form	103
<b>Figure 5.8:</b>	$(\alpha h\nu)^2$ vs E plot of blend thin film	104
<b>Figure 5.9:</b>	PL intensity of blend in thin film form with excitation wavelength of 312 nm	105
<b>Figure 5.10:</b>	J-V characteristic of single layer OLED	107
<b>Figure 5.11:</b>	F-N plot for devices with different dopant system	107
<b>Figure 5.12:</b>	Log J-Log V plot of single layer OLED	109
<b>Figure 5.13:</b>	Schematic diagram of carrier pathways in TPD:PBD:Alq <sub>3</sub> OLED	110
<b>Figure 5.14:</b>	L-V characteristic of single layer OLED	112
<b>Figure 5.15:</b>	Luminance-current characteristic of single layer OLED	112
<b>Figure 5.16:</b>	CIE plot of single layer OLED	114
<b>Figure 5.17:</b>	Current efficiency-voltage plot of different blends OLED	114
<b>Figure 5.18:</b>	Impedance Cole-Cole plots for OLED fabricated with different blends system at (a) large and (b) smaller scale	116

<b>Figure 5.19:</b>	Simulated Cole-Cole plots of OLED device fabricated with different blends system at large (above) and low (below) impedance scales	118
<b>Figure 5.20:</b>	(a) Frequency dependent of real and imaginary part of the impedance and (b) relation between the resonance frequency and the relaxation time of OLED device fabricated with different blends system.	119
<b>Figure 6.1:</b>	FTIR spectrum of TPD:PBD:Alq <sub>3</sub> thin film with different annealing process at range of (a) 2000 to 800 cm <sup>-1</sup> , (b) 1400 to 1300 cm <sup>-1</sup> and (c) 1200 to 1000 cm <sup>-1</sup>	130
<b>Figure 6.2:</b>	XRD pattern of TPD:PBD:Alq <sub>3</sub> thin film with different annealing time	131
<b>Figure 6.3:</b>	UV-Vis absorption of blend thin film with different annealing time	133
<b>Figure 6.4:</b>	( $\alpha E$ ) <sup>2</sup> vs E plot of blend thin film at different annealing time	134
<b>Figure 6.5:</b>	PL of blend thin film with different annealing time with excitation wavelength of 312 nm.	135
<b>Figure 6.6:</b>	Absorption and PL intensity of annealed films with respect to annealing time.	135
<b>Figure 6.7:</b>	AFM images of blend thin film with different annealing time measured at 2000 nm (left) and 300 nm (right) heights	138
<b>Figure 6.8:</b>	Microscopic image of as-cast and annealed device at different annealing time	138
<b>Figure 6.9:</b>	Roughness and thickness of blend thin film with different annealing time	140
<b>Figure 6.10:</b>	J-V characteristic of blend thin film with different annealing time	141
<b>Figure 6.11:</b>	F-N plot of blend thin film with different annealing time	142
<b>Figure 6.12:</b>	Log J-Log V plot of single layer OLED annealed with various annealing time	144
<b>Figure 6.13:</b>	L-V characteristic of blend OLED with different annealing time	146
<b>Figure 6.14:</b>	Maximum luminance and current efficiency of single layer OLED with respect to annealing time	147

<b>Figure 6.15:</b>	CIE plot of the blend OLED with different annealing time	149
<b>Figure 6.16:</b>	L-J characteristic of the blend OLED with different annealing time	149

## List of Tables

	Page
<b>Table 3.1:</b> Summary of solution preparation parameters	50
<b>Table 3.2:</b> Parameter of the FTIR measurement	57
<b>Table 3.3:</b> Setup of XRD measurement	57
<b>Table 3.4:</b> Scanning parameter for PL measurement	61
<b>Table 4.1:</b> Impedance parameter used to simulate the measured absolute impedance plot of Fig. 4.16	87
<b>Table 5.1:</b> Summary of optical and PL properties of blend film.	105
<b>Table 5.2:</b> Performance of single layer OLED	115
<b>Table 5.3:</b> Impedance parameter used to simulate the measured impedance plot of Fig. 5.19	120
<b>Table 6.1:</b> Thickness measured of annealed blend thin film.	132
<b>Table 6.2:</b> Performance of annealed blend OLED	148